US ERA ARCHIVE DOCUMENT

TECHNICAL GUIDANCE DOCUMENT



Indiana Department of Environmental Management

Ex-Situ Treatment of Dense Non-Aqueous Phase Liquids Using Calcium Oxide (Quick Lime)

www.idem.IN.gov

Mitchell E. Daniels, Jr. Governor

Thomas W. Easterly Commissioner

100 N. Ave., Indianapolis, IN 46204 Toll Free: (800) 451-6027

Guidance Created: February 10, 2009 Revised: November 17, 2009

Notice

The Technology Evaluation Work Group completed this evaluation of Ex-Situ Treatment of Dense Non-Aqueous Phase Liquids Using Calcium Oxide (Quick Lime) based on professional expertise and review of items listed in the "References" section of this document. The criteria for performing the evaluation are generally described in the IDEM OLQ technical memorandum, Submittal Guidance for Evaluation of Innovative Remediation Technologies.

This evaluation does not approve this technology nor does it verify its effectiveness in conditions not identified here. Mention of trade names or commercial products does not constitute endorsement or recommendation by the IDEM for use.

Background

Calcium Oxide (CaO, Quick Lime) is a white crystalline solid manufactured by heating limestone, dolomite, coral, oyster shells, or chalk (which are all mainly calcium carbonate, CaCO₃) to drive off carbon dioxide. Quick Lime is used in the construction industry for soil drying, modification, and stabilization. Quick Lime reacts with water to produce heat according to the following reaction:

$$CaO + H_2O \rightarrow Ca(OH)_2 + Heat$$

When applied to wet soils, the reaction consumes approximately 30% water by weight and provides dry solids for stability.

The case-study provided for review (Dean, 2003) discussed the use of Quick Lime for the ex-situ treatment of Dense, Non-Aqueous Phase Liquids (DNAPLs) - specifically TCE and 1,1,1 TCA – in soils at a site in Florida. The original plan for the site called for ex-situ vacuum extraction of all contaminated soils. Quick Lime was added to the soils at an approximate 5% ratio to improve the soil handling characteristics during removal. Project managers observed that the mixing with Quick Lime caused a reaction which



reduced contaminants to below the leachability soil cleanup target levels. Approximately 11,500 cubic yards of soil were eventually treated with Quick Lime and returned to the excavation after verification sample results showed treatment goals had been met.

One conclusion of the case-study is that Quick Lime may likewise be used effectively for treatment of DNAPLs in soils at other similar sites. After reviewing the case-study and consulting additional sources (listed in references section), the following summary comments were compiled.

Advantages

From an environmental standpoint, Quick Lime is benign. Quick Lime is frequently used in water treatment operations and in agriculture when pH control is needed.

Cost: For the Florida case-study provided, an estimated savings of \$2.5 - \$3 million was realized when compared to off-site transport and disposal. Quick Lime is not a specialty chemical, and is readily available and relatively easy to obtain and manage in bulk.

A study in the United Kingdom (Schifano, 2006) showed that "significant decreases in concentrations of petroleum hydrocarbon compounds were measured in soils and leachates upon quick lime mixing."

Physical properties of the soils are favorably changed by Quick Lime treatment in many cases. Lime reacts with medium, moderately fine and fine-grained soils to produce decreased plasticity, increased workability, reduced swelling, and increased strength.

The addition of Quick Lime may be used to adjust the pH of soils to a level where metals contaminants are least likely to leach. However, the long-term stability of this method and the effects of pH change by Quick Lime on the leachability of some metals are currently not well understood.

Limitations

Field demonstrations have not successfully identified the dominant mechanism responsible for the reduction in DNAPL concentrations in Quick Lime treated soils. Possible reactions include:

- Volatilization of the DNAPLs as a result of the increased temperature occurring during Quick Lime addition.
- Enhanced abiotic destruction of the chemicals resulting from an increase in temperature.
- Entrapment of the contaminants in the soil Ca(OH)₂ matrix.

Likewise, a United Kingdom study (Schifano, 2006) concluded:

 The increase in temperature due to the exothermic hydration reaction of quicklime when in contact with porewater helps to volatilize the light compounds but may not be entirely responsible for their concentration decreases and for the decrease of heavy aliphatics and aromatics concentrations.

Other unknowns are the resulting byproducts of conversion, their mobility and toxicity, the disposition of the treated soil for disposal, and the impacts of the treatment on the microbial populations present in the soil.

Due to the above unknowns, additional research is needed before Quick Lime treatment can be considered a reliable, cost-effective remediation process for soils.

Problems Encountered

No major problems encountered in references reviewed.

Safety Issues

Quick Lime will react with any moisture, including sweat, eyes and lung tissue, so adequate PPE is essential. Quick Lime is incompatible with many organics, halogens, acids, and combustible materials. Standard safety procedures should be applied.

<u>Indiana Case Studies (or use in similar environment)</u>

Quick Lime has been and is currently being used – either alone or in combination with other treatments – for treatment of DNAPLs and other contaminants in soils at Indiana sites. However, no detailed case studies for Indiana were available at the time this memorandum was prepared. Although the Florida case-study provided appeared to show that Quick Lime was useful for ex-situ treatment of DNAPLs at a particular site, it cannot be concluded that the treatment would work at a similar site in Indiana. The dominant mechanism for the reaction between Quick Lime and the contaminants has not been determined. Since Indiana site conditions may vary considerably from those at the Florida site, the effect of these variations on the treatment process cannot be accurately predicted.

Conclusion

Quick Lime appears to be an effective, low-cost product for ex-situ treatment of DNAPL contamination in soils. However, very few case-studies for this treatment process were available, and no Indiana case-studies were located. Additional research is needed to determine

- The dominant mechanism for contaminant reductions due to the treatment,
- A list of contaminants for which the treatment is effective.
- Necessary site conditions for the treatment to be effective,
- Appropriate and cost-effective mixing procedures and amounts of Quick Lime needed for treatment, and
- Regulatory guidance for post-treatment monitoring.

Until more information on this treatment has been evaluated, Quick Lime must be seen as experimental only.

Further Information

If you have any additional information regarding this technology or any questions about the evaluation, please contact Jim Risch, Environmental Chemist, at (317) 233-6541 or by e-mail at jrisch@idem.in.gov. This technical guidance document will be updated periodically or if new information is acquired.

References

Barnes, Curtis, Project Manager, 2005. "Evaluation of Quicklime Application as a Method of Treating Contaminated Soils," presented at The TRB Committee on Waste Management's Environmental Stewardship in transportation Through Waste Management, Materials Reuse and EMS Conference, July 18, 2005.

Dean, William Gordon, 2003. "Ex-Situ Treatment of Dense Non-Aqueous Phase Liquids Using Calcium Oxide (Quick Lime)," presented at 19th Annual Conference on Soils, Sediments and Water, October 20-23, 2003.

Marion, Giles M., *et al*, 1997. "Site Remediation via Dispersion by Chemical Reaction (DCR)," U.S. Army Corps of Engineers, Cold Regions Research & Engineering Laboratory, Special Report 97-18.

Medina, Victor F., et al, 2007. "Evaluation of Lime and Persulfate treatment of Mixed Contaminant Soil from Plum Brook Ordnance Works (Sandusky, Ohio)," U.S. Army Corps of Engineers, Engineer Research and Development Center, Environmental Laboratory, September 2007.

Office of Geotechnical Engineering, 2008. "Design Procedures for Soil Modification or Stabilization," Indiana Department of Transportation, January 2008, available at: http://www.in.gov/indot/files/smod.pdf.

Robinson, David and Angyal, Gary, 2008. "Use of Mixed Technologies to Remediate Chlorinated DNAPL at a Brownfields Site," *Remediation Journal*, 18(3), 41-53. [Abstract Only]

Schifano, V., *et al*, 2006. "Evaluation of Quicklime Mixing for the Remediation of Petroleum Contaminated Soils," *Journal of Hazardous Materials*, 141(2): 395-409. [Abstract Only]

Williams, Susan, 2005. "The Uses of Lime in Site Preparation," *Utility Contractor*, July/Aug 2005, 22-23.

FIELD DEMONSTRATION REPORT

FOR THE

TREATMENT OF TCE IMPACTED SOILS
IN THE VADOSE AND PERCHED GROUNDWATER ZONES
AT THE FORMER IMPEX FACILITY
905 LOUISE STREET
CRAWFORDSVILLE, INDIANA 47933
IDEM VRP SITE NO. 6010902

PREPARED FOR

IMPEX REALTY HOLDING, INC. 5430 LBJ FREEWAY DALLAS, TEXAS 75240

PREPARED BY

ENTACT SERVICES LLC 3129 BASS PRO DRIVE GRAPEVINE, TEXAS 76051

MAY 23, 2008

TABLE OF CONTENTS

Sect	tion Pa	age
	Mobilization	
2.0	Site Preparation	1
3.0	Treatment and Excavation	2
4.0	Restoration	3
5.0	Results and Discussion	3
	5.1 Air Monitoring	3
	5.2 Soil Samples	3
6.0	Conclusions	4

List of Tables

Table 1 Personal Air Monitor Laboratory Analytical Results
 Table 2 Summa Canister Laboratory Analytical Results
 Table 3 Soil Laboratory Analytical Results

List of Figures

Figure 1 Field Demonstration Locations

List of Attachments

Attachment 1 Laboratory Analytical Reports

ENTACT performed a field demonstration on TCE-impacted soils in the vadose and perched groundwater zones at the Former Impex Facility to assess the effectiveness of using calcium oxide treatment to reduce TCE concentrations in the impacted upper silty clay present at the site. This field demonstration was conducted from March 6-28, 2008, pursuant to the requirements of the approved Field Demonstration Workplan dated December 5, 2007. The following paragraphs further describe the sequence and components of the field demonstration.

1.0 Mobilization

ENTACT mobilized the required personnel and equipment, e.g., hydraulic excavator with bucket and hammer attachments, a man-lift, water truck, and a box fan, to the site on March 6, 2008. Calcium oxide in the 3/8 inch minus pebble lime form was delivered to the site in 1-ton super sacks and was staged adjacent to the demonstration area on concrete.

2.0 Site Preparation

The field demonstration began at soil boring QB-88, where the highest TCE concentrations were expected at a depth of 0-2 feet below ground surface (bgs). This soil boring was located in the field based on the information provided in the site investigation reports and marked with spray paint. A 25 foot by 25 foot area centered on this soil boring was also marked with spray paint to indicate the extent of the demonstration area.

A 3.5 foot by 8 foot section of the composite wood roof above the center of the proposed excavation was cut using a sawzall, removed and lowered to the floor. A box fan was then installed in the space to facilitate ventilation during the field demonstration. The concrete slab in the 25 foot by 25 foot demonstration area was broken apart using a hydraulic excavator equipped with a concrete hammer. The broken concrete was removed and placed in a stockpile adjacent to the demonstration area under roof.

Background air monitoring was initiated on March 7, 2008, during the site preparation activities, at the site perimeter and near the proposed work zone. Summa canisters were placed on elevated surfaces at the site perimeter on the exterior of the east and west sides of the building. The personal dataRAMs (pDR) were placed inside and outside of the building with one pDR inside the north end of the building and one pDR outside the east side of the building. The personal air monitors were also placed inside and outside of the building with one personal air monitor in the field demonstration area and one personal air monitor outside the east side of the building. The exterior air monitoring locations were consistent with the predominant wind directions identified during the field demonstration. The summa canister samples and personal air monitoring samples were submitted to TestAmerica Laboratories, Inc. in Austin, Texas and TestAmerica Laboratories, Inc. in Phoenix, Arizona, respectively, for analysis of TCE, cis-1,2-DCE and vinyl chloride.

On March 7, 2008, a pre-treatment sample was collected from the exposed soils at soil boring QB-88 from a depth of 0 to 2 feet and submitted to TestAmerica Laboratories, Inc. in Corpus Christi, Texas for analysis of TCE, cis-1,2-DCE and vinyl chloride.

3.0 Excavation, Treatment and Sampling

On March 10, 2008, while awaiting the laboratory results for the pre-treatment sample, the exposed soils were stabilized with 1 ton of calcium oxide. The perched groundwater encountered in the excavation was used to augment the thermal reaction. Additional water was added as needed during treatment and for dust suppression purposes. The expected reaction typical of the mixture of calcium oxide and soil pore space water did not occur. It was later determined that the calcium oxide received at the site was not of appropriate quality. The results of the pre-treatment sample also indicated that TCE concentrations in the 0-2 foot soil horizon were less than indicated from the previous investigation. Since the calcium oxide that was used to stabilize the material did not meet the specifications, a post-treatment sample was not collected.

Based on the fact that the expected concentrations of TCE were not encountered in the soils underneath the building, e.g. 4,900 ug/kg TCE was detected where the previous investigation detected 530,000 ug/kg, ENTACT moved the field demonstration to an area located outside of the building on the west side where recent elevated TCE concentrations, 266,000 ug/kg, were known to exist at a depth of 18-20 feet below ground surface (Grid AB-23). On March 13, 2008, a 20 foot by 20 foot area in Grid AB-23 was excavated to a depth of 18 feet below ground surface. The overburden material was removed from the excavation and placed adjacent to the hole.

A pre-treatment sample was then collected from the exposed soils at a depth of approximately 18 feet below ground surface and submitted to Pace Analytical in Indianapolis, Indiana for analysis of TCE, cis-1,2-DCE and vinyl chloride. Shortly after sample collection, the 18 to 20 foot horizon was stabilized with approximately 5% calcium oxide by weight. The calcium oxide was thoroughly mixed with the soil using the bucket of a hydraulic excavator. The perched groundwater encountered in the excavation was used to augment the thermal reaction. Additional water was added as needed during treatment and for dust suppression purposes. After a period of 24 hours, on March 14, 2008, a post-treatment sample was collected from the stabilized soil and submitted to Pace Analytical for analysis of TCE, cis-1,2-DCE and vinyl chloride. The stabilized soils were then excavated and transferred to the building interior for temporary stockpiling on visqueen sheeting. An additional post-treatment sample was collected from the interior soil stockpile on March 28, 2008, after allowing additional time for cooling of the soils.

The interior stockpile was sampled on April 18, 2008 to further evaluate remedial progress in the the exterior former storage yard area. The samples were submitted for analysis of pH and TCE, cis-1,2-DCE and vinyl chloride using the synthetic precipitation leaching procedure (SPLP).

Air samples were also collected during the treatment effort on March 11 and 12, 2008 at the locations previously presented. All soil samples taken during the field demonstration were collected as grab samples using U.S. EPA Method 5035 and the Encore sampling device. Refer to Figure 1 for a depiction of the field demonstration locations.

4.0 Restoration

The initial treatment and excavation area located inside the building was backfilled with the stabilized soils and graded. The exterior excavation was backfilled with the overburden material initially removed from the excavation and any extra space was filled with locally imported stone material. The backfill soil/stone was placed in the excavation in horizontal lifts not exceeding 18 to 24 inches in thickness. Each lift was placed in the excavation, graded and compacted by mechanical means.

The section of the roof that was removed for the field demonstration was repaired at the completion of the field demonstration. Plywood wrapped in visqueen sheeting was used to patch the roof opening.

The work area was cleaned and all personnel, equipment and supplies were demobilized from the site on March 17, 2008.

5.0 Results and Discussion

5.1 Air Monitoring

Air monitoring was conducted during the field demonstration to determine background concentrations at and near the site and to determine if the potential exists for the treatment activities to impact workers and the surrounding community through fugitive dust emissions. Background samples were collected prior to the start of the treatment activities. These results showed non-detectable concentrations of TCE, cis-1,2-DCE and vinyl chloride for both the personal air monitoring samples and the perimeter summa canisters. Samples collected during the treatment activities showed non-detectable concentrations and minor detections for both the personal air monitoring samples and the perimeter summa canisters. The detectable results were compared to the OSHA permissible exposure levels (PEL) for each constituent of concern. The comparison showed that the detectable air monitoring results were well below the OSHA PELs for each constituent of concern. Therefore, the treatment of the TCE impacted soils at this site will not pose a risk to human health or the environment or the on-site workers or local residences.

The air monitoring results are included on Tables 1 and 2 and the locations of the air monitoring devices are depicted on Figure 1. Copies of the laboratory analytical reports are included in Attachment 1.

5.2 Soil Samples

Pre-treatment soil samples were collected from the identified locations to determine the TCE concentration in the impacted soil prior to treatment. The results of the pre-treatment soil samples from areas QB-88 and AB-23 indicated lower concentrations of TCE than were previously detected. Post-treatment soil samples were collected from the treated soil to show the effect of treatment with calcium oxide on the TCE concentrations in the impacted soil. The post-treatment sample results showed a significant decrease in the TCE concentration in the treated soils, an approximate 87% to 99% decrease. The results, therefore, indicate that the calcium

oxide treatment methodology produces acceptable results for the reuse of the treated soils as backfill at the site.

The March 28, 2008 post-treatment sample results also showed that the treatment methodology is more effective when the treated soils have cooled and the reaction has been completed. In an effort to shorten the curing time and allow the soils to cool completely prior to sampling, ENTACT proposes to spread the stockpile of treated soils after 24 hours to a uniform thickness. This will allow the treated soils to cool completely and achieve a • 10% moisture content before the material is sampled.

The April 18, 2008 post-treatment sample results show that the treated soil reached a pH of 7.9 within a 3 week period after treatment. We believe that the final pH will not have an adverse effect on the biological treatment activities currently being implemented at the downgradient enhanced reductive dechlorination (ERD) barrier system (presently operating in the deeper sand and gravel aquifer underlying the site). The SPLP results indicate that TCE was detected in the leachate at concentrations below the default soil migration to groundwater closure level and the groundwater default closure level for industrial sites. In addition, the movement of any potential TCE present in future leachate will be further attenuated by the compaction of the treated soils in the backfilled excavation.

The pre-treatment and post-treatment soil sample results are included on Table 3. Copies of the laboratory analytical reports are included in Attachment 1.

6.0 Conclusions

Based on the results of the field demonstration activities, we believe that the calcium oxide treatment methodology will be successful in treating the TCE-impacted soils in the vadose and shallow perched groundwater zones to concentrations that will allow the reuse of the soils as backfill at the site.

TABLE 1: PERSONAL AIR MONITOR LABORATORY ANALYTICAL RESULTS FORMER IMPEX FACILITY, CRAWFORDSVILLE, INDIANA

Sample ID No.	Sample Date	Lab Report No.	cis-1,2- DCE (ppm)	TCE (ppm)	Vinyl Chloride (ppm)
OSHA PEL			200	100	1
ENTACT Action Le	evels		100	50	0.5
AS-FD-P01 front	03/07/08	PRC1068	< 0.503	< 0.439	< 0.391
AS-FD-P02 front	03/07/08	PRC1068	< 0.503	< 0.439	< 0.391
AS-FD-PFB1	03/07/08	PRC1068	<9.98*	<11.8*	<5*
AS-FD-P01 back	03/07/08	PRC1068	NA	NA	< 0.391
AS-FD-P02 back	03/07/08	PRC1068	NA	NA	< 0.391
AS-FD-P03 front	03/11/08	PRC1068	5.15	0.841	< 0.391
AS-FD-P03 back	03/11/08	PRC1068	NA	NA	< 0.391
AS-FD-P04 front	03/11/08	PRC1068	< 0.503	< 0.439	< 0.391
AS-FD-P04 back	03/11/08	PRC1068	NA	NA	< 0.391
AS-FD-PFB2	03/11/08	PRC1068	<9.98*	<11.8*	<5*
AS-FD-P05 front	03/12/08	PRC1068	< 0.503	< 0.439	< 0.391
AS-FD-P05 back	03/12/08	PRC1068	NA	NA	< 0.391
AS-FD-P06 front	03/12/08	PRC1068	< 0.503	< 0.439	<0.391
AS-FD-P06 back	03/12/08	PRC1068	NA	NA	<0.391
AS-FD-PFB3	03/12/08	PRC1068	<9.98*	<11.8*	<5*

^{*}Total concentration in ug not considering flow rates, etc. for field blank purposes

TABLE 2: SUMMA CANISTER LABORATORY ANALYTICAL RESULTS FORMER IMPEX FACILITY, CRAWFORDSVILLE, INDIANA

Sample ID No.	Sample Date	Lab Report No.	cis-1	2-DCE	Т	CE		Vinyl hloride
PELs (ug/m3)			793	3050	53	7000		2570
Molecular Weight			96	6.94	13	31.4		62.5
Analytical Results	*		ppbv	ug/m3	ppbv	ug/m3	ppbv	ug/m3
TO-FD-01E	03/07/08	20803040	<0.103	0.408377	<0.130	0.69865	<0.112	0.286298569
TO-FD-01W	03/07/08	20803040	<0.121	0.479744	<0.154	0.827632	<0.133	0.33997955
TO-FD-02E	03/11/08	20803040	0.189	0.749352	0.696	3.740466	<0.136	0.347648262
TO-FD-02W	03/11/08	20803040	<0.153	0.606618	<0.194	1.042601	<0.167	0.426891616
TO-FD-03E	03/12/08	20803040	<0.125	0.495603	0.269	1.445669	<0.137	0.350204499
TO-FD-03W	03/12/08	20803040	0.13	0.515427	0.559	3.004196	<0.134	0.342535787


^{*} Analytical results were reported in ppbv by the laboratory and converted to ug/m³ by ENTACT

TABLE 3: SOIL LABORATORY ANALYTICAL RESULTS FORMER IMPEX FACILITY, CRAWFORDSVILLE, INDIANA

Sample	Sample	Sample	Sample	Lab	1	otal (ug/kg	g)	;	SPLP (ug/l)	
ID No.	Location	Date	Depth Report (ft) No.		cis-1,2- DCE	TCE	Vinyl Chloride	cis-1,2- DCE	TCE	Vinyl Chloride	рН
FD-S88-Pre	Soil boring QB-88	03/07/08	7/08 0-2 560-9081-1		400	4900	<490				
FD-AB23-Pre	Soil boring AB-23	03/13/08	18-19 5012923		6880	48600	297				
AB-23 Post ¹	Treated soil stockpile	03/14/08	NA	5012998	629	6340	<5.1				
AB-23-Post-2 ²	Treated soil stockpile	03/28/08	NA	5013472	<6.3	70	<6.3				
Comp-8	Treated soil stockpile	04/18/08	NA	5014193				<5	22.8	<2	7.9

¹ Post-treatment sample collected after 24 hours

² Post-treatment sample collected after 2 weeks



ATTACHMENT 1 LABORATORY ANALYTICAL REPORTS



March 27, 2008

LABORATORY REPORT

Client:

ENTACT Environmental Services Work Order: PRC1068

3129 Bass Pro Dr. Project Name: Crawfordville, IN

Grapevine, TX 76051 Project Number: Impex Crawfordsville/D1712

Attn: Aaron McCorvey Date Received: 03/13/08

The results listed within this Laboratory Report pertain only to the samples tested in the laboratory. The analyses contained in this report were performed in accordance with the applicable certifications as noted. All soil samples are reported on a wet weight basis unless otherwise noted in the report. This Laboratory Report is confidential and is intended for the sole use of TestAmerica and its client. This report shall not be reproduced, except in full, without written permission from TestAmerica.

TestAmerica Analytical Testing Corporation certifies that the analytical results contained herein apply only to the specific sample(s) analyzed.

The Chain(s) of Custody, 2 pages, are included and are an integral part of this report. This entire report was reviewed and approved for release.

If you have any questions relating to this analytical report, please contact your Laboratory Project Manager at 1-(602)437-3340

Analyses included in this report were performed by the laboratory shown at the top of this report unless otherwise indicated.

Approved By:

EPA ARCHIVE DOCUMEN

Tim Trestrail Project Manager





ENTACT Environmental Services

3129 Bass Pro Dr. Grapevine, TX 76051

PRC1068 Work Order:

Received: Reported:

03/13/08 03/27/08 14:03

Aaron McCorvey

Project: Crawfordville, IN

Project Number: Impex Crawfordsville/D1712

SAMPLE IDENTIFICATION	LAB NUMBER	COLLECTION DATE	CONTAINER TYPE
AS-FD-P01 front	PRC1068-01	03/07/08	50/100 mg - Coconut Shell Charcoal Tube
AS-FD-P02 front	PRC1068-02	03/07/08	50/100 mg - Coconut Shell Charcoal Tube
AS-FD-PFB1	PRC1068-03	03/07/08	50/100 mg - Coconut Shell Charcoal Tube
AS-FD-P01 back	PRC1068-04	03/07/08	50/100 mg - Coconut Shell Charcoal Tube
AS-FD-P02 back	PRC1068-05	03/07/08	50/100 mg - Coconut Shell Charcoal Tube
AS-FD-P03 front	PRC1068-06	03/11/08	50/100 mg - Coconut Shell Charcoal Tube
AS-FD-P03 back	PRC1068-07	03/11/08	50/100 mg - Coconut Shell Charcoal Tube
AS-FD-P04 front	PRC1068-08	03/11/08	50/100 mg - Coconut Shell Charcoal Tube
AS-FD-P04 back	PRC1068-09	03/11/08	50/100 mg - Coconut Shell Charcoal Tube
AS-FD-PFB2	PRC1068-10	03/11/08	50/100 mg - Coconut Shell Charcoal Tube
AS-FD-P05 front	PRC1068-11	03/12/08	50/100 mg - Coconut Shell Charcoal Tube
AS-FD-P05 back	PRC1068-12	03/12/08	50/100 mg - Coconut Shell Charcoal Tube
AS-FD-P06 front	PRC1068-13	03/12/08	50/100 mg - Coconut Shell Charcoal Tube
AS-FD-P06 back	PRC1068-14	03/12/08	50/100 mg - Coconut Shell Charcoal Tube
AS-FD-PFB3	PRC1068-15	03/12/08	50/100 mg - Coconut Shell Charcoal Tube



THE LEADER IN ENVIRONMENTAL TESTING

ENTACT Environmental Services

3129 Bass Pro Dr.

Aaron McCorvey

Grapevine, TX 76051

4645 East Cotton Center Blvd. Building 3, Ste 189 Phoenix, AZ 85040 * (602) 437-3340 * Fax (602) 454-9303

Work Order: PRC1068 Received: 03/13/08

Reported: 03/27/08 14:03

Project: Crawfordville, IN

Project Number: Impex Crawfordsville/D1712

ANALYTICAL REPORT


Analyte		Result		Qual	Date Analyzed	Analyst	Rpt Limit	Method
Halogenated Hydrocarbons by NIO	SH 1003/OSHA 7	(Modified)						
Sample ID: PRC1068-01 (AS-F	D-P01 front)	Tube		Sample A	Air Volume:5L	1	Sa	mpled: 03/07/08
-	ug, Total	mg/m3	ppm	_			ug, Total	•
eis-1,2-Dichloroethylene	<9.98	<2	< 0.503		3/19/2008	ZN	9.98	NIOSH 1003
Trichloroethylene	<11.8	<2.36	< 0.439		3/19/2008	ZN	11.8	NIOSH 1003
Sample ID: PRC1068-02 (AS-F	D-P02 front)	Tube		Sample A	Air Volume:5L	1	Sa	mpled: 03/07/08
	ug, Total	mg/m3	ppm				ug, Total	•
is-1,2-Dichloroethylene	<9.98	<2	< 0.503		3/19/2008	ZN	9.98	NIOSH 1003
richloroethylene	<11.8	<2.36	< 0.439		3/19/2008	ZN	11.8	NIOSH 1003
Sample ID: PRC1068-03 (AS	-FD-PFB1)	Tube		Sample 2	Air Volume:L		Sa	mpled: 03/07/08
-	ug, Total	mg/m3	ppm	_			ug, Total	•
is-1,2-Dichloroethylene	<9.98				3/19/2008	ZN	9.98	NIOSH 1003
richloroethylene	<11.8				3/19/2008	ZN	11.8	NIOSH 1003
Sample ID: PRC1068-06 (AS-F	D-P03 front)	Tube		Sample A	Air Volume:5L	ı	Sa	mpled: 03/11/08
	ug, Total	mg/m3	ppm				ug, Total	-
is-1,2-Dichloroethylene	102	20.4	5.15		3/19/2008	ZN	9.98	NIOSH 1003
richloroethylene	22.6	4.52	0.841		3/19/2008	ZN	11.8	NIOSH 1003
Sample ID: PRC1068-08 (AS-F	D-P04 front)	Tube		Sample A	Air Volume:5L	ı	Sa	mpled: 03/11/08
	ug, Total	mg/m3	ppm				ug, Total	-
is-1,2-Dichloroethylene	<9.98	<2	< 0.503		3/19/2008	ZN	9.98	NIOSH 1003
richloroethylene	<11.8	<2.36	< 0.439		3/19/2008	ZN	11.8	NIOSH 1003
Sample ID: PRC1068-10 (AS-	-FD-PFB2)	Tube		Sample 2	Air Volume:L		Sa	mpled: 03/11/08
	ug, Total	mg/m3	ppm				ug, Total	•
is-1,2-Dichloroethylene	<9.98				3/19/2008	ZN	9.98	NIOSH 1003
richloroethylene	<11.8				3/19/2008	ZN	11.8	NIOSH 1003
Sample ID: PRC1068-11 (AS-F	D-P05 front)	Tube		Sample A	Air Volume:5L	ı	Sa	mpled: 03/12/08
	ug, Total	mg/m3	ppm				ug, Total	
is-1,2-Dichloroethylene	<9.98	<2	< 0.503		3/19/2008	ZN	9.98	NIOSH 1003
richloroethylene	<11.8	<2.36	< 0.439		3/19/2008	ZN	11.8	NIOSH 1003
Sample ID: PRC1068-13 (AS-F	D-P06 front)	Tube		Sample A	Air Volume:5L		Sa	mpled: 03/12/08
	ug, Total	mg/m3	ppm				ug, Total	
s-1,2-Dichloroethylene	<9.98	<2	< 0.503		3/19/2008	ZN	9.98	NIOSH 1003
richloroethylene	<11.8	<2.36	< 0.439		3/19/2008	ZN	11.8	NIOSH 1003
Sample ID: PRC1068-15 (AS	-FD-PFB3)	Tube		Sample 2	Air Volume:L		Sa	mpled: 03/12/08
	ug, Total	mg/m3	ppm				ug, Total	
ris-1,2-Dichloroethylene	<9.98				3/19/2008	ZN	9.98	NIOSH 1003
Trichloroethylene	<11.8				3/19/2008	ZN	11.8	NIOSH 1003

Sample Air Volume:5L

Vinyl Chloride by NIOSH 1007 (Modified)

Sample ID: PRC1068-01 (AS-FD-P01 front) Tube

Sampled. 33/0/f8 9





ENTACT Environmental Services

3129 Bass Pro Dr. Grapevine, TX 76051 Aaron McCorvey Work Order: PRC1068

Received: 0
Reported: 0

03/13/08 03/27/08 14:03

Project: Crawfordville, IN

Project Number: Impex Crawfordsville/D1712

Analyte		Result		Qual	Date Analyzed	Analyst	Rpt Limit	Method
inyl Chloride by NIOSH 1007 ((Modified) - cont.							
Sample ID: PRC1068-01 (AS-F	D-P01 front) - cont.	Tube		Sample A	ir Volume:5L	ı	Samp	oled: 03/07/08
	ug, Total	mg/m3	ppm				ug, Total	
inyl chloride	< 5.00	<1	< 0.391		3/19/2008	ZN	5.00 N	1007(MOD)
Sample ID: PRC1068-02 (A	S-FD-P02 front)	Tube		Sample A	ir Volume:5L	,	Samr	oled: 03/07/08
•	ug, Total	mg/m3	ppm	•			ug, Total	,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,
inyl chloride	<5.00	<1	< 0.391		3/19/2008	ZN		1007(MOD)
Sample ID: PRC1068-03	(AS-FD-PFR1)	Tube		Sample /	Air Volume:L		Samr	oled: 03/07/08
Sample ID: TRETOOD OF	ug, Total	mg/m3	ppm	Sumple	iii voiumeil		ug, Total	neu. 05/07/00
inyl chloride	<5.00	C			3/19/2008	ZN		1007(MOD)
Sample ID: PRC1068-04 (A	S_FD_P01 back)	Tube		Sample A	ir Volume:5L		Come	J. J. 02/07/09
Sample 1D. 1 Re1000-04 (A	ug, Total	mg/m3	ppm	Sample A	iii voiume.si.	•	ug, Total	oled: 03/07/08
inyl chloride	<5.00	<1	< 0.391		3/19/2008	ZN		1007(MOD)
•			0.571	6 1 4				
Sample ID: PRC1068-05 (A	,	Tube		Sample A	ir Volume:5L	•	-	oled: 03/07/08
inyl chloride	ug, Total <5.00	mg/m3 <1	ppm <0.391		3/19/2008	ZN	ug, Total	1007(MOD)
•		<1	\0.391				5.00 IN	1007(MOD)
Sample ID: PRC1068-06 (A	ŕ	Tube		Sample A	ir Volume:5L	•	-	oled: 03/11/08
	ug, Total	mg/m3	ppm		2 14 2 12 2 2 2		ug, Total	
inyl chloride	<5.00	<1	< 0.391		3/19/2008	ZN	5.00 N	1007(MOD)
Sample ID: PRC1068-07 (A	S-FD-P03 back)	Tube		Sample A	ir Volume:5L	ı	Samp	oled: 03/11/08
	ug, Total	mg/m3	ppm				ug, Total	
'inyl chloride	<5.00	<1	< 0.391		3/19/2008	ZN	5.00 N	1007(MOD)
Sample ID: PRC1068-08 (A	S-FD-P04 front)	Tube		Sample A	ir Volume:5L	ı	Samp	oled: 03/11/08
	ug, Total	mg/m3	ppm				ug, Total	
inyl chloride	< 5.00	<1	< 0.391		3/19/2008	ZN	5.00 N	1007(MOD)
Sample ID: PRC1068-09 (A	S-FD-P04 back)	Tube		Sample A	ir Volume:5L	ı	Samp	oled: 03/11/08
	ug, Total	mg/m3	ppm				ug, Total	
inyl chloride	< 5.00	<1	< 0.391		3/19/2008	ZN	5.00 N	1007(MOD)
Sample ID: PRC1068-10	(AS-FD-PFB2)	Tube		Sample A	Air Volume:L		Samr	oled: 03/11/08
•	ug, Total	mg/m3	ppm	•			ug, Total	
inyl chloride	< 5.00				3/19/2008	ZN		1007(MOD)
Sample ID: PRC1068-11 (A	S-FD-P05 front)	Tube		Sample A	ir Volume:5L	4	Samr	oled: 03/12/08
	ug, Total	mg/m3	ppm				ug, Total	,.cu. 05/12/00
inyl chloride	<5.00	<1	< 0.391		3/19/2008	ZN		1007(MOD)
Sample ID: PRC1068-12 (A	(S_FD_P05 back)	Tube		Sample A	ir Volume:5L		Ç	Jod. 02/12/00
Sample 1D. 1 KC1000-12 (A	ug, Total	mg/m3	ppm	Sample A	ar voiume.SL	•	ug, Total	oled: 03/12/08
inyl chloride	<5.00	~1	<0.391		3/19/2008	ZN		1007(MOD)
•				Samula 4				
Sample ID: PRC1068-13 (A	ug, Total	Tube mg/m3	nnm	Sample A	ir Volume:5L	ı	Samp ug, Total	oled: 03/12/08
inyl chloride	(5.00	mg/m3 <1	ppm <0.391		3/19/2008	ZN		1007(MOD) 🕝
	·5.00	~1	.0.571		5/17/2000	<i>L</i> 111	5.00 11	4 6f



THE LEADER IN ENVIRONMENTAL TESTING

4645 East Cotton Center Blvd. Building 3, Ste 189 Phoenix, AZ 85040 * (602) 437-3340 * Fax (602) 454-9303

ENTACT Environmental Services

3129 Bass Pro Dr. Grapevine, TX 76051

Aaron McCorvey

PRC1068 Work Order:

Project:

Received:

Reported:

03/13/08 03/27/08 14:03

Crawfordville, IN

Project Number: In	npex Crawfordsville/D1/12
--------------------	---------------------------

Analyte Vinyl Chloride by NIOSH 10	07 (Modified) cont	Result		Qual	Date Analyzed	Analyst	Rpt Limit	Method			
Vinyi Cinoride by NiOSH 10	o/ (Modified) - cont.										
Sample ID: PRC1068-14 (<i>A</i>	AS-FD-P06 back) - cont.	Tube		Sample A	ir Volume:5L	1	Sampled: 03/12/				
	ug, Total	mg/m3	ppm				ug, Total				
Vinyl chloride	<5.00	<1	< 0.391		3/19/2008	ZN	5.00 N	11007(MOD)			
Sample ID: PRC1068	-15 (AS-FD-PFB3)	Tube		Sample A	Air Volume:L		Sam	pled: 03/12/08			
	ug, Total	mg/m3	ppm				ug, Total				
Vinyl chloride	<5.00				3/19/2008	ZN	5.00 N	11007(MOD)			



Blank Value

Q

4645 East Cotton Center Blvd. Building 3, Ste 189 Phoenix, AZ 85040 * (602) 437-3340 * Fax (602) 454-9303

Lab Number

ENTACT Environmental Services

3129 Bass Pro Dr.

Grapevine, TX 76051 Aaron McCorvey

Analyte

Work Order: PRC1068

Received:

Reported:

Analyzed Date

03/13/08 03/27/08 14:03

Project: Crawfordville, IN

Project Number: Impex Crawfordsville/D1712

Q.C. Batch

PROJECT QUALITY CONTROL DATA

Blank

Units

Vinyl Chloride by NIOSH 1007	7 (Modified)									
P8C1822-BLK1										
Vinyl chloride	<2.50	ug, Tota	l	P8C1822	P8C	1822-BLK	.1	03-18-2008		
Vinyl chloride - Back	<2.50	ug, Tota	1	P8C1822	P8C	1822-BLK	.1	03-18-2008		
Halogenated Hydrocarbons by	NIOSH 1003/OSHA 7 (Mod	lified)								
P8C1821-BLK1										
cis-1,2-Dichloroethylene - Back	<4.99	ug, Tota	l	P8C1821	P8C	1821-BLK	.1	03-18-2008		
Trichloroethylene	< 5.91	ug, Tota	1	P8C1821	P8C	1821-BLK	.1	03-18-2008		
Trichloroethylene - Back	<5.91	ug, Tota	l	P8C1821	P8C	1821-BLK	.1	03-18-2008		
cis-1,2-Dichloroethylene	<4.99	ug, Tota	1	P8C1821	P8C	1821-BLK	.1	03-18-2008		
		LC	S							
Analyte	Known Val.	Analyzed Val	C)	Units	% Rec		Target Range	Batch	Analyzed Date
			`							
Vinyl Chloride by NIOSH 1007	/ (Modified)									
P8C1822-BS1 Vinyl chloride	5.2	4.735			ug, Total	91%		75-125	P8C1822	03-18-2008
vinyi chloride	3.2	4./33			ug, Totai	91/0		73-123	F 0C 1022	03-16-2006
Halogenated Hydrocarbons by	NIOSH 1003/OSHA 7 (Mod	lified)								
P8C1821-BS1	(1100111100)									
Trichloroethylene	14.7	15.10			ug, Total	103%		75-125	P8C1821	03-18-2008
cis-1,2-Dichloroethylene	12.9	12.58			ug, Total	98%		75-125	P8C1821	03-18-2008
		LCS	Dup							
	0: 11 0 "	0 11.	Spike	0/ P	Target	222		D : 1	Sample	Analyzed
Analyte	Orig. Val. Duplicate	Q Units	Conc	% Rec.	Range	RPD	Limit	Batch	Duplicated	Date
Vinyl Chloride by NIOSH 1007	7 (Modified)									
P8C1822-BSD1										
P0C1022-B3D1	4.722	ug, Total	5.2	91%	75-125	0.0423	30	P8C1822		03-18-2008
Vinyl chloride	4.733	<u>.</u>								
		lified)								
Vinyl chloride		lified)								
Vinyl chloride Halogenated Hydrocarbons by		lified)	14.7	102%	75-125	0.664	30	P8C1821		03-18-2008



THE LEADER IN ENVIRONMENTAL TESTING

4645 East Cotton Center Blvd. Building 3, Ste 189 Phoenix, AZ 85040 * (602) 437-3340 * Fax (602) 454-9303

ENTACT Environmental Services Work Order: PRC1068 Received: 03/13/08

3129 Bass Pro Dr. Grapevine, TX 76051

Project: Crawfordville, IN

Aaron McCorvey Project Number: Impex Crawfordsville/D1712

CERTIFICATION SUMMARY

Analyses included in this report were performed by TestAmerica Laboratories, Inc. (TAL), 4645 E. Cotton Center Boulevard, Building 3, Suite 189, Phoenix, AZ 85040.

TAL Phoenix (Lab ID 154268) is accredited by the American Industrial Hygiene Association (AIHA) in the industrial hygiene program for the analytical techniques noted on the scope of accreditation for the following methods: NIOSH 0500, NIOSH 0600, NIOSH 1003, NIOSH 1005, NIOSH 1007, NIOSH 1010, NIOSH 1015, NIOSH 1022, NIOSH 1300, NIOSH 1400, NIOSH 1401, NIOSH 1403, NIOSH 1405, NIOSH 1450, NIOSH 1457, NIOSH 1500, NIOSH 1501, NIOSH 1550, NIOSH 1602, NIOSH 1604, NIOSH 1606, NIOSH 1609, NIOSH 1611, NIOSH, 1613, NIOSH 1615, NIOSH 2000, NIOSH 2532, NIOSH 2546, NIOSH 2551, NIOSH 5000, NIOSH 5503, NIOSH 5506, NIOSH 5600, NIOSH 6001, NIOSH 6006, NIOSH 6009, NIOSH 6010, NIOSH 7300, NIOSH 7600, NIOSH 7903, OSHA 7, OSHA 42, OSHA 47, OSHA 48, OSHA 64, OSHA 69, OSHA 111, OSHA ID-140, OSHA ID-121, OSHA 1001, OSHA 1002, OSHA 1003, OSHA 1004, OSHA 1005 and OSHA Chemical and Sampling Information for Silane. Volatile organic compounds on 3M Organic Vapor Monitors, Assay Technology Passive Monitors and SKC Passive Monitors. Formaldehyde and other aldehydes and ketones on Assay Technology Passive Monitor. Aldehydes and ketones by EPA TO-11A.

TAL Phoenix also holds NELAC accreditation through the State of Oregon (AZ100001) for the analytical techniques noted on the scope of accreditation and the State of New York (11898) for NIOSH 6009.

Samples were analyzed using methods outlined in references such as:

- -OSHA Occupational Safety and Health Administration, U. S. Department of Labor, OSHA Analytical Methods Manual.
- -NIOSH National Institute for Occupational Safety and Health, U. S. Department of Health and Human Services, NIOSH Manual of Analytical Methods, Fourth Edition, 1994, and Updates. NIOSH Method 7300 analyses are performed using a modified digestion procedure to eliminate the use of perchloric acid.
- -EPA U. S. Environmental Protection Agency, Compendium of Methods for the Determination of Toxic Organic Compounds in Ambient Air, Second Edition, 1999.
- -EPA U. S. Environmental Protection Agency, Analytical Methods, Emission Measurement Center (EMC).

Analytical Comments:

Unless otherwise noted, all method blanks and laboratory control spikes met method and/or laboratory quality control objectives for the analyses included in this report.

Unless otherwise noted, sample results have been corrected for method blank values.

For information concerning certifications of this facility or another TestAmerica facility, please visit our website at www.TestAmericaInc.com

03/27/08 14:03

Reported:



[] North Phoenix 1501 W. Knudsen, Phoenix, AZ 85027 623.780,4800 - FAX 623,445.6216 [X] Main Lab 4645 E: Cotton Center Blvd., Building 3; Suite 189, Phoenix, AZ 85040 602.437.3340 - FAX 623.445.6192 Phone: 630-935-9459 Name: ENTACT Customer Number: www.aeroenvirolabs.com or call toll-free 866,772,5227 []Tucson - 4455 S. Park Ave, Suite 110, Tucson, AZ 85714 520,807,3801 - FAX 520,807,3803 City, State, Zip: ontact: Hazan ddress: 3)39 -Mail Address: ance orvey いるという Fax: @ Cotact .com Aerotech Environmental Laboratories Page E-Mail Results: P.O. Number: Project Number: Project Name: トリコン Sampler: A. Fax Results: Craw tords ville Ż || PRC1068 96005000

																	õ								
	31308	7.000	へ しょう	1117		Instruction							ノン	14	W	7	=	Lab#				Total # of	Custody S	Custody S	Temperature
-	_	VI 100 DIM		-		nstructions / Special Requirements:							-	1		(1)	~ () 20 C July 1-100005	IH Media Type				Total # of Containers	Custody Seals Intact: Yes	ls: Yes	emperature
		Hearte				ents:							0			1000111		Flow Rare			Subjec		No	No	ο (C)
	.	MYoury										- V - V - -	ACTO DERR	AC EN BOIL I FRANT	75-F17-102 Dack	DO TO DOS TOST	DOS DOS DO				Subject to scheduling and availability (surcharges apply)	_ Standard 10 Working Days	5 working Day	72 Hours	Jean Pay China China
7	2	10	(S) (S) (S)									E	5 Back	- I sent	Descie	+ toun+	ulleation		emine		y (surcharges apply)	ig Days		48 Hours	THE STATE OF
												7.0.C	7-0-08	XO-O-A	59-E-V	2-12-0X	Date			•					
												10.00	10.12	61:01	10.00	10:00	Start Time								
		THE STREET STREET, STR										11.40	65:11	11,50	0 11 1	0H:H0	Stop Time								
												100	/60	100	100	100	Total Minutes								
													V	\v.	4	75	(L)	Total Volume							
>	でもり																Sample	Number of							
	<i>X</i>			() () () () ()		1000			12 + 2 22 + 2	7 N		<u>×</u>		~	- j.	<u> </u>		TC	E	No.	ns ton	A Property of the Control of the Con	a nave		
		11:17:					T		and the second	la sa		X	~	×	~	X		<u>- 12</u>	1	<u>ز</u>	<u>]</u>	<u>) C</u>	E		
		THE STATE OF				-	-								2		V	iny	1_	<u> </u>	54	70.	J€	oance of the contract of the c	N EN A
		11/1/2			-		-	4	*** ;		12.2		Jar.		**: * \$	A A A A A				- 1:	· : '	. ***			
	٠				 		-														{.			- Jack	
-	-1		2	-	77											; ; ;							1	100	
	٠						-					-										···			

All services are performed subject to the Terms & Co

US EPA ARCHIVE DOCUMENT



							Ş	₹ ₹	5	òō)			6	ō																					ı.
	3/13/08			moderation ope	Incinicione I can	0	4	9	7	6	ヘ	1	(2)	رې	~ 2	L30# HI				Total # of Containers:	Custody Seals: Yes	Temperature	Sa		Phone: (D	Address: 3	Name: E N	Customer Number:	www.aeroenvirol	Tucson - 445	[X] Main Lab - 46	a division of Arratech Labaratories, Inc.	C. WORATOW!	AERO A	7 (S)
	10:30	Eleco.		Special Requirements:		7	74	7	11	11		=	4		TUNG THE	IH Media Timo				ners:		して「	Sample Receipt	- L	COLOR DATE	र्व गुरुट)	SENS MEIS	ENTACT	mber:	abs.com or call to	C-1501 W. Knuds	45 E. Cotton Cen	erios Inc.	THE STATE OF	TYLE.	, who
	76.00 1				0	à	4			0 25 1	~	0.05 11	C	-	U, OS L/N	<u>D</u>			Subje	8		C.	g c	1	6	N.	Pro Dave		200011202	www.aeroenvirolabs.com or call toll-free 866 772 5227	sen, Phoenix, AZ 8	ter Blvd., Building			Þ	
710	Tr. Clury				AS- FD -	11 7 7 5	- 1.	17	20.07	5 -	3	D	AC-50 -	AS-50	ACLEO -				to scheduling and availability (surchan	_5 working Day	_72 Hours	_ 24 Hours	Turn Around	0		16051	W.			Z 85714 520.807. 77	5027 623.780.48	3, Suite 189, Phoe			erotech	k 1
		Samp			14 KZ	FOU DAIL	- !		Doy L. L	202 C	Parauk	Political	- DCK-	AS-40-0000	AS-SO-PAID		Sample		Subject to scheduling and availability (surcharges apply)		****	48 Hours	Turn Around Request	Fax Results:	P.O. Number:	Project Number:	Project Name:	rage	D	www.aeroenvirolabs.com or call toll-free 866 777 5227	Tucson - 4455 C. Park Ave. Science 1 - 1 - 1 - 2 - 3 - 3 - 3 - 3 - 3 - 3 - 3 - 3 - 3	nix, AZ 85040 60				
		mples Relinguished By			2				7	+			760	7 7 6	Date 30								esults:	ılts:		lumber: 'D 7	1	2 01		7.3803	6216	1A) Main Lab - 4645 E. Cotton Center Blvd., Building 3, Suite 189, Phoenix, AZ 85040 602,437,3340 - FAX 623,445,6192			Environment	: :
					ré				09:30	-	+	#	> 0) C) B		ion			•						$\overline{\nu}_{r}$	230					323.445.6192		. ;	onmo	
						1.16					+				ē											ia will a suit	0 11- 0							•	ental	
						100				00		-	-		nutes								3	Z								· · · · · · · · · · · · · · · · · · ·		a di	<u>ה</u>	
	J					13.33 13.33 13.33 14.33 14.33						<u>ရ</u>		N)	(E) Sam	Numb							Z											a division of Aerotech Lab	これが	ac ore
۲ -	(A) C) (A)				< 		×		*		e e e e e e e e e e e e e e e e e e e	X	X	×	1	ا ا ا ا	CE) E	F									(p)		- A - D	Aprese		<u> </u>	ך ס ס	
			The state of the s	×		*	×	×	*	×	~	*	*	×	V		11		hla	Jr -0	- ;	Analyses							スのい						-1.6	
								7														Requested								} C	Number			0	f 9	
				-	+	+						;	_																0	, j			,		: :	

All services are performed subject to the Terms & Conditions on the reverse side.

7

TestAmerica Austin Laboratory Analysis Report

March 31, 2008

Aaron McCorvey 3129 Bass Pro Drive Grapevine, TX 76051

630-935-9459 (Business)

RE: Laboratory Reference: Impex Crawfordsville [20803040] ENTACT

Dear Aaron McCorvey:

TestAmerica Austin received samples with a request for the analytical fractions listed below. Except as noted in the QCER(s) all laboratory quality control parameters were met. These data have been reviewed and released by the person below. Results for the indicated analytical fractions and associated quality control data are enclosed in this report.

	Status	Reported	Approval Signature/D	ate	
VOC	ENCLOSED	03/31/2008	Carly	Spelley	3-3/-08

The report is provided as indicated in the Table of Contents (Page i) and it is followed by Appendix A which includes any additional information associated with the report. This report must not be reproduced, except in full, without the written approval of the laboratory.

TestAmerica Austin appreciates your business and looks forward to serving you again. If you have any questions about your report or need any additional information, please call me at (512)310-5202 or fax inquiries to (512)244-0160.

Sincerely

Client Services/Project Manager

SECTION I Table of Contents

Section	Form Page
	Cover Page - Laboratory Analytical Report
I.	Table of Contents
V(II.	C
III.	Report Summaries 2 Workorder Summary 2
	Protocol Summary
IV.	Comments and Flag Definitions
	Standard Flag Definitions
	Sample Condition Comments
V.	Analytical Results
VI.	TO15 Ambient
•	TO15 Ambient
	Calibration Verification Results
	Mass Spectrometer Tune
	Control Sample Results
VII.	Batch Summaries
	Extraction/Digestion Batch Summary
	Extraction/Digestion Batch Summary
	Analysis Batch Summary
VIII.	Analysis Batch Summary
IX.	Notes
х.	COC/Addendum

SECTION II Case Narrative

The 1,2-dichloroethane-d4 surrogate failed the acceptance criteria in sample TO-FD-01E with a recovery of 137% (limits 70-130%). The sample was reanalyzed, and the 1,2-dichloroethane-d4 surrogate failed the acceptance criteria again with a recovery of 134%. Both sets of results are reported.

The 1,2-dichloroethane-d4 surrogate failed the acceptance criteria in sample TO-FD-01W with a recovery of 136% (limits 70-130%). The sample was reanalyzed, and the 1,2-dichloroethane-d4 surrogate failed the acceptance criteria again with a recovery of 136%. Both sets of results are reported.

The 1,2-dichloroethane-d4 surrogate failed the acceptance criteria in sample TO-FD-02E with a recovery of 136% (limits 70-130%). The sample was reanalyzed, and the 1,2-dichloroethane-d4 surrogate failed the acceptance criteria again with a recovery of 134%. Both sets of results are reported.

The 1,2-dichloroethane-d4 surrogate failed the acceptance criteria in sample TO-FD-02W with a recovery of 137% (limits 70-130%). The sample was reanalyzed, and the 1,2-dichloroethane-d4 surrogate failed the acceptance criteria again with a recovery of 136%. Both sets of results are reported.

The 1,2-dichloroethane-d4 surrogate failed the acceptance criteria in sample TO-FD-03E with a recovery of 136% (limits 70-130%). The sample was reanalyzed, and the 1,2-dichloroethane-d4 surrogate failed the acceptance criteria again with a recovery of 136%. Both sets of results are reported.

The 1,2-dichloroethane-d4 surrogate failed the acceptance criteria in sample TO-FD-03W with a recovery of 134% (limits 70-130%). The sample was reanalyzed, and the 1,2-dichloroethane-d4 surrogate failed the acceptance criteria again with a recovery of 134%. Both sets of results are reported.

SECTION III Report Summaries

VOC

Client Name: ENTACT
Client Code: ENTACT

Project Name: Impex Crawfordsville [20803040] ENTACT

Facility Name:

Workorder Summary

	Lab			
Client Sample ID	Sample ID	Sample Matrix	Method Citation	Method Description
TO-FD-01E	2080304001	Air	TO15 Ambient	VOC Ambient GC/MS
TO-FD-01W	2080304002	Air	TO15 Ambient	VOC Ambient GC/MS
TO-FD-02E	2080304003	Air	TO15 Ambient	VOC Ambient GC/MS
TO-FD-02W	2080304004	Air	TO15 Ambient	VOC Ambient GC/MS
TO-FD-03E	2080304005	Air	TO15 Ambient	VOC Ambient GC/MS
TO-FD-03W	2080304006	Air	TO15 Ambient	VOC Ambient GC/MS

Protocol Summary

			Hold Time Spec
Lab	Date & Time Date & Time Prep	Date & Time Analysis Date & Time	Prep Analysis
Client Sample ID	Collected Received Batch ID	Prepared Batch ID Analyzed	Spec Actual Spec Actual

Method: TO15 Ambient

2080304001	03/07/08 10:30	03/17/08 08:00	54694	03/20/08 21:31	54694	03/20/08 21:31	30D	13D	30D	13D
2080304001	03/07/08 10:30	03/17/08 08:00	54798	03/25/08 21:39	54798	03/25/08 21:39	30D	18D	30D	18D
2080304002	03/07/08 10:30	03/17/08 08:00	54694	03/20/08 22:35	54694	03/20/08 22:35	30D	13D	30D	13D
2080304002	03/07/08 10:30	03/17/08 08:00	54798	03/25/08 22:45	54798	03/25/08 22:45	30D	18D	30D	18D
2080304003	03/11/08 09:00	03/17/08 08:00	54694	03/20/08 23:39	54694	03/20/08 23:39	30D	9D	30D	9D
2080304003	03/11/08 09:00	03/17/08 08:00	54798	03/25/08 23:51	54798	03/25/08 23:51	30D	14D	30D	14D
2080304004	03/11/08 09:00	03/17/08 08:00	54694	03/21/08 00:43	54694	03/21/08 00:43	30D	10D	30D	10D
2080304004	03/11/08 09:00	03/17/08 08:00	54798	03/26/08 00:57	54798	03/26/08 00:57	30D	15D	30D	15D
	2080304001 2080304002 2080304002 2080304003 2080304003 2080304004	2080304001 03/07/08 10:30 2080304002 03/07/08 10:30 2080304002 03/07/08 10:30 2080304003 03/11/08 09:00 2080304003 03/11/08 09:00 2080304004 03/11/08 09:00	2080304001 03/07/08 10:30 03/17/08 08:00 2080304002 03/07/08 10:30 03/17/08 08:00 2080304002 03/07/08 10:30 03/17/08 08:00 2080304003 03/11/08 09:00 03/17/08 08:00 2080304003 03/11/08 09:00 03/17/08 08:00 2080304004 03/11/08 09:00 03/17/08 08:00 2080304004 03/11/08 09:00 03/17/08 08:00	2080304001 03/07/08 10:30 03/17/08 08:00 54798 2080304002 03/07/08 10:30 03/17/08 08:00 54694 2080304002 03/07/08 10:30 03/17/08 08:00 54798 2080304003 03/11/08 09:00 03/17/08 08:00 54694 2080304003 03/11/08 09:00 03/17/08 08:00 54798 2080304004 03/11/08 09:00 03/17/08 08:00 54798 2080304004 03/11/08 09:00 03/17/08 08:00 54694	2080304001 03/07/08 10:30 03/17/08 08:00 54798 03/25/08 21:39 2080304002 03/07/08 10:30 03/17/08 08:00 54694 03/20/08 22:35 2080304002 03/07/08 10:30 03/17/08 08:00 54798 03/25/08 22:45 2080304003 03/11/08 09:00 03/17/08 08:00 54694 03/20/08 23:39 2080304003 03/11/08 09:00 03/17/08 08:00 54798 03/25/08 23:51 2080304004 03/11/08 09:00 03/17/08 08:00 54694 03/21/08 00:43	2080304001 03/07/08 10:30 03/17/08 08:00 54798 03/25/08 21:39 54798 2080304002 03/07/08 10:30 03/17/08 08:00 54694 03/20/08 22:35 54694 2080304002 03/07/08 10:30 03/17/08 08:00 54798 03/25/08 22:45 54798 2080304003 03/11/08 09:00 03/17/08 08:00 54694 03/20/08 23:39 54694 2080304003 03/11/08 09:00 03/17/08 08:00 54798 03/25/08 23:51 54798 2080304004 03/11/08 09:00 03/17/08 08:00 54694 03/21/08 00:43 54694	2080304001 03/07/08 10:30 03/17/08 08:00 54798 03/25/08 21:39 54798 03/25/08 21:39 2080304002 03/07/08 10:30 03/17/08 08:00 54694 03/20/08 22:35 54694 03/20/08 22:35 2080304002 03/07/08 10:30 03/17/08 08:00 54798 03/25/08 22:45 54798 03/25/08 22:45 2080304003 03/11/08 09:00 03/17/08 08:00 54694 03/20/08 23:39 54694 03/20/08 23:39 2080304003 03/11/08 09:00 03/17/08 08:00 54798 03/25/08 23:51 54798 03/25/08 23:51 2080304004 03/11/08 09:00 03/17/08 08:00 54694 03/21/08 00:43 54694 03/21/08 00:43	2080304001 03/07/08 10:30 03/17/08 08:00 54798 03/25/08 21:39 54798 03/25/08 21:39 30D 2080304002 03/07/08 10:30 03/17/08 08:00 54694 03/20/08 22:35 54694 03/20/08 22:35 30D 2080304002 03/07/08 10:30 03/17/08 08:00 54798 03/25/08 22:45 54798 03/25/08 22:45 30D 2080304003 03/11/08 09:00 03/17/08 08:00 54694 03/20/08 23:39 54694 03/20/08 23:39 30D 2080304003 03/11/08 09:00 03/17/08 08:00 54798 03/25/08 23:51 54798 03/25/08 23:51 30D 2080304004 03/11/08 09:00 03/17/08 08:00 54694 03/21/08 00:43 54694 03/21/08 00:43 30D	2080304001 03/07/08 10:30 03/17/08 08:00 54798 03/25/08 21:39 54798 03/25/08 21:39 30D 18D 2080304002 03/07/08 10:30 03/17/08 08:00 54694 03/20/08 22:35 54694 03/20/08 22:35 30D 13D 2080304002 03/07/08 10:30 03/17/08 08:00 54798 03/25/08 22:45 54798 03/25/08 22:45 30D 18D 2080304003 03/11/08 09:00 03/17/08 08:00 54694 03/20/08 23:39 54694 03/20/08 23:39 30D 9D 2080304003 03/11/08 09:00 03/17/08 08:00 54798 03/25/08 23:51 54798 03/25/08 23:51 30D 14D 2080304004 03/11/08 09:00 03/17/08 08:00 54694 03/21/08 00:43 54694 03/21/08 00:43 30D 10D	2080304001 03/07/08 10:30 03/17/08 08:00 54798 03/25/08 21:39 54798 03/25/08 21:39 30D 18D 30D 2080304002 03/07/08 10:30 03/17/08 08:00 54694 03/20/08 22:35 54694 03/20/08 22:35 30D 13D 30D 2080304002 03/07/08 10:30 03/17/08 08:00 54798 03/25/08 22:45 54798 03/25/08 22:45 30D 18D 30D 2080304003 03/11/08 09:00 03/17/08 08:00 54694 03/20/08 23:39 54694 03/20/08 23:39 30D 9D 30D 2080304003 03/11/08 09:00 03/17/08 08:00 54798 03/25/08 23:51 54798 03/25/08 23:51 30D 14D 30D 2080304004 03/11/08 09:00 03/17/08 08:00 54694 03/25/08 23:51 54798 03/25/08 23:51 30D 14D 30D 2080304004 03/11/08 09:00 03/17/08 08:00 54694 03/21/08 00:43 54694 03/21/08 00:43 30D 10D 30D

SECTION III - Report Summaries - 03/31/2008 09:32

LIMS Workorder: Impex Crawfordsville [20803040] ENTACT

SECTION III Report Summaries

VOC

Protocol Summary continued -

					Hold Time Spec
- 기교과 전체 등학생생활명로 시대한 경기 전기 기계 기본다. 	Lab Date & Time	Date & Time P	Prep Date & Time A	Analysis Date & Time	Prep Analysis
Client Sample ID	Sample ID Collected	Received B	Batch ID Prepared E	Batch ID Analyzed	Spec Actual Spec Actual

Method: TO15 Ambient continued -

Michiga. 1015 Ambient continued											
TO-FD-03E	2080304005	03/12/08 09:00	03/17/08 08:00	54694	03/21/08 01:47	54694	03/21/08 01:47	30D	9D	30D	9D
TO-FD-03E	2080304005	03/12/08 09:00	03/17/08 08:00	54798	03/26/08 02:02	54798	03/26/08 02:02	30D	14D	30D	14D
TO-FD-03W	2080304006	03/12/08 09:00	03/17/08 08:00	54694	03/21/08 02:52	54694	03/21/08 02:52	30D	9D	30D	9D
TO-FD-03W	2080304006	03/12/08 09:00	03/17/08 08:00	54798	03/26/08 03:08	54798	03/26/08 03:08	30D	14D	30D	14D

SECTION IV Comments and Flag Definitions

VOC

Standard Data Qualifiers

Flag	Definition
J	Result > or = MDL and < PQL
NA	Not analyzed/Not available
ND	Not detected at the specified reporting limit
Q	Result does not meet specification
Ü	Result less than sample specific method detection limit

Analyst Comments

Flag Affected Sample Method

Sample Condition Comments

Affected Sample Comment	Affected Sample Comment	

SECTION V Analytical Results

VOC **TO15 Ambient**

Client Sample ID Lab Sample ID Matrix Reported As % Moisture **Date/Time Collected** Date/Time Prepared Date/Time Analyzed **Dilution Factor** Instrument Units

TO-FD-01E	TO-FD-01E	TO-FD-01W	
2080304001	2080304001	2080304002	
Air	Air	Air	
RECEIVED	RECEIVED	RECEIVED	
NA	NA	NA	
03/07/2008 10:30	03/07/2008 10:30	03/07/2008 10:30	
03/20/2008 21:31	03/25/2008 21:39	03/20/2008 22:35	
03/20/2008 21:31	03/25/2008 21:39	03/20/2008 22:35	
2.5220	2.5220	2.9812	
GCMSP1	GCMSP1	GCMSP1	
ppbV	ppbV	ppbV	

Parameter	CAS	Conc Flag	j DL	PQL	Conc Flag	DL	PQL	Conc F	lag DL	PQL
cis-1,2-Dichloroethene	156-59-2	ND	0.103	0.504	ND	0.103	0.504	ND	0.121	0.596
Trichloroethene	79-01-6	ND	0.130	0.504	ND	0.130	0.504	ND	0.154	0.596
Vinyl chloride	75-01-4	ND	0.112	0.504	ND	0.112	0.504	ND	0.133	0.596

SECTION V Analytical Results Surrogates

VOC TO15 Ambient

Client Sample ID
Lab Sample ID
Matrix
Reported As
% Moisture
Date/Time Collected
Date/Time Prepared
Date/Time Analyzed
Dilution Factor
Instrument
Units

TO-FD-01E	TO-FD-01E	TO-FD-01W
2080304001	2080304001	2080304002
Air	Air	Air
RECEIVED	RECEIVED	RECEIVED
NA	NA	NA
03/07/2008 10:30	03/07/2008 10:30	03/07/2008 10:30
03/20/2008 21:31	03/25/2008 21:39	03/20/2008 22:35
03/20/2008 21:31	03/25/2008 21:39	03/20/2008 22:35
2.5220	2.5220	2.9812
GCMSP1	GCMSP1	GCMSP1
ppbV	ppbV	ppbV

Surrogate Compound	% Recover	y Limits		% Recov	ery Limits	Æ	% Recov	ery Limits	F
1-Bromo-4-fluorobenzene	80	70-130		80	70-130		82	70-130	
1,2-Dichloroethane-d4	137	70-130	Q	134	70-130	Q	136	70-130	Q
Toluene-d8	98	70-130		99	70-130		98	70-130	

SECTION V Analytical Results

VOC **TO15 Ambient**

Client Sample ID Lab Sample ID Matrix Reported As % Moisture **Date/Time Collected** Date/Time Prepared Date/Time Analyzed **Dilution Factor** Instrument Units

TO-FD-01W	TO-FD-02E	TO-FD-02E
2080304002	2080304003	2080304003
Air	Air	Air
RECEIVED	RECEIVED	RECEIVED
NA	NA	NA
03/07/2008 10:30	03/11/2008 09:00	03/11/2008 09:00
03/25/2008 22:45	03/20/2008 23:39	03/25/2008 23:51
03/25/2008 22:45	03/20/2008 23:39	03/25/2008 23:51
2.9812	3.0533	3.0533
GCMSP1	GCMSP1	GCMSP1
ppbV	ppbV	ppbV

Parameter	CAS	Conc Flag	DL //	PQL	Conc	Flag	DL	PQL	Conc	Flag	· DL	PQL
cis-1,2-Dichloroethene	156-59-2	ND	0.121	0.596	0.189	J	0.124	0.611	0.190	J	0.124	0.611
Trichloroethene	79-01-6	ND	0.154	0.596	0.696		0.158	0.611	0.720		0.158	0.611
Vinyl chloride	75-01-4	ND	0.133	0.596	ND		0.136	0.611	ND		0.136	0.611

SECTION V Analytical Results Surrogates

VOC **TO15 Ambient**

Client Sample ID Lab Sample ID Matrix Reported As % Moisture **Date/Time Collected** Date/Time Prepared Date/Time Analyzed Dilution Factor Instrument Units

TO-FD-01W	TO-FD-02E	TO-FD-02E
2080304002	2080304003	2080304003
Air	Air	Air
RECEIVED	RECEIVED	RECEIVED
NA	NA	NA
03/07/2008 10:30	03/11/2008 09:00	03/11/2008 09:00
03/25/2008 22:45	03/20/2008 23:39	03/25/2008 23:51
03/25/2008 22:45	03/20/2008 23:39	03/25/2008 23:51
2.9812	3.0533	3.0533
GCMSP1	GCMSP1	GCMSP1
ppbV	ppbV	ppbV

Surrogate Compound	% Recover	y Limits	. F a	% Recov	ery Limits	. E	% Recov	ery Limits	F
1-Bromo-4-fluorobenzene	78	70-130		81	70-130		79	70-130	
1,2-Dichloroethane-d4	136	70-130	Q	136	70-130	Q	134	70-130	Q
Toluene-d8	98	70-130		98	70-130		99	70-130	

SECTION V Analytical Results

VOC **TO15 Ambient**

Client Sample ID Lab Sample ID Matrix Reported As % Moisture **Date/Time Collected Date/Time Prepared** Date/Time Analyzed **Dilution Factor** Instrument Units

TO-FD-02W	TO-FD-02W	TO-FD-03E	
2080304004	2080304004	2080304005	
Air	Air	Air	
RECEIVED	RECEIVED	RECEIVED	
NA	NA	NA	
03/11/2008 09:00	03/11/2008 09:00	03/12/2008 09:00	
03/21/2008 00:43	03/26/2008 00:57	03/21/2008 01:47	
03/21/2008 00:43	03/26/2008 00:57	03/21/2008 01:47	
3.7585	3.7585	3.0781	
GCMSP1	GCMSP1	GCMSP1	
ppbV	ppbV	ppbV	

Parameter	CAS	Conc	Flag DL 🐇	PQL	Conc	Flag DL	PQL	Conc	Flag	DL	PQL
cis-1.2-Dichloroethene	156-59-2	ND	0.153	0.752	ND	0.153	0.752	ND		0.125	0.616
Trichloroethene	79-01-6	ND	0.194	0.752	ND	0.194	0.752	0.269	J	0.159	0.616
Vinyl chloride	75-01-4	ND	0.167	0.752	ND	0.167	0.752	ND		0.137	0.616

SECTION V Analytical Results Surrogates

VOC **TO15 Ambient**

> Client Sample ID Lab Sample ID Matrix Reported As % Moisture **Date/Time Collected Date/Time Prepared** Date/Time Analyzed **Dilution Factor** Instrument Units

TO-FD-02W	TO-FD-02W	TO-FD-03E	
2080304004	2080304004	2080304005	
Air	Air	Air	
RECEIVED	RECEIVED	RECEIVED	
NA	NA	NA	
03/11/2008 09:00	03/11/2008 09:00	03/12/2008 09:00	
03/21/2008 00:43	03/26/2008 00:57	03/21/2008 01:47	
03/21/2008 00:43	03/26/2008 00:57	03/21/2008 01:47	
3.7585	3.7585	3.0781	
GCMSP1	GCMSP1	GCMSP1	
ppbV	ppbV	ppbV	

Surrogate Compound	% Reco	very Limits	F	% Recov	ery Limits	J.F.	% Reco	overy Limits F
1-Bromo-4-fluorobenzene	81	70-130		79	70-130		81	70-130
1.2-Dichloroethane-d4	137	70-130	Q	136	70-130	Q	136	70-130 Q
Toluene-d8	99	70-130		98	70-130		97	70-130

SECTION V Analytical Results

VOC **TO15 Ambient**

Client Sample ID Lab Sample ID Matrix Reported As % Moisture **Date/Time Collected Date/Time Prepared** Date/Time Analyzed Dilution Factor Instrument Units

TO-FD-03E	TO-FD-03W	TO-FD-03W
2080304005	2080304006	2080304006
Air	Air	Air
RECEIVED	RECEIVED	RECEIVED
NA	NA	NA
03/12/2008 09:00	03/12/2008 09:00	03/12/2008 09:00
03/26/2008 02:02	03/21/2008 02:52	03/26/2008 03:08
03/26/2008 02:02	03/21/2008 02:52	03/26/2008 03:08
3.0781	3.0048	3.0048
GCMSP1	GCMSP1	GCMSP1
ppbV	ppbV	ppbV

Parameter	CAS	Conc	Flag	DL	PQL	Conc	Flag	DL	PQL	Conc	Flag	DL	PQL
cis-1,2-Dichloroethene	156-59-2	ND		0.125	0.616	0.130	J	0.122	0.601	0.155	J	0.122	0.601
Trichloroethene	79-01-6	0.213	J	0.159	0.616	0.559	J	0.155	0.601	0.639		0.155	0.601
Vinyl chloride	75-01-4	ND		0.137	0.616	ND		0.134	0.601	ND		0.134	0.601

SECTION V Analytical Results Surrogates

VOC TO15 Ambient

Client Sample ID
Lab Sample ID
Matrix
Reported As
% Moisture
Date/Time Collected
Date/Time Prepared
Date/Time Analyzed
Dilution Factor
Instrument
Units

TO-FD-03E	TO-FD-03W	TO-FD-03W	
2080304005	2080304006	2080304006	
Air	Air	Air	
RECEIVED	RECEIVED	RECEIVED	
NA	NA	NA	1
03/12/2008 09:00	03/12/2008 09:00	03/12/2008 09:00	
03/26/2008 02:02	03/21/2008 02:52	03/26/2008 03:08	
03/26/2008 02:02	03/21/2008 02:52	03/26/2008 03:08	
3.0781	3.0048	3.0048	
GCMSP1	GCMSP1	GCMSP1	
ppbV	ppbV	ppbV	

31

Surrogate Compound	% Recovery	Limits F	% Recovery	Limits	F	% Recovery	Limits	:E
1-Bromo-4-fluorobenzene	78	70-130	82	70-130		79	70-130	
1,2-Dichloroethane-d4	136	70-130 Q	134	70-130	Q	134	70-130	Q
Toluene-d8	100	70-130	98	70-130		100	70-130	

SECTION VI Calibration and QC Information Calibration Verification Results

VOC **TO15 Ambient**

Sample Type:

Continuing Calibration Check

Analysis Batch ID:

54694

Instrument Data File: PA032005.D

Date/Time Analyzed:03/20/2008 13:06

Instrument ID:

GCMSP1

Analyst:

EDN

Units:

ppbV

Parameter	Reference Value	Measured Conc	Flag %Recovery	Flag QC Limits %Recovery
cis-1,2-Dichloroethene	11	13.0	118	70-130
Trichloroethene	10.8	11.4	106	70-130
Vinyl chloride	10.5	12.6	120	70-130

SECTION VI Calibration and QC Information **Calibration Verification Results**

VOC **TO15 Ambient**

Sample Type:

Continuing Calibration Check

Analysis Batch ID:

54798

Instrument Data File: PA032502.D

Date/Time Analyzed:03/25/2008 10:49

Instrument ID:

GCMSP1

Analyst:

EDN

Units:

ppbV

Parameter	Reference Value	Measured Conc	Flag %Recovery	Flag QC Limits %Recovery
cis-1,2-Dichloroethene	11	10.4	94	70-130
Trichloroethene	10.8	9.12	85	70-130
Vinyl chloride	10.5	9.14	87	70-130

SECTION VI Calibration and QC Information Mass Spectrometer Tune

VOC TO15 Ambient BFB

Analysis Batch ID: 54694
Instrument ID: GCMSP1

Instrument Data File:

PA032003.D

Date Analyzed: 03/20/2008 11:02

Injection Time: 03/20/2008 11:02

Analyst: EDN

		nce Criteria			
Mass/Energy	Lower Limit	Upper Limit	% Relative Abundance		
50	8	40	20.4		
75	30	66	55.1		
95	100	100	100		
96	5	9	6.8		
173	0	2	.2		
174	50	120	92.4		
175	4	9	6.8		
176 93		101	93.1		
177	5	9	6.4		

SECTION VI Calibration and QC Information Mass Spectrometer Tune

VOC TO15 Ambient BFB

Analysis Batch ID: 54798
Instrument ID: GCMSP1

Instrument Data File:

Injection Time:

PA032502.D 03/25/2008 10:49 Date Analyzed: 03/25/2008 10:49

Analyst: EDN

	lon Abunda	nce Criteria	
Mass/Energy	Lower Limit	Upper Limit	% Relative Abundance
50	8	40	20.1
75	30	66	56.3
95	100	100	100
96	5	9 .	6.4
173	0	2	1.5
174	50	120	94.9
175	4	9	7.2
176	93	101	93.2
177	5	9	6.6

SECTION VI Calibration and QC Information **Method Blank Results**

VOC **TO15 Ambient**

Method Blank ID Sample Type Matrix **Date/Time Prepared** Date/Time Analyzed Instrument Units

1071615	1071663	
Method Blank	Method Blank	
Air	Air	
03/20/2008 14:07	03/25/2008 13:57	
03/20/2008 14:07	03/25/2008 13:57	
GCMSP1	GCMSP1	
ppbV	ppbV	

Parameter	CAS	Conc Flag	DL	PQL	Conc F	lag DL	PQL	Conc Flag	DL PQL
cis-1.2-Dichloroethene	156-59-2	ND	0.0407	0.200	ND	0.0407	0.200		
Trichloroethene	79-01-6	ND	0.0517	0.200	ND	0.0517	0.200		
Vinyl chloride	75-01-4	ND	0.0445	0.200	ND	0.0445	0.200		

TestAmerica Austin

SECTION VI Calibration and QC Information **Method Blank Results**

VOC **TO15 Ambient**

> Method Blank ID Sample Type Matrix Date/Time Prepared Date/Time Analyzed Instrument Units

1071615	1071663	
Method Blank	Method Blank	
Air	Air	
03/20/2008 14:07	03/25/2008 13:57	
03/20/2008 14:07	03/25/2008 13:57	
GCMSP1	GCMSP1	
ppbV	ppbV	

Surrogate Compound	% Recovery	Limits F	% Recovery	Limits F	% Recovery Limits F
1-Bromo-4-fluorobenzene	84	70-130	83	70-130	
1,2-Dichloroethane-d4	118	70-130	120	70-130	
Toluene-d8	92	70-130	92	70-130	

VOC TO15 Ambient

Client Sample ID:

LCS4 for HBN 54694 [VOC/7387]

Instrument ID:

GCMSP1

% Moisture:

NA

Prep Batch ID:

54694

Units: Matrix: ppbV Air Analyst:

EDN

Analysis Batch ID:

54694

Control Sample

Control Sample Duplicate

		COMMENCE	pic		COMMON OF DURING	thre wahrrence			
	i interior de la compara de l			Lab ID: 1071614 File ID: PA032004.D				QC Limits	
Parameter	Spk Amt	Conc	%Rec Flg	Spk Amt	Conc	%Rec Flg	RPD FIg	%Rec	RPD
cis-1,2-Dichloroethene	11.2	12.1	108	11.2	12.3	110	1.8	70-130	25
Trichloroethene	11.3	10.5	93	11.3	10.9	97	4.2	70-130	25
Vinyl chloride	10.8	11.2	104	10.8	11.7	108	3.8	70-130	25

VOC **TO15 Ambient**

	Lab ID: 1071613	Lab ID: 1071614	
Surrogate Compounds	%Recovery	Flags %Recovery	Flags QC Recovery Limits
1-Bromo-4-fluorobenzene	106	106	70-130
1,2-Dichloroethane-d4	112	110	70-130
Toluene-d8	97	96	70-130

SECTION V Analytical Results

VOC **TO15 Ambient**

Client Sample ID Lab Sample ID Matrix Reported As % Moisture **Date/Time Collected Date/Time Prepared** Date/Time Analyzed Dilution Factor Instrument Units

TO-FD-03E	TO-FD-03W	TO-FD-03W
2080304005	2080304006	2080304006
Air	Air	Air
RECEIVED	RECEIVED	RECEIVED
NA	NA	NA
03/12/2008 09:00	03/12/2008 09:00	03/12/2008 09:00
03/26/2008 02:02	03/21/2008 02:52	03/26/2008 03:08
03/26/2008 02:02	03/21/2008 02:52	03/26/2008 03:08
3.0781	3.0048	3.0048
GCMSP1	GCMSP1	GCMSP1
ppbV	ppbV	ppbV

Parameter	CAS	Conc	Flag	DL	PQL	Conc	Flag	DL	PQL	Conc	Flag	DL	PQL
cis-1,2-Dichloroethene	156-59-2	ND		0.125	0.616	0.130	J	0.122	0.601	0.155	J	0.122	0.601
Trichloroethene	79-01-6	0.213	J	0.159	0.616	0.559	J	0.155	0.601	0.639		0.155	0.601
Vinyl chloride	75-01-4	ND		0.137	0.616	ND		0.134	0.601	ND		0.134	0.601

SECTION V Analytical Results Surrogates

VOC TO15 Ambient

Client Sample ID
Lab Sample ID
Matrix
Reported As
% Moisture
Date/Time Collected
Date/Time Prepared
Date/Time Analyzed
Dilution Factor
Instrument
Units

TO-FD-03E	TO-FD-03W	TO-FD-03W	
2080304005	2080304006	2080304006	
Air	Air	Air	
RECEIVED	RECEIVED	RECEIVED	
NA	NA	NA	1
03/12/2008 09:00	03/12/2008 09:00	03/12/2008 09:00	
03/26/2008 02:02	03/21/2008 02:52	03/26/2008 03:08	
03/26/2008 02:02	03/21/2008 02:52	03/26/2008 03:08	
3.0781	3.0048	3.0048	
GCMSP1	GCMSP1	GCMSP1	
ppbV	ppbV	ppbV	

31

Surrogate Compound	% Recovery	Limits F	% Recovery	Limits	F	% Recovery	Limits	:E
1-Bromo-4-fluorobenzene	78	70-130	82	70-130		79	70-130	
1,2-Dichloroethane-d4	136	70-130 Q	134	70-130	Q	134	70-130	Q
Toluene-d8	100	70-130	98	70-130		100	70-130	

SECTION VI Calibration and QC Information Calibration Verification Results

VOC **TO15 Ambient**

Sample Type:

Continuing Calibration Check

Analysis Batch ID:

54694

Instrument Data File: PA032005.D

Date/Time Analyzed:03/20/2008 13:06

Instrument ID:

GCMSP1

Analyst:

EDN

Units:

ppbV

Parameter	Reference Value	Measured Conc	Flag %Recovery	Flag QC Limits %Recovery
cis-1,2-Dichloroethene	11	13.0	118	70-130
Trichloroethene	10.8	11.4	106	70-130
Vinyl chloride	10.5	12.6	120	70-130

SECTION VI Calibration and QC Information **Calibration Verification Results**

VOC **TO15 Ambient**

Sample Type:

Continuing Calibration Check

Analysis Batch ID:

54798

Instrument Data File: PA032502.D

Date/Time Analyzed:03/25/2008 10:49

Instrument ID:

GCMSP1

Analyst:

EDN

Units:

ppbV

Parameter	Reference Value	Measured Conc	Flag %Recovery	Flag QC Limits %Recovery
cis-1,2-Dichloroethene	11	10.4	94	70-130
Trichloroethene	10.8	9.12	85	70-130
Vinyl chloride	10.5	9.14	87	70-130

SECTION VI Calibration and QC Information Mass Spectrometer Tune

VOC TO15 Ambient BFB

Analysis Batch ID: 54694
Instrument ID: GCMSP1

Instrument Data File:

PA032003.D

Date Analyzed: 03/20/2008 11:02

Injection Time: 03/20/2008 11:02

Analyst: EDN

		nce Criteria	
Mass/Energy	Lower Limit	Upper Limit	% Relative Abundance
50	8	40	20.4
75	30	66	55.1
95	100	100	100
96	5	9	6.8
173	0	2	.2
174	50	120	92.4
175	4	9	6.8
176	93	101	93.1
177	5	9	6.4

SECTION VI Calibration and QC Information Mass Spectrometer Tune

VOC TO15 Ambient BFB

Analysis Batch ID: 54798
Instrument ID: GCMSP1

Instrument Data File:

Injection Time:

PA032502.D 03/25/2008 10:49 Date Analyzed: 03/25/2008 10:49

Analyst: EDN

	lon Abunda	nce Criteria	
Mass/Energy	Lower Limit	Upper Limit	% Relative Abundance
50	8	40	20.1
75	30	66	56.3
95	100	100	100
96	5	9 .	6.4
173	0	2	1.5
174	50	120	94.9
175	4	9	7.2
176	93	101	93.2
177	5	9	6.6

SECTION VI Calibration and QC Information **Method Blank Results**

VOC **TO15 Ambient**

Method Blank ID Sample Type Matrix **Date/Time Prepared** Date/Time Analyzed Instrument Units

1071615	1071663	
Method Blank	Method Blank	
Air	Air	
03/20/2008 14:07	03/25/2008 13:57	
03/20/2008 14:07	03/25/2008 13:57	
GCMSP1	GCMSP1	
ppbV	ppbV	

Parameter	CAS	Conc Flag	DL	PQL	Conc Flag	DL	PQL	Conc F	lag DL PQL
cis-1.2-Dichloroethene	156-59-2	ND	0.0407	0.200	ND	0.0407	0.200		
Trichloroethene	79-01-6	ND	0.0517	0.200	ND	0.0517	0.200		
Vinyl chloride	75-01-4	ND	0.0445	0.200	ND	0.0445	0.200		

TestAmerica Austin

SECTION VI Calibration and QC Information **Method Blank Results**

VOC **TO15 Ambient**

> Method Blank ID Sample Type Matrix **Date/Time Prepared** Date/Time Analyzed Instrument Units

1071615	1071663	
Method Blank	Method Blank	
Air	Air	
03/20/2008 14:07	03/25/2008 13:57	
03/20/2008 14:07	03/25/2008 13:57	
GCMSP1	GCMSP1	
ppbV	ppbV	

Surrogate Compound	% Recover	y Limits F	% Recove	ry Limits F	% Recovery Limits F
1-Bromo-4-fluorobenzene	84	70-130	83	70-130	
1,2-Dichloroethane-d4	118	70-130	120	70-130	
Toluene-d8	92	70-130	92	70-130	

VOC **TO15 Ambient**

Client Sample ID:

LCS4 for HBN 54694 [VOC/7387]

Instrument ID:

% Moisture:

NA

Prep Batch ID:

54694

Units: Matrix: ppbV Air

GCMSP1

Analyst:

EDN

Analysis Batch ID:

54694

Control Sample

Control Sample Duplicate

	Lab ID: 1071613 File ID: PA032003.D			Lab ID: 1071614 File ID: PA032004.D			QC Limits		
Parameter	Spk Amt	Conc	%Rec Flg	Spk Amt	Conc	%Rec Flg	RPD Flg	%Rec	RPD
cis-1,2-Dichloroethene	11.2	12.1	108	11.2	12.3	110	1.8	70-130	25
Trichloroethene	11.3	10.5	93	11.3	10.9	97	4.2	70-130	25
Vinyl chloride	10.8	11.2	104	10.8	11.7	108	3.8	70-130	25

VOC **TO15 Ambient**

	Lab ID: 1071613	Lab ID: 1071614	
Surrogate Compounds	%Recovery Flags	%Recovery Flags	QC Recovery Limits
1-Bromo-4-fluorobenzene	106	106	70-130
1,2-Dichloroethane-d4	112	110	70-130
Toluene-d8	97	96	70-130

VOC **TO15 Ambient**

Client Sample ID:

LCS6 for HBN 54798 [VOC/7397]

Instrument ID: GCMSP1

% Moisture:

NA

Prep Batch ID:

54798

Units:

ppbV

Analyst:

EDN

Analysis Batch ID:

54798

Matrix:

Air

Control Sample

Control Sample Duplicate

	Lab ID: 1071661 File ID: PA032503.D			Lab ID: 1071662 File ID: PA032504.D				QC Limits		
Parameter	Spk Amt	Conc	%Rec Flg	Spk Amt	Conc	%Rec Flg	RPD Flg	%Rec	RPD	
cis-1,2-Dichloroethene	11.4	11.8	104	11.4	11.5	100	3.9	70-130	25	
Trichloroethene	11.5	10.6	92	11.5	10.2	88	4.4	70-130	25	
Vinyl chloride	11	11.3	103	11	10.5	96	7	70-130	25	

VOC **TO15 Ambient**

	Lab ID: 1071661	Lab ID: 1071662	
Surrogate Compounds	%Recovery Flags	%Recovery Flags	QC Recovery Limits
1-Bromo-4-fluorobenzene	108	118	70-130
1,2-Dichloroethane-d4	116	115	70-130
Toluene-d8	97	96	70-130

Extraction/Digestion Batch Summary VOC **TO15 Ambient**

Extraction Batch ID:

54694

Start Date/Time:

03/20/2008 11:02

Analyst:

EDN

Stop Date/Time:

03/21/2008 05:51

				Samp	le Size	
Client Sample ID	Lab Sample ID	Sample Type	Matrix	Initial	Final	Preparation Method
INSTRUMENT QC	1000	GC/MS Tune	Air	0.5 L	1 L	TO15 Ambient
LCS4 for HBN 54694 [VOC/7387]	1071613	Lab Control Sample	Air	0.5 L	1 L	TO15 Ambient
LCSD4 for HBN 54694 [VOC/7387]	1071614	Lab Control Sample Duplicate	Air	0.5 L	1 L	TO15 Ambient
INSTRUMENT QC	1493	Continuing Calibration Check	Air	0.5 L	1 L	TO15 Ambient
MB for HBN 54694 [VOC/7387]	1071615	Method Blank	Air	0.5 L	1 L	TO15 Ambient
ZZZZZZZZZ	2080303401	Field Sample	Air	0.5 L	1 L	TO15 Ambient
ZZZZZZZZZ	2080303501	Field Sample	Air	0.5 L	1 L	TO15 Ambient
ZZZZZZZZZZ	2080303402	Field Sample	Air	0.5 L	1 L	TO15 Ambient
ZZZZZZZZZZ	2080303502	Field Sample	Air	0.5 L	1 L	TO15 Ambient
ZZZZZZZZZZ	2080303403	Field Sample	Air	0.5 L	1 L	TO15 Ambient
ZZZZZZZZZZ	2080303503	Field Sample	Air	0.5 L	1 L	TO15 Ambient
ZZZZZZZZZZ	1071628	Duplicate Sample	Air	0.5 L	1 L	TO15 Ambient
ZZZZZZZZZ	1071629	Duplicate Sample	Air	0.5 L	1 L	TO15 Ambient
ZZZZZZZZZ	2080303404	Field Sample	Air	0.5 L	1 L	TO15 Ambient
ZZZZZZZZZ	2080303504	Field Sample	Air	0.5 L	1 L	TO15 Ambient
ZZZZZZZZZZ	2080303405	Field Sample	Air	0.5 L	1 L	TO15 Ambient
ZZZZZZZZZ	2080303505	Field Sample	Air	0.5 L	1 L	TO15 Ambient
TO-FD-01E	2080304001	Field Sample	Air	0.5 L	1 L	TO15 Ambient
TO-FD-01W	2080304002	Field Sample	Air	0.5 L	1 L	TO15 Ambient
TO-FD-02E	2080304003	Field Sample	Air	0.5 L	1 L	TO15 Ambient
TO-FD-02W	2080304004	Field Sample	Air	0.5 L	1 L	TO15 Ambient
TO-FD-03E	2080304005	Field Sample	Air	0.5 L	1 L	TO15 Ambient
TO-FD-03W	2080304006	Field Sample	Air	0.5 L	1 L	TO15 Ambient
ZZZZZZZZZZ	2080303002	Field Sample	Air	0.1 L	1 L	TO15 Ambient
ZZZZZZZZZZ	2080303003	Field Sample	Air	0.1 L	1 L	TO15 Ambient
ZZZZZZZZZZ	1071630	Duplicate Sample	Air	0.1 L	1 L	TO15 Ambient

Extraction/Digestion Batch Summary VOC TO15 Ambient

Extraction Batch ID:

54798

Start Date/Time:

03/25/2008 10:49

Analyst:

EDN

Stop Date/Time:

03/26/2008 03:08

				Sample	e Size	
Client Sample ID	Lab Sample ID	Sample Type	Matrix	Initial	Final	Preparation Method
INSTRUMENT QC	1000	GC/MS Tune	Air	0.5 L	1 L	TO15 Ambient
INSTRUMENT QC	1493	Continuing Calibration Check	Air	0.5 L	1 L	TO15 Ambient
LCS6 for HBN 54798 [VOC/7397]	1071661	Lab Control Sample	Air	0.5 L	1 L	TO15 Ambient
LCSD6 for HBN 54798 [VOC/7397]	1071662	Lab Control Sample Duplicate	Air	0.5 L	1 L	TO15 Ambient
MB for HBN 54798 [VOC/7397]	1071663	Method Blank	Air	0.5 L	1 L	TO15 Ambient
ZZZZZZZZZZ	2080305501	Field Sample	Air	0.5 L	1 L	TO15 Ambient
ZZZZZZZZZZ	2080305502	Field Sample	Air	0.5 L	1 L	TO15 Ambient
ZZZZZZZZZZ	2080305503	Field Sample	Air	0.5 L	1 L	TO15 Ambient
ZZZZZZZZZZ	1071670	Duplicate Sample	Air	0.5 L	1 L	TO15 Ambient
ZZZZZZZZZZ	2080305504	Field Sample	Air	0.5 L	1 L	TO15 Ambient
ZZZZZZZZZ	2080305505	Field Sample	Air	0.5 L	1 L	TO15 Ambient
TO-FD-01E	2080304001	Field Sample	Air	0.5 L	1 L	TO15 Ambient
TO-FD-01W	2080304002	Field Sample	Air	0.5 L	1 L	TO15 Ambient
TO-FD-02E	2080304003	Field Sample	Air	0.5 L	1 L	TO15 Ambient
TO-FD-02W	2080304004	Field Sample	Air	0.5 L	1 L	TO15 Ambient
TO-FD-03E	2080304005	Field Sample	Air	0.5 L	1 L	TO15 Ambient
TO-FD-03W	2080304006	Field Sample	Air	0.5 L	1 L	TO15 Ambient

Analysis Batch Summary VOC TO15 Ambient

Analysis Batch ID:

54694

Instrument ID:

GCMSP1

Analyst:

EDN

			Ana	lysis			Sub-
Sequence	Client Sample ID	Lab Sample ID	Date	Time	Sample Type	Analysis File ID	Batch ID
1	INSTRUMENT QC	1000	03/20/2008	11:02:00	GC/MS Tune	PA032003.D	0
2	LCS4 for HBN 54694 [VOC/7387]	1071613	03/20/2008	11:02:00	Lab Control Sample	PA032003.D	0
3	LCSD4 for HBN 54694 [VOC/7387]	1071614	03/20/2008	12:04:00	Lab Control Sample Duplicate	PA032004.D	0
4	INSTRUMENT QC	1493	03/20/2008	13:06:00	Continuing Calibration Check	PA032005.D	0
5	MB for HBN 54694 [VOC/7387]	1071615	03/20/2008	14:07:00	Method Blank	PA032006.D	0
6	ZZZZZZZZZZ	2080303401	03/20/2008	15:08:00	Field Sample	PA032007.D	0
7	ZZZZZZZZZZ	2080303501	03/20/2008	15:08:00	Field Sample	PA032007.D	0
8	ZZZZZZZZZ	2080303402	03/20/2008	16:11:00	Field Sample	PA032008.D	0
9	ZZZZZZZZZZ	2080303502	03/20/2008	16:11:00	Field Sample	PA032008.D	0
10	ZZZZZZZZZZ	2080303403	03/20/2008	17:14:00	Field Sample	PA032009.D	0
11	ZZZZZZZZZZ	2080303503	03/20/2008	17:14:00	Field Sample	PA032009.D	0
12	ZZZZZZZZZ	1071628	03/20/2008	18:17:00	Duplicate Sample	PA032010.D	0
13	ZZZZZZZZZZ	1071629	03/20/2008	18:17:00	Duplicate Sample	PA032010.D	0
14	ZZZZZZZZZZ	2080303404	03/20/2008	19:21:00	Field Sample	PA032011.D	0
15	ZZZZZZZZZZ	2080303504	03/20/2008	19:21:00	Field Sample	PA032011.D	0
16	ZZZZZZZZZZ	2080303405	03/20/2008	20:27:00	Field Sample	PA032012.D	0
17	ZZZZZZZZZZ	2080303505	03/20/2008	20:27:00	Field Sample	PA032012.D	0
18	TO-FD-01E	2080304001	03/20/2008	21:31:00	Field Sample	PA032013.D	0
19	TO-FD-01W	2080304002	03/20/2008	22:35:00	Field Sample	PA032014.D	0
20	TO-FD-02E	2080304003	03/20/2008	23:39:00	Field Sample	PA032015.D	0
21	TO-FD-02W	2080304004	03/21/2008	00:43:00	Field Sample	PA032016.D	0
22	TO-FD-03E	2080304005	03/21/2008	01:47:00	Field Sample	PA032017.D	0
23	TO-FD-03W	2080304006	03/21/2008	02:52:00	Field Sample	PA032018.D	0
24	ZZZZZZZZZZ	2080303002	03/21/2008	03:51:00	Field Sample	PA032019.D	0
25	ZZZZZZZZZZ	2080303003	03/21/2008	04:51:00	Field Sample	PA032020.D	0
26	ZZZZZZZZZZ	1071630	03/21/2008	05:51:00	Duplicate Sample	PA032021.D	0

Analysis Batch Summary VOC TO15 Ambient

Analysis Batch ID:

54798

Instrument ID:

GCMSP1

Analyst:

EDN

			Anal	lysis			Sub-
Sequence	Client Sample ID	Lab Sample ID	Date	Time	Sample Type	Analysis File ID	Batch ID
1	INSTRUMENT QC	1000	03/25/2008	10:49:00	GC/MS Tune	PA032502.D	0
2	INSTRUMENT QC	1493	03/25/2008	10:49:00	Continuing Calibration Check	PA032502.D	0
3	LCS6 for HBN 54798 [VOC/7397]	1071661	03/25/2008	11:51:00	Lab Control Sample	PA032503.D	0
4	LCSD6 for HBN 54798 [VOC/7397]	1071662	03/25/2008	12:54:00	Lab Control Sample Duplicate	PA032504.D	0
5	MB for HBN 54798 [VOC/7397]	1071663	03/25/2008	13:57:00	Method Blank	PA032505.D	0
6	ZZZZZZZZZZ	2080305501	03/25/2008	15:03:00	Field Sample	PA032506.D	0
7	ZZZZZZZZZZ	2080305502	03/25/2008	16:09:00	Field Sample	PA032507.D	0
8	ZZZZZZZZZZZ	2080305503	03/25/2008	17:15:00	Field Sample	PA032508.D	0
9	ZZZZZZZZZZ	1071670	03/25/2008	18:21:00	Duplicate Sample	PA032509.D	0
10	ZZZZZZZZZZZ	2080305504	03/25/2008	19:27:00	Field Sample	PA032510.D	0
11	ZZZZZZZZZZ	2080305505	03/25/2008	20:33:00	Field Sample	PA032511.D	0
12	TO-FD-01E	2080304001	03/25/2008	21:39:00	Field Sample	PA032512.D	0
13	TO-FD-01W	2080304002	03/25/2008	22:45:00	Field Sample	PA032513.D	0
14	TO-FD-02E	2080304003	03/25/2008	23:51:00	Field Sample	PA032514.D	0
15	TO-FD-02W	2080304004	03/26/2008	00:57:00	Field Sample	PA032515.D	0
16	TO-FD-03E	2080304005	03/26/2008	02:02:00	Field Sample	PA032516.D	0
17	TO-FD-03W	2080304006	03/26/2008	03:08:00	Field Sample	PA032517.D	0

SECTION VIII Certifications

State/Agency	ID#
Arkansas Department of Environmental Quality	
California Environmental Laboratory Accreditation Program / Waste Water/Hazardous Waste	2411
Kansas Department of Health and Environment / Solid and Hazardous Waste / Wastewater	E-10165
Louisiana Department of Environmental Quality, ELAP / Waste Water/Hazardous Waste/Air Emissions	30736
North Carolina Dept. of Natural Resources & Community Development / Waste Water / Ground Water	302
Oklahoma Department of Environmental Quality/General Water Quality/Sludge	8720
PA Department of Environmental Protection	68-04085
South Carolina Dept. of Health & Environmental Control / Solid & Hazardous Waste / CWA	82003
Texas Commission on Environmental Quality (TCEQ) NELAP	T104704217-06-TX
Texas Department of Public Safety/Precursor Chemical and Lab Apparatus	3039
US Department of Agriculture / Restricted Soils Permit	S-42350

SECTION VIII - Certifications - 03/31/2008 09:32

LIMS Workorder: Impex Crawfordsville [20803040] ENTACT

SECTION IX Notes

The results included in this report have been reviewed for compliance with the laboratory QA/QC plan and meet all requirements of NELAC. All data have been found to be compliant with laboratory protocol except as otherwise noted.

Note that if this report contains tests performed for the following methods, the associated method deviations are applicable:

EPA 410.4, COD:	Use of different analytical wavelength as specified by instrument manufacturer.	
EPA 340.2, Fluoride:	Preliminary Bellack distillation not performed.	
IOWA OA1:	Benzene, toluene, ethylbenzene and xylenes (BTEX) not analyzed along with Gasoline Range Organics	
IOWA OA1 (cont):	if client does not require BTEX.	
EPA TO12:	Samples not analyzed in duplicate.	
EPA TO14A and TO15:	Zero humidified nitrogen is used in place of air for method blanks.	
EPA 624:	Laboratory uses a different desorb time and purge volume than stated in the method.	

For all methods that require matrix spike/matrix spike duplicate or laboratory duplicate analyses: In cases where insufficient sample volume is available for method required matrix spike, matrix spike duplicate and/or laboratory duplicate analyses, these QC analyses will not be included in the report.

TRRP Reporting Requirements

If this package contains reports requiring TRRP (Texas Risk Reduction Program) reporting criteria, the following information applies.

The REPORTING LIMIT (RL) is equivalent to the TRRP acronym MQL (method quantitation limit).

The METHOD DETECTION LIMIT (MDL) is equivalent to the TRRP acronym SDL (sample detection limit).

31

ಕ

LIMS Workorder: Impex Crawfordsville [20803040] ENTACT SECTION X - COC/Addendum - 03/31/2008 09:32

Revised 10/17/07

FestAmerica Austin

ö

Lot No: 4.0 CONDITION OF BOTTLES/CONTAINERS VERIFIED BY: Samples received match COC: YES NO Bottles received intact: TYES TNO See additional discrepancies/comments section: YES NO Samples received from USDA restricted area: YES NO Chain-of-Custody form properly maintained: YES NO VOA trip blanks included: ☐ YES ☐ NO ☐ N/A 5.0 ADDITIONAL DISCREPANCIES Appears on COC Appears on Label Date/Time Sample ID Sample ID Date/Time Comments 6.0 SHIPPING DOCUMENTATION: Air/freight bill is available and attached to COC: TES NO Air bill #: _ Hand-delivered Carrier:_____ 7.0 OTHER COMMENTS: Received GXVFR SN# 7500138, 1300954, 7301018 7300947, 1299272, 7301137 CORRECTIVE ACTION: Client's Name: Informed verbally on: _ Client's Name: Informed verbally on: ___ Sample(s) processed "as is" comments: Samples(s) on hold until: If released, notify: REVIEW: Project Management: SIGNED ORIGINAL MUST BE RETAINED IN THE PROJECT FILE

31

TestAmerica - Austin 14050 Summit Drive					
		,			
Austin, TX 78728 Tel. 512-244-0855 Fax 512-244-0160	VOC Chain of Custody Record	Record			
	SAMPLING	O A STATE OF THE PARTY OF THE P		Pageof	
ENTACT - TORK COLOR		SHIMPLING 17PE	ANALYSIS	FIELD	· -
COLLECTED BY (Signature) A A A Coney	J.	ΞŪ	. SW/OS	ESSUPE	
	DATE	VENT VENT OID	ABIENT	ED GAS IG) IG) AL PRE IG)	
Crawford		3	OS OS	Sa) Lini	
70-FD - 03E SHIP				-30 C	
31.	00:00 00:00			12	
70- FD-03E " 5465	+				
2	00:60			-30 -5	
6				S- 05-	
DESTRUCTO					
FOTACT					
3139 Bass As Done	contact		CONVERSION FACTOR: Hg x 0.49116 - PSIG	Hg x 0.49116 - PSIG	
Grapewie, TX 76051	Haren McCorney 630-935-9459				
	anccorved@ entact.	act.com			
	•				
	DATE TIME RELINQUISHED BY	7,000			
Serve house			RECEIVED BY:	DATE: TIME	
RECEIVED FOR JOBORATORY BY: DATE TIME	ARBILL NO MODICOLO				-
14 3-17-08 0800	2080 3040	ER: SHELF LOCATION:	N: # OF VFR'S	'S # OF FILTERS	

SECTION X - COC/Addendum - 03/31/2008 09:32 LIMS Workorder: Impex Crawfordsville [20803040] ENTACT **TestAmerica Austin**

VOC PREP REPORT (by HSN)

			Initial	Final	Final		Initial	Primary	Ų.	
	Canister	•	Pressure	Pressure Pressure	Pressure	Diluent	Dilution	Dilution		Final
HSN ID	I	Prep Date (PSIG) (PSIG)	(PSIG)	(PSIG) ("Hg)	("Hg)	Added	Factor Factor Dilution	Factor	D	Dilution
2080304001 5424		3/20/2008 15:36:41	-14.05	7.0	•	0	22.5	_	2.522	2.522
2080304002 5416	5416	3/20/2008 15:36:42	-14.05	-1.5717		3.2	22.5	-	2.9812	2.9812
2080304003 5447	5447	3/20/2008 15:37:00	-14.05	-1.8664		3.8	22.5	-	3.0533	3.0533
2080304004 5438	5438	3/20/2008 15:37:17	-14.05	-4.1257		8.4	22.6	-	3.7585	3.7585
2080304005 5465	5465	3/20/2008-15:37:59	-14.05	-1.9646	6	4	22.5	-	3.0781	3.0781
2080304006 5426	5426	3/20/2008 15:38:32	-14.05	-1.6699		3.4	22.5	-	3.0048	3.0048



ANALYTICAL REPORT

Job Number: 560-9081-1

Job Description: Crawfordsville, IN

For: Entact, LLC 3129 Bass Pro Drive Grapevine, TX 76051

Attention: Mr. Aaron McCorvey

Julie Darrow
Project Manager I
julie.darrow@testamericainc.com
03/28/2008

The test results entered in this report meet all NELAC requirements for accredited parameters. Any exceptions to NELAC requirements are noted in the report. Pursuant to NELAC, this report may not be reproduced except in full, and with written approval from the laboratory. TestAmerica Corpus Christi Certifications and Approvals: NELAC TX T104704210-06-TX, NELAC KS E-10362, Oklahoma 9968, USDA Soil Permit S-42935 Revised.



Job Narrative 560-J9081-1

Volatile Orgaincs Analysis

Sample 560-9081-1 was analyzed for volatile orgainics using EPA 8260C in batch 560-21194. During the extraction process, the spiking compounds were inadvertently omitted. Therefore, matrix spike and matrix spike duplicate recoveries were not available. The method blank and LCS were within acceptable limits and the data are therefore reported.

No other analytical or quality issues were noted.

EXECUTIVE SUMMARY - Detections

Client: Entact, LLC Job Number: 560-9081-1

Lab Sample ID Analyte	Client Sample ID	Result / 0	Qualifier	Reporting Limit	Units	Method
560-9081-1	FD-S88-PRE					
cis-1,2-Dichloroether TCE Percent Moisture Percent Solids	ne	400 4900 6.2 94	J	490 490 0.010 0.010	ug/Kg ug/Kg % %	8260B 8260B PercentMoisture PercentMoisture

METHOD SUMMARY

Client: Entact, LLC Job Number: 560-9081-1

Description	Lab Location	Method	Preparation Method
Matrix Solid			
Volatile Organic Compounds by GC/MS	TAL CC	SW846 8260B	
Closed System Purge & Trap/Laboratory Preservation	TAL CC		SW846 5035

Lab References:

TAL CC = TestAmerica Corpus Christi

Method References:

SW846 = "Test Methods For Evaluating Solid Waste, Physical/Chemical Methods", Third Edition, November 1986 And Its Updates.

METHOD / ANALYST SUMMARY

Client: Entact, LLC Job Number: 560-9081-1

Method	Analyst	Analyst ID
SW846 8260B	Newman, David	DN
EPA PercentMoisture	Zwierzykowski. Hanna M	HMZ

SAMPLE SUMMARY

Client: Entact, LLC Job Number: 560-9081-1

			Date/Time	Date/Time
Lab Sample ID	Client Sample ID	Client Matrix	Sampled	Received
560-9081-1	FD-S88-PRE	Solid	03/07/2008 1030	03/10/2008 0850

SAMPLE RESULTS

Client: Entact, LLC Job Number: 560-9081-1

Client Sample ID: FD-S88-PRE

Lab Sample ID: 560-9081-1 Date Sampled: 03/07/2008 1030 Client Matrix: Solid % Moisture: 6.2 Date Received: 03/10/2008 0850

8260B Volatile Organic Compounds by GC/MS

Method:8260BAnalysis Batch: 560-21194Instrument ID:VGCMS#2Preparation:5035Prep Batch: 560-21180Lab File ID:03110707.D

Dilution: 50 Initial Weight/Volume: 5.43 g
Date Analyzed: 03/11/2008 1139 Final Weight/Volume: 10 mL

Date Prepared: 03/11/2008 0907

Analyte	DryWt Corrected: Y Result (ug/Kg)	Qualifier	MDL	RL
Vinyl chloride	<490		49	490
cis-1,2-Dichloroethene	400	J	49	490
TCE	4900		49	490
Surrogate	%Rec		Accept	ance Limits
Dibromofluoromethane (Surr)	105		59 - 1	120
1,2-Dichloroethane-d4 (Surr)	111		71 - 1	120
4-Bromofluorobenzene (Surr)	103		47 - 1	120
Toluene-d8 (Surr)	109		57 - 1	120

Client: Entact, LLC Job Number: 560-9081-1

General Chemistry

Client Sample ID: FD-S88-PRE

 Lab Sample ID:
 560-9081-1
 Date Sampled:
 03/07/2008 1030

 Client Matrix:
 Solid
 Date Received:
 03/10/2008 0850

Analyte	Result	Qual Units	RL	RL	Dil	Method
Percent Moisture	6.2	%	0.010	0.010	1.0	PercentMoisture
	Anly Batch: 560-21169	Date Analyzed	03/10/2008 1330			
Percent Solids	94 Anly Batch: 560-21169	% Date Analyzed	0.010 03/10/2008 1330	0.010	1.0	PercentMoisture

DATA REPORTING QUALIFIERS

Client: Entact, LLC Job Number: 560-9081-1

Lab Section	Qualifier	Description	
GC/MS VOA			
	J	Result is less than the RL but greater than or equal to the	

QUALITY CONTROL RESULTS

Quality Control Results

Client: Entact, LLC Job Number: 560-9081-1

QC Association Summary

Lab Sample ID	Client Sample ID	Report Basis	Client Matrix	Method	Prep Batch
GC/MS VOA	Ollent Gample ID	Buolo	Offerit Waters	Wethou	T Tep Daten
Prep Batch: 560-21180		_			
_CS 560-21180/1-A	Lab Control Spike	T	Solid	5035	
MB 560-21180/2-A	Method Blank	Т	Solid	5035	
560-9081-1	FD-S88-PRE	Т	Solid	5035	
Analysis Batch:560-2119	4				
_CS 560-21180/1-A	Lab Control Spike	Т	Solid	8260B	560-21180
MB 560-21180/2-A	Method Blank	Ť	Solid	8260B	560-21180
560-9081-1	FD-S88-PRE	+	Solid	8260B	560-21180
100-9081-1	FD-300-FRE	ı	Soliu	0200B	300-21100
Report Basis					
T = Total					
General Chemistry					
Analysis Batch:560-2116	9				
560-9081-1	FD-S88-PRE	T	Solid	PercentMoisture	
560-9081-1DU	Duplicate	Т	Solid	PercentMoisture	
			Solid Solid	PercentMoisture PercentMoisture	

Report Basis

T = Total

Client: Entact, LLC Job Number: 560-9081-1

Method Blank - Batch: 560-21180 Method: 8260B Preparation: 5035

Lab Sample ID: MB 560-21180/2-A

Client Matrix: Solid Dilution: 50

Date Analyzed: 03/11/2008 1045 Date Prepared: 03/11/2008 0907 Analysis Batch: 560-21194 Prep Batch: 560-21180

Units: ug/Kg

Instrument ID: VGCMS#2 Lab File ID: 03110705.D Initial Weight/Volume: 5 g

Final Weight/Volume: 10 mL

Analyte	Result	Qual	MDL	RL	
Vinyl chloride	<500		50	500	
cis-1,2-Dichloroethene	<500		50	500	
TCE	<500		50	500	
Surrogate	% Rec		Acceptance Limits		
Dibromofluoromethane (Surr)	109		59 - 120		
Dibromofluoromethane (Surr) 1,2-Dichloroethane-d4 (Surr)	109 111		59 - 120 71 - 120		

Lab Control Spike - Batch: 560-21180 Method: 8260B Preparation: 5035

Lab Sample ID: LCS 560-21180/1-A

Client Matrix: Solid Dilution: 50

Date Analyzed: 03/11/2008 0954 Date Prepared: 03/11/2008 0907 Analysis Batch: 560-21194 Prep Batch: 560-21180

Units: ug/Kg

Instrument ID: VGCMS#2 Lab File ID: 03110703.D Initial Weight/Volume: 5 g

Final Weight/Volume: 10 mL

Date Prepared: 03/11/2008 0907

Analyte Spike Amount Result % Rec. Limit

Vinyl chloride cis-1,2-Dichloroethene TCE	5000 5000 5000	3670 4730 5120	73 95 102	58 - 126 67 - 125 77 - 124	
Surrogate		% Rec	A	Acceptance Limits	
Dibromofluoromethane (Surr)		107		59 - 120	
1,2-Dichloroethane-d4 (Surr)		107		71 - 120	
4-Bromofluorobenzene (Surr)		101		47 - 120	
Toluene-d8 (Surr)		105		57 - 120	

Calculations are performed before rounding to avoid round-off errors in calculated results.

Qual

Quality Control Results

Client: Entact, LLC Job Number: 560-9081-1

Duplicate - Batch: 560-21169

Method: PercentMoisture

Preparation: N/A

Lab Sample ID: 560-9081-1

Client Matrix: Solid Dilution: 1.0

Date Analyzed: 03/10/2008 1330

Date Prepared: N/A

Analysis Batch: 560-21169

Prep Batch: N/A

Units: %

Instrument ID: No Equipment Assigned

Lab File ID: N/A Initial Weight/Volume: Final Weight/Volume:

Analyte	Sample Result/Qual	Result	RPD	Limit	Qual
Percent Moisture Percent Solids	6.2 94	5.8 94	8	20 20	

Calculations are performed before rounding to avoid round-off errors in calculated results.

EPA ARCHIVE DOCUMENT

Client: Entact, LLC Job Number: 560-9081-1

Laboratory Chronicle

Lab ID: 560-9081-1 Client ID: FD-S88-PRE

Sample Date/Time: 03/07/2008 10:30 Received Date/Time: 03/10/2008 08:50

			Analysis		Date Prepared /			
Method	Bottle ID	Run	Batch	Prep Batch	Analyzed	Dil	Lab	Analyst
P:5035	560-9081-C-1-A		560-21194	560-21180	03/11/2008 09:07	50	TAL CC	DN
A:8260B	560-9081-C-1-A		560-21194	560-21180	03/11/2008 11:39	50	TAL CC	DN
A:PercentMoistur	560-9081-A-1		560-21169		03/10/2008 13:30	1	TAL CC	HMZ
е								

Lab ID: 560-9081-1 DU Client ID: FD-S88-PRE

Sample Date/Time: 03/07/2008 10:30 Received Date/Time: 03/10/2008 08:50

Analysis Date Prepared / **Batch Analyzed** Method **Bottle ID** Run Dil **Prep Batch** Lab Analyst A:PercentMoistur 560-9081-A-1 DU 560-21169 03/10/2008 13:30 TAL CC HMZ

Lab ID: MB Client ID: N/A

Sample Date/Time: N/A Received Date/Time: N/A

Analysis Date Prepared / Method Batch **Prep Batch Analyzed Bottle ID** Run Dil Lab Analyst P:5035 MB 560-21180/2-A 560-21194 560-21180 03/11/2008 09:07 50 TAL CC DN A:8260B MB 560-21180/2-A 560-21194 560-21180 03/11/2008 10:45 50 TAL CC DN

Lab ID: LCS Client ID: N/A

Sample Date/Time: N/A Received Date/Time: N/A

Date Prepared / **Analysis Batch** Method **Bottle ID** Run **Prep Batch Analyzed** Dil Lab Analyst 560-21194 P:5035 LCS 560-21180/1-A 560-21180 03/11/2008 09:07 50 TAL CC DN A:8260B LCS 560-21180/1-A 560-21194 560-21180 03/11/2008 09:54 50 TAL CC DN

Lab References:

TAL CC = TestAmerica Corpus Christi

TestAmerica Corpus Christi A = Analytical Method P = Prep Method

US EPA ARCHIVE DOCUMENT | CSTAMPTICO 35000

Chain of Custody Record

TAL-4142 (0907)				TATAL MANAGEMENT AND ADDRESS OF THE PARTY OF	
Client EAMACT	Project Manager	lanager		2-1-0X	364050
Address	Telephor	Telephone Number (Area Code)/Fax Number	ax Number	Lab Number	
Side Bash Pro Drive	630-935	65h6-556		The statement of the st	Page / of
State		24 C. 24 C.	Lab Contact	Analysis (Attach list if more space is needed)	
Project/Name and Location (State)			3p:	3.	
Former IMBG - Crawbooks, ile, IN	0	**************************************	7	- Da	Special Instructions/
Contract/Purchase Order/Guote No.		Matrix		-	Conditions of Aeceipt
Sample I.D. No. and Description (Containers for each sample may be combined on one line)	Date Time	Aqueous Soil	NICON NGOH HOIS HAGS	\$\\5	2000
\vdash	3-7-08 10:30	×	<i>y y y y y y y y y y</i>	2	Facere deviet sor
		-		- Committee of the Comm	Laddand
Paç	A LA				
e					Transfer of the state of the st
146					Annual minore states and a second state and a secon
φf		44			
17	- Control of the Cont				- Constitution of the Cons
On the second se					16000000
A DESCRIPTION OF THE PROPERTY				a de la companya de l	
A TANAMATAN AND AND AND AND AND AND AND AND AND A			-		Andready .
2 -					- APPROXIMATE -
And the second s				The state of the s	
Possible Hazard Identification	Andrew Control of the	Sample Disposal			(A fee may be assessed if samples are retained
Non-Hazard	ison B Unknown	Return To Client	☐ Disposal By Lab ☐ Archive For	Months	nth)
e Required 7 Days 14 Days	21 Days Other_	J	QC Requirements (Specify)	- Constitution of the cons	
d By	Date 3-7	Time	7. Received By (7.	Exangelhheas	Date
Reimoujaned By	'}	Time	2. Reserved By Sm		Date 10850 10850
8. Relinquished By	Date	Time	3. Received By		Date
O O O O O O O O O O O O O O O O O O O	- Annual management of the second of the sec	Carrier and Carrie	- CANADARAN AND AND AND AND AND AND AND AND AND A		

DISTRIBUTION: WHITE - Returned to Client with Report. CANARY - Stays with the Sample; PINK - Field Copy

Login Sample Receipt Check List

Client: Entact, LLC Job Number: 560-9081-1

Login Number: 9081 List Source: TestAmerica Corpus Christi

Creator: McDermott, Vivian

List Number: 1

Question	T / F/ NA	Comment
Radioactivity either was not measured or, if measured, is at or below background	N/A	
The cooler's custody seal, if present, is intact.	True	
The cooler or samples do not appear to have been compromised or tampered with.	True	
Samples were received on ice.	True	
Cooler Temperature is acceptable.	True	
Cooler Temperature is recorded.	True	3.3C IR 5
COC is present.	True	
COC is filled out in ink and legible.	True	
COC is filled out with all pertinent information.	True	
There are no discrepancies between the sample IDs on the containers and the COC.	True	
Samples are received within Holding Time.	False	HELD AT FED EX DUE TO WEATHER
Sample containers have legible labels.	True	
Containers are not broken or leaking.	True	
Sample collection date/times are provided.	True	
Appropriate sample containers are used.	True	
Sample bottles are completely filled.	True	
There is sufficient vol. for all requested analyses, incl. any requested MS/MSDs	True	
VOA sample vials do not have headspace or bubble is <6mm (1/4") in diameter.	N/A	
If necessary, staff have been informed of any short hold time or quick TAT needs	True	
Multiphasic samples are not present.	True	
Samples do not require splitting or compositing.	True	

(317)875-5894



March 14, 2008

Mr. Jason Cosgrove Arcadis U.S., Inc. 251 E. Ohio Street Suite 800 Indianapolis, IN 46204

RE: Project: Valhi, Crawfordsville, IN

Pace Project No.: 5012923

Dear Mr. Cosgrove:

Enclosed are the analytical results for sample(s) received by the laboratory on March 13, 2008. The results relate only to the samples included in this report. Results reported herein conform to the most current NELAC standards, where applicable, unless otherwise narrated in the body of the report.

If you have any questions concerning this report, please feel free to contact me.

Sincerely,

Donna S. Soyther

Donna Spyker

dspyker@pacelabs.com Project Manager

Illinois/NELAC Certification Number: 100418 Indiana Certification Number: C-49-06 Kansas Certification Number: E-10247 Kentucky Certification Number: 0042

Ohio VAP: CL0065 Pennsylvania: 68-00791

West Virginia Certification Number: 330

Enclosures






SAMPLE SUMMARY

Project: Valhi, Crawfordsville, IN

Pace Project No.: 5012923

Lab ID	Sample ID	Matrix	Date Collected	Date Received
5012923001	FD- AB23-Pre	Solid	03/13/08 10:43	03/13/08 14:04
5012923002	FD- AB23- Arc	Solid	03/13/08 10:43	03/13/08 14:04







SAMPLE ANALYTE COUNT

Project: Valhi, Crawfordsville, IN

Pace Project No.: 5012923

Lab ID	Sample ID	Method	Analysts	Analytes Reported
5012923001	FD- AB23-Pre	ASTM D2974-87	ILP	1
		EPA 8260	JLF	6
5012923002	FD- AB23- Arc	ASTM D2974-87	ILP	1
		EPA 8260	JLF	6





ANALYTICAL RESULTS

Project: Valhi, Crawfordsville, IN

Pace Project No.: 5012923

Sample: FD- AB23-Pre Lab ID: 5012923001 Collected: 03/13/08 10:43 Received: 03/13/08 14:04 Matrix: Solid

Results reported on a "dry-weight" basis

Results reported on a "dry-weig	nt" pasis							
Parameters	Results	Units	Report Limit	DF	Prepared	Analyzed	CAS No.	Qual
8260 MSV 5035A VOA	Analytical Me	thod: EPA 8260	0					
cis-1,2-Dichloroethene	6880 u	g/kg	2300	500		03/14/08 02:12	156-59-2	
Trichloroethene	48600 u	g/kg	2300	500		03/14/08 02:12	79-01-6	
Vinyl chloride	297 u	g/kg	230	50		03/14/08 14:18	75-01-4	
Dibromofluoromethane (S)	90 %	, D	80-124	50		03/14/08 14:18	1868-53-7	
Toluene-d8 (S)	99 %	, D	58-145	50		03/14/08 14:18	2037-26-5	
4-Bromofluorobenzene (S)	95 %	, D	61-131	50		03/14/08 14:18	460-00-4	
Percent Moisture	Analytical Me	thod: ASTM D2	2974-87					
Percent Moisture	10.0 %	ó	0.10	1		03/13/08 14:59		

Date: 03/14/2008 05:32 PM

REPORT OF LABORATORY ANALYSIS

Page 4 of 9





ANALYTICAL RESULTS

Project: Valhi, Crawfordsville, IN

Pace Project No.: 5012923

Sample: FD- AB23- Arc Lab ID: 5012923002 Collected: 03/13/08 10:43 Received: 03/13/08 14:04 Matrix: Solid

Results reported on a "dry-weight" basis

Results reported on a dry-weigh	it basis							
Parameters	Results	Units	Report Limit	DF	Prepared	Analyzed	CAS No.	Qual
8260 MSV 5030 Low Level	Analytical Met	thod: EPA 8260	0					
cis-1,2-Dichloroethene	7300 ug	g/kg	2760	500		03/14/08 02:46	156-59-2	
Trichloroethene	53500 ug	g/kg	2760	500		03/14/08 02:46	79-01-6	
Vinyl chloride	ND u	g/kg	276	50		03/14/08 14:36	75-01-4	
Dibromofluoromethane (S)	90 %)	80-124	50		03/14/08 14:36	1868-53-7	
Toluene-d8 (S)	100 %	•	58-145	50		03/14/08 14:36	2037-26-5	
4-Bromofluorobenzene (S)	98 %)	61-131	50		03/14/08 14:36	460-00-4	
Percent Moisture	Analytical Met	thod: ASTM D2	2974-87					
Percent Moisture	9.3 %		0.10	1		03/13/08 14:59		

Date: 03/14/2008 05:32 PM

REPORT OF LABORATORY ANALYSIS

Page 5 of 9









Project: Valhi, Crawfordsville, IN

Pace Project No.: 5012923

QC Batch: PMST/2334 Analysis Method: ASTM D2974-87

QC Batch Method: ASTM D2974-87 Analysis Description: Dry Weight/Percent Moisture

Associated Lab Samples: 5012923001, 5012923002

SAMPLE DUPLICATE: 142180

•		5012923001	Dup		Max	
Parameter	Units	Result	Result	RPD	RPD	Qualifiers
Percent Moisture		10.0	10.0		5	

Date: 03/14/2008 05:32 PM





Project: Valhi, Crawfordsville, IN

Pace Project No.: 5012923

QC Batch: MSV/7982 Analysis Method: EPA 8260

QC Batch Method: EPA 8260 Analysis Description: 8260 MSV 5035A Volatile Organics

Associated Lab Samples: 5012923001

METHOD BLANK: 142786

Associated Lab Samples: 5012923001

		Blank	Reporting	
Parameter	Units	Result	Limit	Qualifiers
cis-1,2-Dichloroethene	ug/kg	ND	5.0	
Trichloroethene	ug/kg	ND	5.0	
Vinyl chloride	ug/kg	ND	5.0	
4-Bromofluorobenzene (S)	%	95	61-131	
Dibromofluoromethane (S)	%	92	80-124	
Toluene-d8 (S)	%	101	58-145	

LABORATORY CONTROL SAMPLE: 142787

Parameter	Units	Spike Conc.	LCS Result	LCS % Rec	% Rec Limits	Qualifiers
cis-1,2-Dichloroethene	ug/kg	50	49.6	99	76-119	
Trichloroethene	ug/kg	50	46.9	94	74-121	
Vinyl chloride	ug/kg	50	46.9	94	50-146	
4-Bromofluorobenzene (S)	%			93	61-131	
Dibromofluoromethane (S)	%			90	80-124	
Toluene-d8 (S)	%			102	58-145	

Date: 03/14/2008 05:32 PM





Project: Valhi, Crawfordsville, IN

Pace Project No.: 5012923

QC Batch: MSV/7983 Analysis Method: EPA 8260

QC Batch Method: EPA 8260 Analysis Description: 8260 MSV 5030 Low

Associated Lab Samples: 5012923002

METHOD BLANK: 142788

Associated Lab Samples: 5012923002

Parameter	Units	Blank Result	Reporting Limit	Qualifiers
cis-1,2-Dichloroethene	ug/kg	ND	5.0	
Trichloroethene	ug/kg	ND	5.0	
Vinyl chloride	ug/kg	ND	5.0	
4-Bromofluorobenzene (S)	%	93	61-131	
Dibromofluoromethane (S)	%	93	80-124	
Toluene-d8 (S)	%	99	58-145	

LABORATORY CONTROL SAMPLE: 142789

Parameter	Units	Spike Conc.	LCS Result	LCS % Rec	% Rec Limits	Qualifiers
cis-1,2-Dichloroethene	ug/kg	50	58.4	117	76-119	
Trichloroethene	ug/kg	50	51.4	103	74-121	
Vinyl chloride	ug/kg	50	44.7	89	50-146	
4-Bromofluorobenzene (S)	%			96	61-131	
Dibromofluoromethane (S)	%			91	80-124	
Toluene-d8 (S)	%			101	58-145	

Date: 03/14/2008 05:32 PM





QUALIFIERS

Project: Valhi, Crawfordsville, IN

Pace Project No.: 5012923

DEFINITIONS

DF - Dilution Factor, if reported, represents the factor applied to the reported data due to changes in sample preparation, dilution of the sample aliquot, or moisture content.

ND - Not Detected at or above adjusted reporting limit.

J - Estimated concentration above the adjusted method detection limit and below the adjusted reporting limit.

MDL - Adjusted Method Detection Limit.

S - Surrogate

1,2-Diphenylhydrazine (8270 listed analyte) decomposes to Azobenzene.

Consistent with EPA guidelines, unrounded data are displayed and have been used to calculate % recovery and RPD values.

LCS(D) - Laboratory Control Sample (Duplicate)

MS(D) - Matrix Spike (Duplicate)

DUP - Sample Duplicate

RPD - Relative Percent Difference

NC - Not Calculable.

Pace Analytical is NELAP accredited. Contact your Pace PM for the current list of accredited analytes.

Date: 03/14/2008 05:32 PM REPORT OF LABORATORY ANALYSIS

Page 9 of 9



Custody Record Chain of

TestAmerica

THE LEADER IN ENVIRONMENTAL TESTING

3 encore & 1 402. Jar 601 902 1/2/1/V Special Instructions/ Conditions of Receipt 7,000 KD 5012923 (A fee may be assessed if samples are retained Months longer than 1 month) Time 2-4 02. Jal Chain of Custody Number 364151 Date 3-13-08 Page_ Date Date Analysis (Attach list if more space is needed) 3.13-08 Lab Number Date 334-6/ 5() <u> ICE</u> Telephone Number (Area Code)/Fax Number OC Requirements (Specify) \oAn∑ HO£V Containers & Preservatives HOPN 1. Received By
2. Received By Lap Contact
Douna Spyle 3. Received By ЮH CONF POSZH səudur 120.00 l ☐ Unknown ☐ Return To Client Comments — 24 hour TUTW CLOUNCH DISTRIBUTION: WHITE - Returned to Client with Report; CANARY - Stays with the Sample; PINK - Field Copy Sample Disposal goil Time Carner/Waybill Number pəş Project Manager snoanbb Site Contact ήP Other, 10:43 10.43 Time Date 21 Days 3.0.8 8.5.8 ☐ Poison B Date State | Zip Code Contract/Purchase Order/Quote No. 14 Days Sample I.D. No. and Description (Containers for each sample may be combined on one line) Skin trritant 🗌 7 Days ☐ Flammable Project Name and Location (State) FD - ABOJS - Arc 1. Relinquisperse FD-ARJS-Re Possible Hazard Identification Turn Around Time Required Accadis 2. Relinquished But 3. Relinquished By □ Non-Hazard TAL-4142 (0907) Address Š

GOKENT CHENT LL

San	nple Condition	n Upon Receipt	
Pace Analytical Client Name:	ANGAI	lis 1	Project # 5012923
Chefft Name.	-(X/IGA)	<u>(L/)</u> [-Toject # <u> </u>
Courier: Fed Ex UPS USPS Clien Tracking #:	t Commercial	Pace Other	
Custody Seal on Cooler/Box Present: yes	no Seals	intact: 🗆 yes 💢	no Pri Gilliano
Packing Material: Bubble-W(rap , Bubble	Bags None	Other	·
Thermometer Used 1234	Type of Ice: (Wet	Blue None	Samples on ice, cooling process has begun
Cooler Temperature Temp should be above freezing to 6°C	Biological Tissue	is Frozen: Yes No	Date and Initials of person examining contents:
Chain of Custody Present:	EYes DNo DN/A	 	
Chain of Custody Filled Out:	MYes □No □N/A	2.	
Chain of Custody Relinquished:	Dres □No □N/A	3.	
Sampler Name & Signature on COC:	QYes □No □N/A	4.	
Samples Arrived within Hold Time:	MYeş □No □N/A	5.	
Short Hold Time Analysis (<72hr):	Xes □No □N/A	6. Incore	5
Rush Turn Around Time Requested: 24 10 12	Yes □No □N/A	7.	
Sufficient Volume:	Dices Ono On/A	8.	
Correct Containers Used:	Dixes Ono On/A	9.	
-Pace Containers Used:	YOYes ONO. ON/A		
Containers Intact:	XYes □No □N/A	10.	
Filtered volume received for Dissolved tests	□Yes □No □N/A	11.	
Sample Labels match COC:	DYES DNO DN/A	12.	
-Includes date/time/ID/Analysis Matrix:	<u> </u>		
All containers needing preservation have been checked.	□Yes □No □N/A	13.	
All containers needing preservation are found to be in compliance with EPA recommendation.	□Yes □No □N/A		
exceptions: VOA, coliform, TOC, O&G, WI-DRO (water)	□Yes □No	Initial when completed	Lot # of added preservative
Samples checked for dechlorination:	□Yes □No \ □Ñ/A	14.	
Headspace in VOA Vials (>6mm):	□Yes □No \□N/A	15.	
Trip Blank Present:	□Yes □No □MA	16.	
Trip Blank Custody Seals Present	□Yes □No □NA		
Pace Trip Blank Lot # (if purchased):			
Client Notification/ Resolution:			Field Data Required? Y / N
Person Contacted:	Date/	Гіme:	
Comments/ Resolution:			
	<u></u>		
			
			
		<u> </u>	
			- · · · · · ·
Project Manager Review: \(\langle \infty \langle \lang	NIS		Date: 3-13-68

Note: Whenever there is a discrepancy affecting North Carolina compliance samples, a copy of this form will be sent to the North Carolina DEHNR Certification Office (i.e. out of hold, incorrect preservative, out of temp, incorrect containers)



March 20, 2008

Mr. Jason Cosgrove Arcadis U.S., Inc. 251 E. Ohio Street Suite 800 Indianapolis, IN 46204

RE: Project: Valhi

Pace Project No.: 5012998

Dear Mr. Cosgrove:

Enclosed are the analytical results for sample(s) received by the laboratory on March 14, 2008. The results relate only to the samples included in this report. Results reported herein conform to the most current NELAC standards, where applicable, unless otherwise narrated in the body of the report.

If you have any questions concerning this report, please feel free to contact me.

Sincerely,

Donna S. Soyther

Donna Spyker

dspyker@pacelabs.com Project Manager

Illinois/NELAC Certification Number: 100418 Indiana Certification Number: C-49-06 Kansas Certification Number: E-10247 Kentucky Certification Number: 0042

Ohio VAP: CL0065 Pennsylvania: 68-00791

West Virginia Certification Number: 330

Enclosures











SAMPLE SUMMARY

Project: Valhi
Pace Project No.: 5012998

Lab ID	Sample ID	Matrix	Date Collected	Date Received
5012998001	FD-AB23-Post	Solid	03/14/08 08:00	03/14/08 12:46

Page 2 of 7






SAMPLE ANALYTE COUNT

Project: Valhi
Pace Project No.: 5012998

Lab ID	Sample ID	Method	Analysts	Analytes Reported
5012998001	FD-AB23-Post	ASTM D2974-87	ILP	1
		EPA 8260	JLF	6







ANALYTICAL RESULTS

Project: Valhi Pace Project No.: 5012998

Sample: FD-AB23-Post Lab ID: 5012998001 Collected: 03/14/08 08:00 Received: 03/14/08 12:46 Matrix: Solid

Results reported on a "dry-weig	nt" basis							
Parameters	Results	Units	Report Limit	DF	Prepared	Analyzed	CAS No.	Qual
8260 MSV 5035A VOA	Analytical Met	hod: EPA 826	0					
cis-1,2-Dichloroethene	629 ug	g/kg	257	50		03/20/08 00:33	156-59-2	
Trichloroethene	6340 ug	g/kg	257	50		03/20/08 00:33	79-01-6	
Vinyl chloride	ND ug	g/kg	5.1	1		03/19/08 23:58	75-01-4	
Dibromofluoromethane (S)	20 %)	80-124	1		03/19/08 23:58	1868-53-7	S5
Toluene-d8 (S)	102 %)	58-145	1		03/19/08 23:58	2037-26-5	
4-Bromofluorobenzene (S)	92 %)	61-131	1		03/19/08 23:58	460-00-4	
Percent Moisture	Analytical Met	hod: ASTM D2	2974-87					
Percent Moisture	15.1 %)	0.10	1		03/17/08 16:59		

Date: 03/20/2008 04:11 PM

REPORT OF LABORATORY ANALYSIS

Page 4 of 7









Project: Valhi
Pace Project No.: 5012998

QC Batch: PMST/2340 Analysis Method: ASTM D2974-87

QC Batch Method: ASTM D2974-87 Analysis Description: Dry Weight/Percent Moisture

Associated Lab Samples: 5012998001

SAMPLE DUPLICATE: 143665

5012998001 Dup Max Parameter Units Result Result RPD **RPD** Qualifiers 15.1 5 R2 Percent Moisture % 16.8 10

Date: 03/20/2008 04:11 PM





Project: Valhi
Pace Project No.: 5012998

QC Batch: MSV/8110 Analysis Method: EPA 8260

QC Batch Method: EPA 8260 Analysis Description: 8260 MSV 5035A Volatile Organics

Associated Lab Samples: 5012998001

METHOD BLANK: 145027

Associated Lab Samples: 5012998001

		Blank	Reporting	
Parameter	Units	Result	Limit	Qualifiers
cis-1,2-Dichloroethene	ug/kg	ND ND	5.0	
Trichloroethene	ug/kg	ND	5.0	
Vinyl chloride	ug/kg	ND	5.0	
4-Bromofluorobenzene (S)	%	97	61-131	
Dibromofluoromethane (S)	%	100	80-124	
Toluene-d8 (S)	%	100	58-145	

LABORATORY CONTROL SAMPLE: 145028

Parameter	Units	Spike Conc.	LCS Result	LCS % Rec	% Rec Limits	Qualifiers
cis-1,2-Dichloroethene	ug/kg	50	61.9	124	71-126	
Trichloroethene	ug/kg	50	59.2	118	74-121	
Vinyl chloride	ug/kg	50	43.3	87	50-146	
4-Bromofluorobenzene (S)	%			98	61-131	
Dibromofluoromethane (S)	%			99	80-124	
Toluene-d8 (S)	%			101	58-145	

Date: 03/20/2008 04:11 PM





QUALIFIERS

Project: Valhi
Pace Project No.: 5012998

DEFINITIONS

DF - Dilution Factor, if reported, represents the factor applied to the reported data due to changes in sample preparation, dilution of the sample aliquot, or moisture content.

ND - Not Detected at or above adjusted reporting limit.

J - Estimated concentration above the adjusted method detection limit and below the adjusted reporting limit.

MDL - Adjusted Method Detection Limit.

S - Surrogate

1,2-Diphenylhydrazine (8270 listed analyte) decomposes to Azobenzene.

Consistent with EPA guidelines, unrounded data are displayed and have been used to calculate % recovery and RPD values.

LCS(D) - Laboratory Control Sample (Duplicate)

MS(D) - Matrix Spike (Duplicate)

DUP - Sample Duplicate

RPD - Relative Percent Difference

NC - Not Calculable.

Pace Analytical is NELAP accredited. Contact your Pace PM for the current list of accredited analytes.

ANALYTE QUALIFIERS

R2 RPD value was outside control limits due to matrix interference

S5 Surrogate recovery outside control limits due to matrix interferences (not confirmed by re-analysis).

Date: 03/20/2008 04:11 PM



Chain of Custody Record

THE LEADER IN ENVIRONMENTAL TESTING

TAL-4142 (0907)		0			2							
Arcadis		Project	Project Manager Donna	ర	į			<u>u</u>	Date 5-14-08		Chain of Custody Number 364153	
ess		. Telepho	3	Code)/Fax	Vumber			7	Lab Number		Page / of	
City State Zip (Zip Code	Site Contact	ite Contact	Lab C	Lab Contact				Analysis (Attach list if more space is needed)	if (b)	(2
Project Name and Location (State)		CarrierA	Carrier/Waybill Number				33°	<u>36:40</u>			3)
Contract/Purchase Order/Quote No.			Matrix		Containers & Preservatives	ers & tives	1-6,1	CP			Special Instructions/ Conditions of Receipt	ictions/ Receipt
Sample I.D. No. and Description (Containers for each sample may be combined on one line)	Date	Тіте	Air Aqueous Sed.	.serqnU	нсі ниоз нъго¢	HO _B OH HO _B O	21.0 21.0	lo;Λ,				
FD- AB23- Post	3-14-08		8				Y & X	2			Sencore/4	4 02. jar
												100
												į
											- 24	
							-					
											コをロ	10 D
											Temp	15, 18
										-	Fncoke	Received
Possible Hazard Identification Non-Hazard Flammable Skin trritant [☐ Poison B	Unknown	Sample Disposal Return To Client		Disposal By Lab		Archive For	ļ	(A fei Months longe	e may be as ir than 1 mo	(A fee may be assessed if samples are retained longer than 1 month)	p _i
Required 48 Hours	21 Da	Otther	1 🖫		C Requirem	I.Q.	0		1			
M			30	Time 11.30am	1. Received By	34 /W	1.	_ \			Date Time 11:	11:300
2. Relinquished By		Date	Тіте	6	Peceived By	61180	12/2	LI SOM.	DAS LOGO	0	7	3.76
3. Relinquished By		Date	Time	6	3. Received By						1	
Comments												

DISTRIBUTION: WHITE - Returned to Client with Report; CANARY - Stays with the Sample; PINK - Field Copy

Sample Condition Upon Receipt ace Analytical" Client Name: Project # 3012998 Courier: ☐ Fed Ex ☐ UPS ☐ USPS ☐ Client ☐ Commercial ☐ Pace Other Tracking #: Custody Seal on Cooler/Box Present: yes ∠ ne Seals intact: ves ☐Bubble Bags Packing Material: Bubble Wrap ☐ None ☐ Other Samples on ice, cooling process has begun Thermometer Used Type of Ice: Wet Blue None Date and Initials of person examining, 00 Biological Tissue is Frozen: Yes Cooler Temperature Temp should be above freezing to 6°C Comments: ŽÍYes □No □N/A Chain of Custody Present: ☐Yes □No □n/A 2. Chain of Custody Filled Out: Z Yes DNo DN/A 3. Chain of Custody Relinquished: ☑Yes □No Sampler Name & Signature on COC: FIN/A ☑Yes □No □N/A Samples Arrived within Hold Time: ☐Yes ØNO ☐N/A Short Hold Time Analysis (<72hr): Rush Turn Around Time Requested: ☐Yes ☐No □n/a ☐Yes □No □N/A 8. Sufficient Volume: ☐Yes ☐No □N/A 9. Correct Containers Used: -EYes □No □N/A -Pace Containers Used: ☑ Yes □ No □N/A 10. Containers Intact: □Yes □No Filtered volume received for Dissolved tests **Ð**N/A 11. □N/A 12. Sample Labels match COC: -Includes date/time/ID/Analysis Matrix: All containers needing preservation have been checked. ☐Yes ☐No ☐N#A All containers needing preservation are found to be in ☐Yes ☐No ☐Ñ/A compliance with EPA recommendation. Lot # of added Initial when ☐Yes ☑No preservative exceptions: VOA, coliform, TOC, O&G, WI-DRO (water) completed 14. ☐Yes ☐No **₽**MA Samples checked for dechlorination: Headspace in VOA Vials (>6mm): ☐Yee ☐No **⊠**N/A 15, ☐Yes ☐No **☑**N/A Trip Blank Present: ☐Yes ☐No **DN/A** Trip Blank Custody Seals Present Pace Trip Blank Lot # (if purchased):

Client Notification/ Resolution:			Field Data Require	ed? Y / N
Person Contacted:		Date/Time:		1
Comments/ Resolution:	ient was aw	pare of	temp l'ust	Sampled
an hour	Gan			
	<u></u>			
			<u> </u>	
	<u> </u>			
Project Manager Review:	Myhn		Date:	3/14/09)

Note: Whenever there is a discrepancy affecting North Carolina compliance samples, a copy of this form will be sent to the North Carolina DEHNR Certification Office (i.e. out of hold, incorrect preservative, out of temp, incorrect containers)

(317)875-5894



March 31, 2008

Mr. Jason Cosgrove Arcadis U.S., Inc. 251 E. Ohio Street Suite 800 Indianapolis, IN 46204

RE: Project: Valhi

Pace Project No.: 5013472

Dear Mr. Cosgrove:

Enclosed are the analytical results for sample(s) received by the laboratory on March 28, 2008. The results relate only to the samples included in this report. Results reported herein conform to the most current NELAC standards, where applicable, unless otherwise narrated in the body of the report.

If you have any questions concerning this report, please feel free to contact me.

Sincerely,

Donna S. Soyther

Donna Spyker

dspyker@pacelabs.com Project Manager

Illinois/NELAC Certification Number: 100418 Indiana Certification Number: C-49-06 Kansas Certification Number: E-10247 Kentucky Certification Number: 0042


Ohio VAP: CL0065 Pennsylvania: 68-00791

West Virginia Certification Number: 330

Enclosures









US EPA ARCHIVE DOCUMENT

SAMPLE SUMMARY

Project: Valhi Pace Project No.: 5013472

Pace Analytical

www.pacelabs.com

Lab ID	Sample ID	Matrix	Date Collected	Date Received
5013472001	AB-23-Post-2	Solid	03/28/08 10:00	03/28/08 13:00






SAMPLE ANALYTE COUNT

Project: Valhi
Pace Project No.: 5013472

Lab ID	Sample ID	Method	Analysts	Analytes Reported
5013472001	AB-23-Post-2	ASTM D2974-87	ILP	1
		EPA 8260	JLF	6







Project: Valhi
Pace Project No.: 5013472

Sample: AB-23-Post-2 Lab ID: 5013472001 Collected: 03/28/08 10:00 Received: 03/28/08 13:00 Matrix: Solid

Results reported on a "dry-weight" basis

Results reported on a "dry-weig	nt" basis							
Parameters	Results	Units	Report Limit	DF	Prepared	Analyzed	CAS No.	Qual
8260 MSV 5035A VOA	Analytical Met	hod: EPA 826	0					
cis-1,2-Dichloroethene	ND ug	g/kg	6.3	1		03/28/08 14:34	156-59-2	
Trichloroethene	70.0 ug	g/kg	6.3	1		03/28/08 14:34	79-01-6	
Vinyl chloride	ND ug	g/kg	6.3	1		03/28/08 14:34	75-01-4	
Dibromofluoromethane (S)	18 %	•	80-124	1		03/28/08 14:34	1868-53-7	S2
Toluene-d8 (S)	107 %	1	58-145	1		03/28/08 14:34	2037-26-5	
4-Bromofluorobenzene (S)	78 %	•	61-131	1		03/28/08 14:34	460-00-4	
Percent Moisture	Analytical Met	hod: ASTM D	2974-87					
Percent Moisture	9.0 %)	0.10	1		03/28/08 14:38		

Date: 03/31/2008 12:49 PM

REPORT OF LABORATORY ANALYSIS

Page 4 of 7





Project: Valhi
Pace Project No.: 5013472

QC Batch: MSV/8238 Analysis Method: EPA 8260

QC Batch Method: EPA 8260 Analysis Description: 8260 MSV 5035A Volatile Organics

Associated Lab Samples: 5013472001

METHOD BLANK: 148205

Associated Lab Samples: 5013472001

		Blank	Reporting	
Parameter	Units	Result	Limit	Qualifiers
cis-1,2-Dichloroethene	ug/kg	ND ND	5.0	
Trichloroethene	ug/kg	ND	5.0	
Vinyl chloride	ug/kg	ND	5.0	
4-Bromofluorobenzene (S)	%	84	61-131	
Dibromofluoromethane (S)	%	96	80-124	
Toluene-d8 (S)	%	101	58-145	

LABORATORY CONTROL SAMPLE: 148206

Parameter	Units	Spike Conc.	LCS Result	LCS % Rec	% Rec Limits	Qualifiers
cis-1,2-Dichloroethene	ug/kg	50	55.6	111	76-119	
Trichloroethene	ug/kg	50	56.2	112	74-121	
Vinyl chloride	ug/kg	50	53.0	106	50-146	
4-Bromofluorobenzene (S)	%			88	61-131	
Dibromofluoromethane (S)	%			102	80-124	
Toluene-d8 (S)	%			106	58-145	

Date: 03/31/2008 12:49 PM









Project: Valhi
Pace Project No.: 5013472

QC Batch: PMST/2377 Analysis Method: ASTM D2974-87

QC Batch Method: ASTM D2974-87 Analysis Description: Dry Weight/Percent Moisture

Associated Lab Samples: 5013472001

SAMPLE DUPLICATE: 148211

5013472001 Dup Max Parameter Units Result Result **RPD RPD** Qualifiers 9.0 2 Percent Moisture % 8.8 5

Date: 03/31/2008 12:49 PM





QUALIFIERS

Project: Valhi
Pace Project No.: 5013472

DEFINITIONS

DF - Dilution Factor, if reported, represents the factor applied to the reported data due to changes in sample preparation, dilution of the sample aliquot, or moisture content.

ND - Not Detected at or above adjusted reporting limit.

J - Estimated concentration above the adjusted method detection limit and below the adjusted reporting limit.

MDL - Adjusted Method Detection Limit.

S - Surrogate

1,2-Diphenylhydrazine (8270 listed analyte) decomposes to Azobenzene.

Consistent with EPA guidelines, unrounded data are displayed and have been used to calculate % recovery and RPD values.

LCS(D) - Laboratory Control Sample (Duplicate)

MS(D) - Matrix Spike (Duplicate)

DUP - Sample Duplicate

RPD - Relative Percent Difference

NC - Not Calculable.

Pace Analytical is NELAP accredited. Contact your Pace PM for the current list of accredited analytes.

ANALYTE QUALIFIERS

Date: 03/31/2008 12:49 PM

Surrogate recovery outside laboratory control limits due to matrix interferences (confirmed by similar results from sample re-analysis).

REPORT OF LABORATORY ANALYSIS

nelac

Custody Record Chain of



THE LEADER IN ENVIRONMENTAL TESTING

Finerical S28-08 11:43 am 3 encore 14 02 jar Special Instructions/ Conditions of Receipt EN SAFI (A fee may be assessed if samples are retained Months longer than 1 month) Chain of Custody Number 364155 3-2808 Page. Analysis (Attach list if more space is needed) Lab Number Date 71177 CP11821 1970-61 メダ ☐ Archive For *3*2<u>1</u> OC Requirements (Specify) Lab Contact
Ponna Spyker \ɔAn∑ HO₅N Disposal By Lab Containers & Preservatives HOPN 1. Received By ЮН Telephone Number (Area Code)/Fax Number CONH DOSTH səudur) 17 Days 14 Days 21 Days Stother Same day Rush Unknown | Return To Client 11: ua Sample Disposal *gos* Matrix Carrier/Waybill Number pes Project Manager laron Milory Services TX 3-28-08 Site Contact ijΨ Time 3-28-08 16:00 Skin trritant Doison B Date Zip Code Sample I.D. No. and Description (Containers for each sample may be combined on one line) State | Flammable AB-23-Poxy-4-2 Contract/Purchase Order/Quote No. Project Name and Location (State) 48 Hours Possible Hazard Identification Tum Around Time Required TAL-4142 (0907)
Client
ArCadiS Non-Hazard Relinguished By 24 Hours 3. Rei和 ŝ

DISTRIBUTION: WHITE - Returned to Client with Report; CANARY - Stays with the Sample; PINK - Field Copy

Sample Condition Upon Receipt Client Name: //////// Project # 601347-2 Courier: ☐ Fed Ex ☐ UPS ☐ USPS ☐ Client ☐ Commercial ☐ Pace Other Tracking #: Custody Seal on Cooler/Box Present: yes ☐ yes Seals intact: Bubble Bags None | Other Packing Material: Bubble-Wrap Thermometer Used Type of Ice: (Wet) Blue None Samples on ice, cooling process has begun Date and initials of person standing Biological Tissue is Frozen: Yes No **Cooler Temperature** contents/ Temp should be above freezing to 6°C Comments: Chain of Custody Present: Íyes □No □n/a Chain of Custody Filled Out: Yes □No □n/A ÄL⊻es □No Chain of Custody Relinquished: □N/A Sampler Name & Signature on COC: ⊠Yes □No □N/A Samples Arrived within Hold Time: XiYes □No □N/A □Yes \ZINo Short Hold Time Analysis (<72hr): □N/A 6. □Yes □No Rush Turn Around Time Requested: □n/a Sufficient Volume: QYeş ∐No □N/A 18. Correct Containers Used: ŲÝes □No □N/A 9, -Pace Containers Used: JYes □No □N/A KDYes □No Containers Intact: □N/A 10. Filtered volume received for Dissolved tests Ďyes □no □n/A 11. Sample Labels match COC: DYes □No □N/A 12. -includes date/time/ID/Analysis All containers needing preservation have been checked. ☐Yes ☐No DAMY 13. All containers needing preservation are found to be in □Yes □No compliance with EPA recommendation. linitial when Lot # of added ☐Yes ☐No exceptions: VOA, coliform, TOC, O&G, WI-DRO (water) completed preservative Samples checked for dechlorination: ☐Yes ☐No ŪΝ/Α 14. Headspace in VOA Vials (>6mm): □Yes □No **√**DN/A 15. Trip Blank Present: ☐Yes ☐No* N/A 16. Trip Blank Custody Seals Present □Yes □No DN/A Pace Trip Blank Lot # (if purchased): Client Notification/ Resolution: Field Data Required? Person Contacted: Date/Time:

Project Manager Review: Date: 3/24/09)

Note: Whenever there is a discrepancy affecting Worth Carolina compliance samples, a copy of this form will be sent to the North Carolina DEHNR Certification Office (i.e. out of hold, incorrect preservative, out of temp, incorrect containers)

(317)875-5894



April 30, 2008

Mr. Jason Cosgrove Arcadis U.S., Inc. 251 E. Ohio Street Suite 800 Indianapolis, IN 46204

RE: Project: Valhi

Pace Project No.: 5014193

Dear Mr. Cosgrove:

Enclosed are the analytical results for sample(s) received by the laboratory on April 22, 2008. The results relate only to the samples included in this report. Results reported herein conform to the most current NELAC standards, where applicable, unless otherwise narrated in the body of the report.

If you have any questions concerning this report, please feel free to contact me.

Sincerely,

Kelly Jones for

Donna Spyker donna.spyker@pacelabs.com

Kelly M gmis

Project Manager

Illinois/NELAC Certification Number: 100418 Indiana Certification Number: C-49-06 Kansas Certification Number: E-10247 Kentucky Certification Number: 0042

Ohio VAP: CL0065 Pennsylvania: 68-00791

West Virginia Certification Number: 330

Enclosures







SAMPLE SUMMARY

Project: Valhi
Pace Project No.: 5014193

Lab ID	Sample ID	Matrix	Date Collected	Date Received
5014193001	Comp-8	Solid	04/18/08 14:30	04/22/08 14:16
5014193002	Comp-8 SPLP	Water	04/18/08 14:30	04/22/08 14:16





SAMPLE ANALYTE COUNT

Project: Valhi
Pace Project No.: 5014193

Lab ID	Sample ID	Method	Analysts	Analytes Reported
5014193001	Comp-8	EPA 9045	TPD	1
5014193002	Comp-8 SPLP	EPA 150.1	TPD	1
		FPA 8260	.II F	73





Project: Valhi
Pace Project No.: 5014193

Sample: Comp-8 Lab ID: 5014193001 Collected: 04/18/08 14:30 Received: 04/22/08 14:16 Matrix: Solid

Results reported on a "dry-weight" basis

Parameters Results Units Report Limit DF Prepared Analyzed CAS No. Qual

9045 pH Soil Analytical Method: EPA 9045

pH at 25 Degrees C 7.9 Std. Units 1 04/28/08 09:06

Date: 04/30/2008 04:17 PM

REPORT OF LABORATORY ANALYSIS

Page 4 of 14







Project: Valhi
Pace Project No.: 5014193

Sample: Comp-8 SPLP	Lab ID: 5014193002	Collected: 04/18/08	3 14:30	Received:	04/22/08 14:16	Matrix: Water	
Parameters	Results Unit	Report Limit	DF	Prepared	Analyzed	CAS No.	Qua
3260 MSV	Analytical Method: EPA	8260					
Acetone	ND ug/L	100	1		04/25/08 15:2	0 67-64-1	
Acrolein	ND ug/L	100	1		04/25/08 15:2	0 107-02-8	
Acrylonitrile	ND ug/L	100	1		04/25/08 15:2	0 107-13-1	
Benzene	ND ug/L	5.0	1		04/25/08 15:2	0 71-43-2	
Bromobenzene	ND ug/L	5.0	1		04/25/08 15:2	0 108-86-1	
Bromochloromethane	ND ug/L	5.0	1		04/25/08 15:2	0 74-97-5	
Bromodichloromethane	ND ug/L	5.0	1		04/25/08 15:2	0 75-27-4	
Bromoform	ND ug/L	5.0	1		04/25/08 15:2	0 75-25-2	
Bromomethane	ND ug/L	5.0	1		04/25/08 15:2	0 74-83-9	
2-Butanone (MEK)	ND ug/L	25.0	1		04/25/08 15:2	0 78-93-3	
n-Butylbenzene	ND ug/L	5.0	1		04/25/08 15:2	0 104-51-8	
sec-Butylbenzene	ND ug/L	5.0	1		04/25/08 15:2		
ert-Butylbenzene	ND ug/L	5.0	1		04/25/08 15:2		
Carbon disulfide	ND ug/L	10.0	1		04/25/08 15:2		
Carbon tetrachloride	ND ug/L	5.0	1		04/25/08 15:2		
Chlorobenzene	ND ug/L	5.0	1		04/25/08 15:2		
Chloroethane	ND ug/L	5.0	1		04/25/08 15:2		
Chloroform	ND ug/L	5.0	1		04/25/08 15:2		
Chloromethane		5.0	1		04/25/08 15:2		
	ND ug/L				04/25/08 15:2		
2-Chlorotoluene	ND ug/L	5.0	1				
4-Chlorotoluene	ND ug/L	5.0	1		04/25/08 15:2		
Dibromochloromethane	ND ug/L	5.0	1		04/25/08 15:2		
1,2-Dibromoethane (EDB)	ND ug/L	5.0	1		04/25/08 15:2		
Dibromomethane	ND ug/L	5.0	1		04/25/08 15:2		
1,2-Dichlorobenzene	ND ug/L	5.0	1		04/25/08 15:2		
1,3-Dichlorobenzene	ND ug/L	5.0	1		04/25/08 15:2		
1,4-Dichlorobenzene	ND ug/L	5.0	1		04/25/08 15:2		
rans-1,4-Dichloro-2-butene	ND ug/L	100	1		04/25/08 15:2		
Dichlorodifluoromethane	ND ug/L	5.0	1		04/25/08 15:2		
1,1-Dichloroethane	ND ug/L	5.0	1		04/25/08 15:2	0 75-34-3	
1,2-Dichloroethane	ND ug/L	5.0	1		04/25/08 15:2	0 107-06-2	
1,1-Dichloroethene	ND ug/L	5.0	1		04/25/08 15:2	0 75-35-4	
cis-1,2-Dichloroethene	ND ug/L	5.0	1		04/25/08 15:2	0 156-59-2	
rans-1,2-Dichloroethene	ND ug/L	5.0	1		04/25/08 15:2	0 156-60-5	
1,2-Dichloropropane	ND ug/L	5.0	1		04/25/08 15:2	0 78-87-5	
1,3-Dichloropropane	ND ug/L	5.0	1		04/25/08 15:2	0 142-28-9	
2,2-Dichloropropane	ND ug/L	5.0	1		04/25/08 15:2	0 594-20-7	
1,1-Dichloropropene	ND ug/L	5.0	1		04/25/08 15:2	0 563-58-6	
cis-1,3-Dichloropropene	ND ug/L	5.0	1			0 10061-01-5	
rans-1,3-Dichloropropene	ND ug/L	5.0	1			0 10061-02-6	
Ethylbenzene	ND ug/L	5.0	1		04/25/08 15:2		
Ethyl methacrylate	ND ug/L	100	1		04/25/08 15:2		
Hexachloro-1,3-butadiene	ND ug/L	5.0	1		04/25/08 15:2		
n-Hexane	ND ug/L	5.0	1		04/25/08 15:2		
2-Hexanone	ND ug/L	25.0	1		04/25/08 15:2		
odomethane	ND ug/L ND ug/L	10.0	1		04/25/08 15:2		
ouomemane	ND ug/L	10.0	ı		04/25/06 15:2	U 14-00-4	

Date: 04/30/2008 04:17 PM

REPORT OF LABORATORY ANALYSIS

Page 5 of 14







Project: Valhi
Pace Project No.: 5014193

Sample: Comp-8 SPLP	Lab ID: 5014193002	Collected: 04/18/0	8 14:30	Received: 04/22/08 14:16 Matrix: Water	
Parameters	Results Units	Report Limit	DF	Prepared Analyzed CAS No.	Qual
8260 MSV	Analytical Method: EPA 826	0			
p-Isopropyltoluene	ND ug/L	5.0	1	04/25/08 15:20 99-87-6	
Methylene chloride	ND ug/L	5.0	1	04/25/08 15:20 75-09-2	
4-Methyl-2-pentanone (MIBK)	ND ug/L	25.0	1	04/25/08 15:20 108-10-1	
Methyl-tert-butyl ether	ND ug/L	4.0	1	04/25/08 15:20 1634-04-4	
Naphthalene	ND ug/L	5.0	1	04/25/08 15:20 91-20-3	
n-Propylbenzene	ND ug/L	5.0	1	04/25/08 15:20 103-65-1	
Styrene	ND ug/L	5.0	1	04/25/08 15:20 100-42-5	
1,1,1,2-Tetrachloroethane	ND ug/L	5.0	1	04/25/08 15:20 630-20-6	
1,1,2,2-Tetrachloroethane	ND ug/L	5.0	1	04/25/08 15:20 79-34-5	
Tetrachloroethene	ND ug/L	5.0	1	04/25/08 15:20 127-18-4	
Toluene	ND ug/L	5.0	1	04/25/08 15:20 108-88-3	
1,2,3-Trichlorobenzene	ND ug/L	5.0	1	04/25/08 15:20 87-61-6	
1,2,4-Trichlorobenzene	ND ug/L	5.0	1	04/25/08 15:20 120-82-1	
1,1,1-Trichloroethane	ND ug/L	5.0	1	04/25/08 15:20 71-55-6	
1,1,2-Trichloroethane	ND ug/L	5.0	1	04/25/08 15:20 79-00-5	
Trichloroethene	22.8 ug/L	5.0	1	04/25/08 15:20 79-01-6	
Trichlorofluoromethane	ND ug/L	5.0	1	04/25/08 15:20 75-69-4	
1,2,3-Trichloropropane	ND ug/L	5.0	1	04/25/08 15:20 96-18-4	
1,2,4-Trimethylbenzene	ND ug/L	5.0	1	04/25/08 15:20 95-63-6	
1,3,5-Trimethylbenzene	ND ug/L	5.0	1	04/25/08 15:20 108-67-8	
Vinyl acetate	ND ug/L	10.0	1	04/25/08 15:20 108-05-4	
Vinyl chloride	ND ug/L	2.0	1	04/25/08 15:20 75-01-4	
Xylene (Total)	ND ug/L	10.0	1	04/25/08 15:20 1330-20-7	
Dibromofluoromethane (S)	32 %	80-123	1	04/25/08 15:20 1868-53-7 S2	2
4-Bromofluorobenzene (S)	101 %	70-126	1	04/25/08 15:20 460-00-4	
Toluene-d8 (S)	101 %	80-116	1	04/25/08 15:20 2037-26-5	
150.1 pH	Analytical Method: EPA 150	.1			
рН	7.6 Std. Units		1	04/25/08 10:12	

Date: 04/30/2008 04:17 PM

REPORT OF LABORATORY ANALYSIS

Page 6 of 14









Project: Valhi Pace Project No.: 5014193

QC Batch: WET/3017 Analysis Method: EPA 150.1
QC Batch Method: EPA 150.1 Analysis Description: 150.1 pH

Associated Lab Samples: 5014193002

SAMPLE DUPLICATE: 157226

_		5014283001	Dup		Max	
Paramete	r Units	Result	Result	RPD	RPD	Qualifiers
pН	Std. Units	6.9	6.8	0	20	

Date: 04/30/2008 04:17 PM

REPORT OF LABORATORY ANALYSIS

Page 7 of 14





Qualifiers





QUALITY CONTROL DATA

EPA 9045

9045 pH

Analysis Method:

Analysis Description:

Project: Valhi Pace Project No.: 5014193

QC Batch: WET/3019 QC Batch Method: EPA 9045

Associated Lab Samples: 5014193001

SAMPLE DUPLICATE: 157284

5014224001 Dup Max Parameter Units Result Result **RPD** RPD

7.8 7.7 pH at 25 Degrees C Std. Units

SAMPLE DUPLICATE: 157285

5014224015 Dup Max RPD RPD Parameter Units Result Result Qualifiers

pH at 25 Degrees C Std. Units 7.6 7.5 1

Date: 04/30/2008 04:17 PM







Project: Valhi
Pace Project No.: 5014193

QC Batch: MSV/8748 Analysis Method: EPA 8260
QC Batch Method: EPA 8260 Analysis Description: 8260 MSV

Associated Lab Samples: 5014193002

METHOD BLANK: 158031

Associated Lab Samples: 5014193002

Parameter	Units	Blank Result	Reporting Limit	Qualifiers
1,1,1,2-Tetrachloroethane	ug/L	ND	5.0	
1,1,1-Trichloroethane	ug/L	ND ND	5.0	
1,1,2,2-Tetrachloroethane	ug/L	ND	5.0	
1,1,2-Trichloroethane	ug/L	ND	5.0	
1,1-Dichloroethane	ug/L	ND	5.0	
1,1-Dichloroethene	ug/L	ND	5.0	
1,1-Dichloropropene	ug/L	ND	5.0	
1,2,3-Trichlorobenzene	ug/L	ND	5.0	
1,2,3-Trichloropropane	ug/L	ND	5.0	
1,2,4-Trichlorobenzene	ug/L	ND	5.0	
1,2,4-Trimethylbenzene	ug/L	ND	5.0	
1,2-Dibromoethane (EDB)	ug/L	ND	5.0	
1,2-Dichlorobenzene	ug/L	ND	5.0	
1,2-Dichloroethane	ug/L	ND	5.0	
1,2-Dichloropropane	ug/L	ND	5.0	
1,3,5-Trimethylbenzene	ug/L	ND	5.0	
1,3-Dichlorobenzene	ug/L	ND	5.0	
1,3-Dichloropropane	ug/L	ND	5.0	
1,4-Dichlorobenzene	ug/L	ND	5.0	
2,2-Dichloropropane	ug/L	ND	5.0	
2-Butanone (MEK)	ug/L	ND	25.0	
2-Chlorotoluene	ug/L	ND	5.0	
2-Hexanone	ug/L	ND	25.0	
4-Chlorotoluene	ug/L	ND	5.0	
4-Methyl-2-pentanone (MIBK)	ug/L	ND	25.0	
Acetone	ug/L	ND	100	
Acrolein	ug/L	ND	100	
Acrylonitrile	ug/L	ND	100	
Benzene	ug/L	ND	5.0	
Bromobenzene	ug/L	ND	5.0	
Bromochloromethane	ug/L	ND	5.0	
Bromodichloromethane	ug/L	ND	5.0	
Bromoform	ug/L	ND	5.0	
Bromomethane	ug/L	ND	5.0	
Carbon disulfide	ug/L	ND	10.0	
Carbon tetrachloride	ug/L	ND	5.0	
Chlorobenzene	ug/L	ND	5.0	
Chloroethane	ug/L	ND	5.0	
Chloroform	ug/L	ND	5.0	
Chloromethane	ug/L	ND	5.0	
cis-1,2-Dichloroethene	ug/L	ND	5.0	
cis-1,3-Dichloropropene	ug/L	ND	5.0	
Dibromochloromethane	ug/L	ND	5.0	

Date: 04/30/2008 04:17 PM

REPORT OF LABORATORY ANALYSIS

Page 9 of 14





Project: Valhi Pace Project No.: 5014193

METHOD BLANK: 158031

Associated Lab Samples: 5014193002

Parameter Units Result Limit Qualifiers Dibromomethane ug/L ND 5.0 Ethyl methacrylate ug/L ND 100 Ethylbenzene ug/L ND 5.0 Hexachloro-1,3-butadiene ug/L ND 5.0 Iodomethane ug/L ND 10.0 Isopropylbenzene (Cumene) ug/L ND 5.0 Methyl-tert-butyl ether ug/L ND 5.0 n-Butylbenzene (Cumene) ug/L ND 5.0 n-Butylbenzene ug/L ND 5.0 n-Butylbenzene ug/L ND 5.0 Naphthalene ug/L ND 5.0 P-Isopropyltoluene ug/L ND 5.0 sec-Butylbenzene ug/L ND 5.0 <t< th=""><th></th><th></th><th>Blank</th><th>Reporting</th><th></th></t<>			Blank	Reporting	
Dichlorodifluoromethane ug/L ND 5.0 Ethyl methacrylate ug/L ND 100 Ethylbenzene ug/L ND 5.0 Hexachloro-1,3-butadiene ug/L ND 5.0 Idodomethane ug/L ND 10.0 Isopropylbenzene (Cumene) ug/L ND 5.0 Methyl-tert-butyl ether ug/L ND 5.0 Methylene chloride ug/L ND 5.0 Methylene chloride ug/L ND 5.0 n-Butylbenzene chloride ug/L ND 5.0 n-Hexane ug/L ND 5.0 n-Hexane ug/L ND 5.0 n-Propylbenzene ug/L ND 5.0 Naphthalene ug/L ND 5.0 p-Isopropyltoluene ug/L ND 5.0 sec-Butylbenzene ug/L ND 5.0 Styrene ug/L ND 5.0 tert-Butylbenzene ug/L <th>Parameter</th> <th>Units</th> <th>Result</th> <th>Limit</th> <th>Qualifiers</th>	Parameter	Units	Result	Limit	Qualifiers
Ethyl methacrylate ug/L ND 100 Ethylbenzene ug/L ND 5.0 Hexachloro-1,3-butadiene ug/L ND 5.0 lodomethane ug/L ND 10.0 Isopropylbenzene (Cumene) ug/L ND 5.0 Methyl-tert-butyl ether ug/L ND 4.0 Methyl-tert-butyl ether ug/L ND 5.0 Methyl-tert-butyl ether ug/L ND 4.0 Methyl-tert-butyl ether ug/L ND 5.0 n-Butylbenzene chloride ug/L ND 5.0 n-Butylbenzene ug/L ND 5.0 n-Hexane ug/L ND 5.0 n-Propylbenzene ug/L ND 5.0 n-Propylbenzene ug/L ND 5.0 Naphthalene ug/L ND 5.0 p-Isopropyltoluene ug/L ND 5.0 sec-Butylbenzene ug/L ND 5.0 Styrene	Dibromomethane	ug/L	ND	5.0	
Ethylbenzene ug/L ND 5.0 Hexachloro-1,3-butadiene ug/L ND 5.0 lodomethane ug/L ND 10.0 Isopropylbenzene (Cumene) ug/L ND 5.0 Methyl-tert-butyl ether ug/L ND 5.0 Methylene chloride ug/L ND 5.0 n-Butylbenzene chloride ug/L ND 5.0 n-Butylbenzene ug/L ND 5.0 n-Butylbenzene ug/L ND 5.0 n-Hexane ug/L ND 5.0 n-Propylbenzene ug/L ND 5.0 n-Propylbenzene ug/L ND 5.0 Naphthalene ug/L ND 5.0 p-Isopropyltoluene ug/L ND 5.0 sec-Butylbenzene ug/L ND 5.0 Styrene ug/L ND 5.0 tert-Butylbenzene ug/L ND 5.0 Tetrachloroethene ug/L	Dichlorodifluoromethane	ug/L	ND	5.0	
Hexachloro-1,3-butadiene ug/L ND 5.0 lodomethane ug/L ND 10.0 Isopropylbenzene (Cumene) ug/L ND 5.0 Methyl-tert-butyl ether ug/L ND 4.0 Methylene chloride ug/L ND 5.0 n-Butylbenzene ug/L ND 5.0 n-Butylbenzene ug/L ND 5.0 n-Hexane ug/L ND 5.0 n-Propylbenzene ug/L ND 5.0 Naphthalene ug/L ND 5.0 Naphthalene ug/L ND 5.0 p-Isopropyltoluene ug/L ND 5.0 sec-Butylbenzene ug/L ND 5.0 set-Butylbenzene ug/L ND 5.0 Styrene ug/L ND 5.0 tert-Butylbenzene ug/L ND 5.0 Tetrachloroethene ug/L ND 5.0 Toluene ug/L ND 5.0 trans-1,2-Dichloroethene ug/L ND 5.0 trans-1,3-Dichloropropene ug/L ND 5.0 trans-1,4-Dichloro-2-butene ug/L ND 5.0 Trichloroethene ug/L ND 5.0 Trichlorofluoromethane ug/L ND 10.0 Trichlorofluoromethane	Ethyl methacrylate	ug/L	ND	100	
Iodomethane	Ethylbenzene	ug/L	ND	5.0	
Isopropy benzene (Cumene)	Hexachloro-1,3-butadiene	ug/L	ND	5.0	
Methyl-tert-butyl ether ug/L ND 4.0 Methylene chloride ug/L ND 5.0 n-Butylbenzene ug/L ND 5.0 n-Hexane ug/L ND 5.0 n-Propylbenzene ug/L ND 5.0 Naphthalene ug/L ND 5.0 p-Isopropyltoluene ug/L ND 5.0 sec-Butylbenzene ug/L ND 5.0 styrene ug/L ND 5.0 tert-Butylbenzene ug/L ND 5.0 tert-Butylbenzene ug/L ND 5.0 Tetrachloroethene ug/L ND 5.0 Tetrachloroethene ug/L ND 5.0 Toluene ug/L ND 5.0 trans-1,2-Dichloroethene ug/L ND 5.0 trans-1,3-Dichloropropene ug/L ND 5.0 trans-1,4-Dichloro-2-butene ug/L ND 5.0 Trichloroethene ug/L	Iodomethane	ug/L	ND	10.0	
Methylene chloride ug/L ND 5.0 n-Butylbenzene ug/L ND 5.0 n-Hexane ug/L ND 5.0 n-Propylbenzene ug/L ND 5.0 Naphthalene ug/L ND 5.0 p-Isopropyltoluene ug/L ND 5.0 sec-Butylbenzene ug/L ND 5.0 Styrene ug/L ND 5.0 tert-Butylbenzene ug/L ND 5.0 Tetrachloroethene ug/L ND 5.0 Tetrachloroethene ug/L ND 5.0 Toluene ug/L ND 5.0 trans-1,2-Dichloroethene ug/L ND 5.0 trans-1,3-Dichloropropene ug/L ND 5.0 trans-1,4-Dichloro-2-butene ug/L ND 5.0 Trichloroethene ug/L ND 5.0 Vinyl acetate ug/L ND 5.0 Vinyl chloride ug/L	Isopropylbenzene (Cumene)	ug/L	ND	5.0	
n-Butylbenzene ug/L ND 5.0 n-Hexane ug/L ND 5.0 n-Propylbenzene ug/L ND 5.0 Naphthalene ug/L ND 5.0 p-Isopropyltoluene ug/L ND 5.0 sec-Butylbenzene ug/L ND 5.0 Styrene ug/L ND 5.0 tert-Butylbenzene ug/L ND 5.0 Tetrachloroethene ug/L ND 5.0 Tetrachloroethene ug/L ND 5.0 Toluene ug/L ND 5.0 trans-1,2-Dichloroethene ug/L ND 5.0 trans-1,3-Dichloropropene ug/L ND 5.0 trans-1,4-Dichloro-2-butene ug/L ND 5.0 Trichloroethene ug/L ND 5.0 Trichlorofluoromethane ug/L ND 5.0 Vinyl acetate ug/L ND 10.0 Vinyl chloride ug/L	Methyl-tert-butyl ether	ug/L	ND	4.0	
n-Hexane ug/L ND 5.0 n-Propylbenzene ug/L ND 5.0 Naphthalene ug/L ND 5.0 p-Isopropyltoluene ug/L ND 5.0 sec-Butylbenzene ug/L ND 5.0 Styrene ug/L ND 5.0 tert-Butylbenzene ug/L ND 5.0 Tetrachloroethene ug/L ND 5.0 Toluene ug/L ND 5.0 trans-1,2-Dichloroethene ug/L ND 5.0 trans-1,3-Dichloropropene ug/L ND 5.0 trans-1,4-Dichloro-2-butene ug/L ND 100 Trichloroethene ug/L ND 5.0 Vinyl acetate ug/L ND 5.0 Vinyl acetate ug/L ND 10.0 Vinyl chloride ug/L ND 10.0 Xylene (Total) ug/L ND 10.0 4-Bromofluorobenzene (S) % <t< td=""><td>Methylene chloride</td><td>ug/L</td><td>ND</td><td>5.0</td><td></td></t<>	Methylene chloride	ug/L	ND	5.0	
n-Propylbenzene ug/L ND 5.0 Naphthalene ug/L ND 5.0 p-Isopropyltoluene ug/L ND 5.0 sec-Butylbenzene ug/L ND 5.0 Styrene ug/L ND 5.0 tert-Butylbenzene ug/L ND 5.0 Tetrachloroethene ug/L ND 5.0 Toluene ug/L ND 5.0 trans-1,2-Dichloroethene ug/L ND 5.0 trans-1,3-Dichloropropene ug/L ND 5.0 trans-1,4-Dichloro-2-butene ug/L ND 100 Trichloroethene ug/L ND 5.0 Trichlorofluoromethane ug/L ND 5.0 Vinyl acetate ug/L ND 10.0 Vinyl chloride ug/L ND 10.0 Xylene (Total) ug/L ND 10.0 4-Bromofluorobenzene (S) % 98 70-126 Dibromofluoromethane (S)	n-Butylbenzene	ug/L	ND	5.0	
Naphthalene ug/L ND 5.0 p-Isopropyltoluene ug/L ND 5.0 sec-Butylbenzene ug/L ND 5.0 Styrene ug/L ND 5.0 tert-Butylbenzene ug/L ND 5.0 Tetrachloroethene ug/L ND 5.0 Toluene ug/L ND 5.0 trans-1,2-Dichloroethene ug/L ND 5.0 trans-1,3-Dichloropropene ug/L ND 5.0 trans-1,4-Dichloro-2-butene ug/L ND 100 Trichloroethene ug/L ND 5.0 Trichloroethene ug/L ND 5.0 Vinyl acetate ug/L ND 5.0 Vinyl chloride ug/L ND 10.0 Vinyl chloride ug/L ND 10.0 Xylene (Total) ug/L ND 10.0 4-Bromofluorobenzene (S) % 98 70-126 Dibromofluoromethane (S)<	n-Hexane	ug/L	ND	5.0	
p-Isopropyltoluene ug/L ND 5.0 sec-Butylbenzene ug/L ND 5.0 Styrene ug/L ND 5.0 tert-Butylbenzene ug/L ND 5.0 Tetrachloroethene ug/L ND 5.0 Toluene ug/L ND 5.0 trans-1,2-Dichloroethene ug/L ND 5.0 trans-1,3-Dichloropropene ug/L ND 5.0 trans-1,4-Dichloro-2-butene ug/L ND 5.0 trans-1,4-Dichloroethene ug/L ND 5.0 trans-1,4-Dichloro-2-butene ug/L ND 5.0 Trichloroethene ug/L ND 5.0 Trichlorofluoromethane ug/L ND 5.0 Vinyl acetate ug/L ND 5.0 Vinyl acetate ug/L ND 5.0 Vinyl chloride ug/L ND 10.0 Vinyl chloride ug/L ND 10.0 Vinyl chloride ug/L ND 10.0 Viplene (Total) ug/L ND 10.0 4-Bromofluoromethane (S) % 98 70-126 Dibromofluoromethane (S) % 93 80-123	n-Propylbenzene	ug/L	ND	5.0	
sec-Butylbenzene ug/L ND 5.0 Styrene ug/L ND 5.0 tert-Butylbenzene ug/L ND 5.0 Tetrachloroethene ug/L ND 5.0 Toluene ug/L ND 5.0 trans-1,2-Dichloroethene ug/L ND 5.0 trans-1,3-Dichloropropene ug/L ND 5.0 trans-1,4-Dichloro-2-butene ug/L ND 100 Trichloroethene ug/L ND 5.0 Trichlorofluoromethane ug/L ND 5.0 Vinyl acetate ug/L ND 10.0 Vinyl chloride ug/L ND 10.0 Xylene (Total) ug/L ND 10.0 4-Bromofluorobenzene (S) % 98 70-126 Dibromofluoromethane (S) % 93 80-123	Naphthalene	ug/L	ND	5.0	
Styrene ug/L ND 5.0 tert-Butylbenzene ug/L ND 5.0 Tetrachloroethene ug/L ND 5.0 Toluene ug/L ND 5.0 trans-1,2-Dichloroethene ug/L ND 5.0 trans-1,3-Dichloropropene ug/L ND 5.0 trans-1,4-Dichloro-2-butene ug/L ND 100 Trichloroethene ug/L ND 5.0 Trichlorofluoromethane ug/L ND 5.0 Vinyl acetate ug/L ND 10.0 Vinyl chloride ug/L ND 2.0 Xylene (Total) ug/L ND 10.0 4-Bromofluorobenzene (S) % 98 70-126 Dibromofluoromethane (S) % 93 80-123	p-Isopropyltoluene	ug/L	ND	5.0	
tert-Butylbenzene ug/L ND 5.0 Tetrachloroethene ug/L ND 5.0 Toluene ug/L ND 5.0 trans-1,2-Dichloroethene ug/L ND 5.0 trans-1,3-Dichloropropene ug/L ND 5.0 trans-1,4-Dichloro-2-butene ug/L ND 100 Trichloroethene ug/L ND 100 Trichloroethene ug/L ND 5.0 Trichlorofluoromethane ug/L ND 5.0 Vinyl acetate ug/L ND 5.0 Vinyl chloride ug/L ND 10.0 Vinyl chloride ug/L ND 10.0 Vinyl chloride ug/L ND 10.0 A-Bromofluorobenzene (S) % 98 70-126 Dibromofluoromethane (S) % 93 80-123	sec-Butylbenzene	ug/L	ND	5.0	
Tetrachloroethene ug/L ND 5.0 Toluene ug/L ND 5.0 trans-1,2-Dichloroethene ug/L ND 5.0 trans-1,3-Dichloropropene ug/L ND 5.0 trans-1,4-Dichloro-2-butene ug/L ND 100 Trichloroethene ug/L ND 5.0 Trichlorofluoromethane ug/L ND 5.0 Vinyl acetate ug/L ND 10.0 Vinyl chloride ug/L ND 2.0 Xylene (Total) ug/L ND 10.0 4-Bromofluorobenzene (S) % 98 70-126 Dibromofluoromethane (S) % 93 80-123	Styrene	ug/L	ND	5.0	
Toluene ug/L ND 5.0 trans-1,2-Dichloroethene ug/L ND 5.0 trans-1,3-Dichloropropene ug/L ND 5.0 trans-1,4-Dichloro-2-butene ug/L ND 100 Trichloroethene ug/L ND 5.0 Trichlorofluoromethane ug/L ND 5.0 Vinyl acetate ug/L ND 10.0 Vinyl chloride ug/L ND 2.0 Xylene (Total) ug/L ND 10.0 4-Bromofluorobenzene (S) % 98 70-126 Dibromofluoromethane (S) % 93 80-123	tert-Butylbenzene	ug/L	ND	5.0	
trans-1,2-Dichloroethene ug/L ND 5.0 trans-1,3-Dichloropropene ug/L ND 5.0 trans-1,4-Dichloro-2-butene ug/L ND 100 Trichloroethene ug/L ND 5.0 Trichlorofluoromethane ug/L ND 5.0 Vinyl acetate ug/L ND 10.0 Vinyl chloride ug/L ND 2.0 Xylene (Total) ug/L ND 10.0 4-Bromofluorobenzene (S) % 98 70-126 Dibromofluoromethane (S) % 93 80-123	Tetrachloroethene	ug/L	ND	5.0	
trans-1,3-Dichloropropene ug/L ND 5.0 trans-1,4-Dichloro-2-butene ug/L ND 100 Trichloroethene ug/L ND 5.0 Trichlorofluoromethane ug/L ND 5.0 Vinyl acetate ug/L ND 10.0 Vinyl chloride ug/L ND 2.0 Xylene (Total) ug/L ND 10.0 4-Bromofluorobenzene (S) % 98 70-126 Dibromofluoromethane (S) % 93 80-123	Toluene	ug/L	ND	5.0	
trans-1,4-Dichloro-2-butene ug/L ND 100 Trichloroethene ug/L ND 5.0 Trichlorofluoromethane ug/L ND 5.0 Vinyl acetate ug/L ND 10.0 Vinyl chloride ug/L ND 2.0 Xylene (Total) ug/L ND 10.0 4-Bromofluorobenzene (S) % 98 70-126 Dibromofluoromethane (S) % 93 80-123	trans-1,2-Dichloroethene	ug/L	ND	5.0	
Trichloroethene ug/L ND 5.0 Trichlorofluoromethane ug/L ND 5.0 Vinyl acetate ug/L ND 10.0 Vinyl chloride ug/L ND 2.0 Xylene (Total) ug/L ND 10.0 4-Bromofluorobenzene (S) % 98 70-126 Dibromofluoromethane (S) % 93 80-123	trans-1,3-Dichloropropene	ug/L	ND	5.0	
Trichlorofluoromethane ug/L ND 5.0 Vinyl acetate ug/L ND 10.0 Vinyl chloride ug/L ND 2.0 Xylene (Total) ug/L ND 10.0 4-Bromofluorobenzene (S) % 98 70-126 Dibromofluoromethane (S) % 93 80-123	· · · · · · · · · · · · · · · · · · ·	ug/L			
Vinyl acetate ug/L ND 10.0 Vinyl chloride ug/L ND 2.0 Xylene (Total) ug/L ND 10.0 4-Bromofluorobenzene (S) % 98 70-126 Dibromofluoromethane (S) % 93 80-123		-	ND	5.0	
Vinyl chloride ug/L ND 2.0 Xylene (Total) ug/L ND 10.0 4-Bromofluorobenzene (S) % 98 70-126 Dibromofluoromethane (S) % 93 80-123	Trichlorofluoromethane	ug/L		5.0	
Xylene (Total) ug/L ND 10.0 4-Bromofluorobenzene (S) % 98 70-126 Dibromofluoromethane (S) % 93 80-123	Vinyl acetate	ug/L	ND	10.0	
4-Bromofluorobenzene (S) % 98 70-126 Dibromofluoromethane (S) % 93 80-123	•	ug/L			
Dibromofluoromethane (S) % 93 80-123		•			
()					
Toluene-d8 (S)	` '				
	Toluene-d8 (S)	%	98	80-116	

LABORATORY CONTROL SAMPLE: 158032

Parameter	Units	Spike Conc.	LCS Result	LCS % Rec	% Rec Limits	Qualifiers
1,1,1,2-Tetrachloroethane	ug/L		41.9	84	69-130	
1,1,1-Trichloroethane	ug/L	50	41.0	82	69-136	
1,1,2,2-Tetrachloroethane	ug/L	50	44.7	89	69-131	
1,1,2-Trichloroethane	ug/L	50	45.2	90	77-132	
1,1-Dichloroethane	ug/L	50	42.0	84	67-133	
1,1-Dichloroethene	ug/L	50	47.1	94	63-128	
1,1-Dichloropropene	ug/L	50	45.7	91	75-134	
1,2,3-Trichlorobenzene	ug/L	50	45.7	91	58-131	
1,2,3-Trichloropropane	ug/L	50	43.8	88	60-131	
1,2,4-Trichlorobenzene	ug/L	50	49.4	99	60-130	
1,2,4-Trimethylbenzene	ug/L	50	49.2	98	73-130	

Date: 04/30/2008 04:17 PM

REPORT OF LABORATORY ANALYSIS

Page 10 of 14







Project: Valhi
Pace Project No.: 5014193

LABORATORY CONTROL SAMPLE: Spike LCS LCS % Rec Parameter Units Conc. Result % Rec Limits Qualifiers 1,2-Dibromoethane (EDB) ug/L 50 41.8 84 75-126 1,2-Dichlorobenzene ug/L 50 43.8 88 76-124 50 39.6 79 69-139 1,2-Dichloroethane ug/L 43.0 1,2-Dichloropropane ug/L 50 86 76-129 97 74-130 1,3,5-Trimethylbenzene ug/L 50 48.6 1,3-Dichlorobenzene 50 46.1 92 76-125 ug/L 1,3-Dichloropropane 50 44.4 89 74-126 ug/L 50 44.0 88 75-122 1,4-Dichlorobenzene ug/L 47.2 94 53-144 2,2-Dichloropropane ug/L 50 2-Butanone (MEK) ug/L 250 356 143 47-189 2-Chlorotoluene ug/L 50 45.4 91 72-128 2-Hexanone ug/L 250 338 135 57-167 4-Chlorotoluene 50 45.9 92 73-124 ug/L 4-Methyl-2-pentanone (MIBK) ug/L 250 240 96 61-135 227 Acetone ug/L 250 567 30-170 L0 256 Acrolein ug/L 1000 2560 30-170 L3 1000 864 67-136 Acrylonitrile ug/L 86 50 44.0 88 78-127 Benzene ug/L Bromobenzene 50 43.1 86 62-139 ug/L 54.2 Bromochloromethane ug/L 50 108 54-162 Bromodichloromethane 50 39.3 69-133 ug/L 79 Bromoform ug/L 50 42.3 85 60-127 Bromomethane ug/L 50 65.9 132 30-170 Carbon disulfide 100 90.7 91 58-152 ug/L Carbon tetrachloride 44.9 90 62-143 ug/L 50 Chlorobenzene ug/L 50 43.0 86 75-123 Chloroethane ug/L 50 51.6 103 56-153 Chloroform 50 40.3 81 74-131 ug/L 53.5 35-147 50 107 Chloromethane ug/L 74-128 cis-1,2-Dichloroethene 50 44.6 ug/L 89 42.2 58-123 cis-1,3-Dichloropropene ug/L 50 84 Dibromochloromethane 50 41.9 ug/L 84 66-131 Dibromomethane ug/L 50 44.0 88 73-133 Dichlorodifluoromethane ug/L 50 48.9 98 30-170 Ethyl methacrylate ug/L 50 ND 84 59-138 Ethylbenzene ug/L 50 45.5 91 81-126 Hexachloro-1,3-butadiene ug/L 50 44.5 89 70-130 ug/L Iodomethane 100 187 187 41-170 L3 48.6 Isopropylbenzene (Cumene) ug/L 50 97 80-130 ug/L 100 89.5 Methyl-tert-butyl ether 89 66-147 Methylene chloride 50 46.9 94 ug/L 32-164 n-Butylbenzene 50 49.7 99 68-135 ug/L 46.6 93 n-Hexane ug/L 50 69-157 n-Propylbenzene ug/L 50 50.5 101 71-132 Naphthalene ug/L 50 38.8 78 61-135 p-Isopropyltoluene ug/L 50 48.8 98 66-131 50 50.7 101 73-130 sec-Butylbenzene ug/L

Date: 04/30/2008 04:17 PM

Styrene

REPORT OF LABORATORY ANALYSIS

45.8

92

74-128

50

ug/L

Page 11 of 14







Project: Valhi
Pace Project No.: 5014193

LABORATORY CONTROL SAMPLE: Spike LCS LCS % Rec Parameter Units Conc. Result % Rec Limits Qualifiers tert-Butylbenzene ug/L 50 44.2 88 63-117 Tetrachloroethene ug/L 50 41.7 83 60-119 Toluene ug/L 50 45.1 90 75-129 trans-1,2-Dichloroethene 50 44.9 90 71-126 ug/L 50 40.6 81 54-123 trans-1,3-Dichloropropene ug/L 47-141 trans-1,4-Dichloro-2-butene ug/L 50 42.1J 84 50 Trichloroethene 42.0 84 74-130 ug/L Trichlorofluoromethane 50 47.8 96 62-150 ug/L Vinyl acetate 200 147 73 41-145 ug/L Vinyl chloride ug/L 50 51.2 102 55-141 Xylene (Total) ug/L 150 140 94 76-132 4-Bromofluorobenzene (S) % 97 70-126 Dibromofluoromethane (S) % 94 80-123 Toluene-d8 (S) % 103 80-116

MATRIX SPIKE SAMPLE:	158033						
		5014193002	Spike	MS	MS	% Rec	
Parameter	Units	Result	Conc.	Result	% Rec	Limits	Qualifiers
1,1,1,2-Tetrachloroethane	ug/L	ND	50	36.8	74	55-131	
1,1,1-Trichloroethane	ug/L	ND	50	43.5	87	64-143	
1,1,2,2-Tetrachloroethane	ug/L	ND	50	.92J	2	64-142	
1,1,2-Trichloroethane	ug/L	ND	50	13.8	28	71-143	
1,1-Dichloroethane	ug/L	ND	50	44.4	89	68-139	
1,1-Dichloroethene	ug/L	ND	50	76.6	153	55-140 1	ld
1,1-Dichloropropene	ug/L	ND	50	46.5	93	66-140	
1,2,3-Trichlorobenzene	ug/L	ND	50	45.9	89	33-140	
1,2,3-Trichloropropane	ug/L	ND	50	40.8	82	58-133	
1,2,4-Trichlorobenzene	ug/L	ND	50	45.9	90	28-140	
1,2,4-Trimethylbenzene	ug/L	ND	50	48.6	96	39-146	
1,2-Dibromoethane (EDB)	ug/L	ND	50	42.2	84	67-134	
1,2-Dichlorobenzene	ug/L	ND	50	44.2	88	48-137	
1,2-Dichloroethane	ug/L	ND	50	41.2	82	63-148	
1,2-Dichloropropane	ug/L	ND	50	44.2	88	70-136	
1,3,5-Trimethylbenzene	ug/L	ND	50	48.4	96	39-145	
1,3-Dichlorobenzene	ug/L	ND	50	45.2	90	40-143	
1,3-Dichloropropane	ug/L	ND	50	43.7	87	65-133	
1,4-Dichlorobenzene	ug/L	ND	50	42.6	85	38-142	
2,2-Dichloropropane	ug/L	ND	50	48.0	96	35-157	
2-Butanone (MEK)	ug/L	ND	250	415	166	62-132	
2-Chlorotoluene	ug/L	ND	50	45.7	91	44-143	
2-Hexanone	ug/L	ND	250	375	150	61-141	
4-Chlorotoluene	ug/L	ND	50	45.7	91	43-140	
4-Methyl-2-pentanone (MIBK)	ug/L	ND	250	248	99	57-135	
Acetone	ug/L	ND	250	683	273	30-170	
Acrolein	ug/L	ND	1000	2650	265	30-170	
Acrylonitrile	ug/L	ND	1000	860	86	66-137	
Benzene	ug/L	ND	50	45.9	92	63-141	

Date: 04/30/2008 04:17 PM

REPORT OF LABORATORY ANALYSIS

Page 12 of 14





Project: Valhi Pace Project No.: 5014193

MATRIX SPIKE SAMPLE:	158033						
		5014193002	Spike	MS	MS	% Rec	
Parameter	Units	Result	Conc.	Result	% Rec	Limits	Qualifiers
Bromobenzene	ug/L	ND	50	43.9	88	57-128	
Bromochloromethane	ug/L	ND	50	57.6	115	65-157	
Bromodichloromethane	ug/L	ND	50	30.2	60	63-135	
Bromoform	ug/L	ND	50	39.5	79	58-124	
Bromomethane	ug/L	ND	50	64.0	128	30-170	
Carbon disulfide	ug/L	ND	100	82.6	83	46-162	
Carbon tetrachloride	ug/L	ND	50	47.2	94	54-145	
Chlorobenzene	ug/L	ND	50	43.2	86	56-133	
Chloroethane	ug/L	ND	50	70.2	140	54-157	
Chloroform	ug/L	ND	50	42.0	84	67-134	
Chloromethane	ug/L	ND	50	65.3	131	36-137	
cis-1,2-Dichloroethene	ug/L	ND	50	47.0	93	65-132	
cis-1,3-Dichloropropene	ug/L	ND	50	40.3	81	46-121	
Dibromochloromethane	ug/L	ND	50	34.4	69	64-124	
Dibromomethane	ug/L	ND	50	46.1	92	67-144	
Dichlorodifluoromethane	ug/L	ND	50	54.4	109	30-163	
Ethyl methacrylate	ug/L	ND	50	ND	0	52-140	
Ethylbenzene	ug/L	ND	50	47.7	93	44-151	
Hexachloro-1,3-butadiene	ug/L	ND	50	44.7	88	30-145	
lodomethane	ug/L	ND	100	150	150	28-168	
Isopropylbenzene (Cumene)	ug/L	ND	50	49.9	100	40-148	
Methyl-tert-butyl ether	ug/L	ND	100	93.1	93	52-156	
Methylene chloride	ug/L	ND	50	53.5	105	46-154	
n-Butylbenzene	ug/L	ND	50	48.6	97	27-153	
n-Hexane	ug/L	ND	50	48.0	96	32-176	
n-Propylbenzene	ug/L	ND	50	50.9	102	40-148	
Naphthalene	ug/L	ND	50	40.0	79	44-138	
p-Isopropyltoluene	ug/L	ND	50	47.8	95	34-146	
sec-Butylbenzene	ug/L	ND	50	51.1	102	38-150	
Styrene	ug/L	ND	50	46.6	93	38-141	
tert-Butylbenzene	ug/L	ND	50	45.1	90	32-133	
Tetrachloroethene	ug/L	ND	50	41.4	81	25-146	
Toluene	ug/L	ND	50	45.3	89	59-142	
trans-1,2-Dichloroethene	ug/L	ND	50	46.5	93	60-137	
trans-1,3-Dichloropropene	ug/L	ND	50	39.9	80	43-117	
trans-1,4-Dichloro-2-butene	ug/L	ND	50	40.4J	81	44-139	
Trichloroethene	ug/L	22.8	50	105	163	61-137	
Trichlorofluoromethane	ug/L	ND	50	49.8	100	53-162	
Vinyl acetate	ug/L	ND	200	28.5	14	24-132	
Vinyl chloride	ug/L	ND	50	53.2	106	51-144	
Xylene (Total)	ug/L	ND	150	150	95	44-152	
4-Bromofluorobenzene (S)	%				99	70-126	
Dibromofluoromethane (S)	%				32	80-123 \$	32
Toluene-d8 (S)	%				102	80-116	

Date: 04/30/2008 04:17 PM

REPORT OF LABORATORY ANALYSIS





QUALIFIERS

Project: Valhi
Pace Project No.: 5014193

DEFINITIONS

DF - Dilution Factor, if reported, represents the factor applied to the reported data due to changes in sample preparation, dilution of the sample aliquot, or moisture content.

ND - Not Detected at or above adjusted reporting limit.

J - Estimated concentration above the adjusted method detection limit and below the adjusted reporting limit.

MDL - Adjusted Method Detection Limit.

S - Surrogate

1,2-Diphenylhydrazine (8270 listed analyte) decomposes to Azobenzene.

Consistent with EPA guidelines, unrounded data are displayed and have been used to calculate % recovery and RPD values.

LCS(D) - Laboratory Control Sample (Duplicate)

MS(D) - Matrix Spike (Duplicate)

DUP - Sample Duplicate

RPD - Relative Percent Difference

NC - Not Calculable.

Pace Analytical is NELAP accredited. Contact your Pace PM for the current list of accredited analytes.

SAMPLE QUALIFIERS

Sample: 5014193002

[1] Sample was prepared by SPLP Method 1312.

ANALYTE QUALIFIERS

Tu inditiple compounds are outside acceptance limits, refer to EOO for data acceptability and system control. Jet 4/20/00	1d	Multiple compounds are outside acceptance limits	 refer to LCS for data acceptability 	v and system control. JLF 4/28/08.
---	----	--	---	------------------------------------

- L0 Analyte recovery in the laboratory control sample (LCS) was outside QC limits.
- L3 Analyte recovery in the laboratory control sample (LCS) exceeded QC limits. Analyte presence below reporting limits in associated samples. Results unaffected by high bias.
- S2 Surrogate recovery outside laboratory control limits due to matrix interferences (confirmed by similar results from sample re-analysis).

Date: 04/30/2008 04:17 PM



CAMPS W Total No. of Bottles/ Containers CHAIN-OF-CUSTODY RECORD Page _ 200 Remarks Other g 122,08 Time – Time. Time -**ANALYSIS / METHOD / SIZE** ☐ Lab Courier Date 4 Date_ Date_ Date-SPECIFY Laboratory Task Order No./P.O. No._ □ Common Carrier. Organization: __ Organization: . Organization: Organization: A = Air 0811/80181/1-Date/Time Sampled 1ARCADES Project Location Clar Fordsville IN = Solid; **本In Person** Matrix Project Manager 5 Cosgrava Project Number/Name_16/h; L = Liquid; Special Instructions/Remarks: **A** ARCADIS Sample ID/Location Delivery Method: Laboratory Pace Relinquished by: 🚽 Relinquished by:_ Received by: — COMP - 8 Sample Matrix: Received by:

Total ત AG 05.17/01

Yes No N/A

Seal Intact?

Yes No N/A Seal Intact?

Sample Condition Upon Receipt ace Analytical` **Client Name:** Project # 6014/9 Pace Other Courier: Fed Ex UPS USPS Grain Commercial Custody Seal on Cooler/Box Present: ☐ yes Do Seals intact: Bubble Bags Packing Materiai: Bubble Wrap ☐ None 、 Type of ice: (Wet) Samples on ice, cooling process has begun Thermometer Used Blue Date and Initials of person examining Biological Tissue is Frozen: Yes Mo **Cooler Temperature** contents: Temp should be above freezing to 6°C Comments: DYES DNO DNA 1. Chain of Custody Present: Ves DNO DNA Chain of Custody Filled Out: □N/A Chain of Custody Relinquished: TYes No IN/A 4, Sampler Name & Signature on COC: Samples Arrived within Hold Time: ☐Yes □No □N/A | 5, □Yes □No ₽N/A 6. Short Hold Time Analysis (<72hr): UNIA 17. Rush Turn Around Time Requested: ☐Yes ☐No DYES DNO DNA Sufficient Volume: DYES DNO DN/A Correct Containers Used: ☑Yes □Ne ¹□n/a -Pace Containers Used: ☐Yes □No □N/A 10. Containers Intact: ☐Yes ☐No -☐N/A Filtered volume received for Dissolved tests ĺ11. ØYes □No □N/A Sample Labels match COC: Includes date/time/ID/Analysis All containers needing preservation have been checked. ☐Yes ☐No ₽N/A 13. All containers needing preservation are found to be in ☐Yes ☐No DAN/A compliance with EPA recommendation. Lot # of added Initial when ☐Yes ☐NO completed exceptions: VOA, coliform, TOC, O&G, WI-DRO (water) preservative ☐Yes ☐No **□**N/A Samples checked for dechlorination: □Yes □No **□**N/A Headspace in VOA Vials (>6mm): ☐Yes ☐No **₽N/A** Trip Blank Present: 16 □Yes □No □ NL/A Trip Blank Custody Seals Present

Client Notification/ Resolution:

Person Contacted:

Comments/ Resolution:

Date/Time:

Pace Trip Blank Lot # (if purchased):

Project Manager Review:

Note: Whenever there is a discrepancy affecting North Carolina compliance samples, a copy of this form will be sent to the North Carolina DEHNR Certification Office (i.e. out of hold, incorrect preservative, out of temp, incorrect containers)

Date:

Evaluation of Quicklime Application as a Method of Treating Contaminated Soils

Presented at:

The TRB Committee on Waste Management's Environmental Stewardship in Transportation Through Waste Management, Materials Reuse and EMS Conference

July 18, 2005

UF Principal Investigators: Tim Townsend and Angela Lindner UF Graduate Assistants: Jae Hac Ko, Aaron Jordan, and Kim Cochran FDOT Participants: Curtis Barnes, Terry Zinn, and Louis Reis



Motivation

- A site remediation project conducted by the Florida Department of Environmental Protection found that the addition of quicklime to the site's contaminated soils greatly reduced soil organic contaminant concentrations.
- More information was needed on what happened, why, and whether this technique might have application at other sites.

Fairbanks

- Contaminated FDOT site in Fairbanks, Florida where the Bureau of Materials Research (BMR) laboratory conducted tests to determine if asphalt paving materials met specifications
- Solvents (including TCE) were originally used to dissolve the asphalt
- Wastes from the BMR lab were disposed on-site


Fairbanks

- After original remediation, more source contamination was found in 1998
- DNAPL was found approximately 35 feet below ground surface
- Soils were excavated, processed and stored in a lined pond for vacuum extraction

Fairbanks

- Quicklime was added to amend the soils physical properties as it became more clayey at 32 feet bgs
- Heat was generated from the exothermic reaction
- The contaminants of concern were then below limits after the reaction
- Quicklime was used to treat the rest of the contaminated soils





Lined Pond Tused for Soil

Treatment

Excavation of Contamination
Source Areas

Soli Processing Area

FDOT Office

Possible Contaminant Reduction Mechanisms

- Volatilization
 - $-CaO + H_2O \rightarrow Ca(OH)_2 + heat$
- Abiotic reaction
 - Destructive adsorption
- Encapsulation/adsorption
 - Entrapment of the contaminants in the soil-Ca(OH)₂ matrix

Sedlak et al., 1991

Research Objectives

- Determine the <u>dominant mechanism</u> of contaminant removal by quicklime treatment.
- Evaluate the <u>conditions and parameters that</u> <u>impact</u> the treatment process.
- Assess the <u>feasibility</u> of quicklime addition as a cost-effective, efficient and regulatorypermissible treatment scheme.
- Evaluate the application of the technology at <u>other contaminated sites</u>.

Applicability

- If quicklime application is found to be a feasible method of remediation, this research will provide guidance on how DOT can use it at other sites
- Including:
 - Which pollutants this treatment is effective for
 - Necessary site conditions for effectiveness
 - Amount of quicklime needed
 - Mixing procedure
 - Regulatory guidance
 - Costs

Current Activities


- Laboratory Research
 - Identify the treatment mechanism
 - Determine the amount volatilized by examining the air above the soil
 - Determine the amount treated by examining the amount of chloride left in the soil
 - Determine the amount of contaminant left in the soil
 - Perform a mass balance of the contaminants for the quicklime reaction
 - Ensure that all of the contaminant is accounted for
- Feasibility Study
 - Investigate possible regulatory restrictions

Two Laboratory Tests

- Batch tests
 - Testing the reaction of quicklime and VOCs in a closed system
 - Quick way to look at the results before and after the reaction
- Real-time tests
 - Air flows through the system
 - Allows analysis throughout the entire reaction to determine when treatment occurs

Initial Batch Experiments


- Initial Apparatus
 - 40 mL EPA VOC vials
- Media
 - 20 g sand and 1g or 2g water
- Contaminants
 - 100 L cis-dichloroethylene (cis-DCE) or trichloroethylene (TCE)
- Analyses
 - Volatile Organic Compounds (VOCs):
 - Gas Chromatography/Mass Spectrometry (GC/MS), Gas Chromatography/ Electron Capture Detector (GC/ECD)
 - Chloride ions: Ion
 Chromatography (IC)




VOCs are able to escape when quicklime is added! New apparatus needed to prevent any VOC loss.

Newly Designed Vial


- Minimizes the loss of VOCs during quicklime addition
- Completely closed system that does not require opening when adding quicklime
- Larger volume (~100mL) than that of the EPA vials (40 mL)
- Secure caps



Before and After: Quicklime Treatment in the Laboratory Experiments




Before




After

Extraction of VOCs from Treated Soils (Batch Tests)




- After the reaction is complete, air is pumped through the vessel and into three vials that contain methanol, which trap gas-phase chemicals from the headspace of the vessel.
- The vessels are heated after the reaction promote the evaporation of VOCs for analysis.

Real-Time Experiments




- Air is pumped through the vessels throughout the reaction during the realtime experiments. This allows the volatilization rate to be measured.
- Temperatures are monitored throughout the experiments to determine the highest temperature reached during the reaction.

Temperatures During the Reaction



- The temperatures during the reaction varied with moisture content and the amount of CaO. The temperature peaked quickly a few minutes after treatment.
- The temperatures ranged from 50°C to 184°C in the selected mole ratios of CaO to H₂O.

Amount of Chloride in the Soil After Treatment with Various Amounts of Quicklime and Water



The chloride concentration dramatically increased with higher ratios of CaO to H₂O in the 10% MC contaminated soil, but chloride concentrations in soils containing 5% MC showed relatively smaller increases.

Preliminary Conclusions

- The treatment of cis-DCE or TCEcontaminated soil with quicklime using laboratory tests has shown a decrease in the concentrations of the contaminants.
- The presence of chloride in the treated soils indicates that at least some TCE and DCE destruction is occurring.
- Chloride in the treated soil increased as the amount of quicklime and water added increased.

Preliminary Conclusions

- Regulatory Concerns:
 - The amount that is volatilized and not destroyed
 - Affect of the reaction products on the environment
- Our experiments must be able to fully account for all chemicals before and after the reaction
- One commercial product similar to quicklime has been approved by the FDEP for use, but its exact chemical composition and reaction mechanism is unknown

Future Activities

Continue batch and real-time tests:

- Refine procedure for various factors (soil properties, chemicals, and mixing properties)
- Replicate the contaminated soil from Fairbanks and use in experiments

Perform Larger-Scale Experiments

- Test the effectiveness of quicklime as a treatment of contaminated soils using a larger vessel to attempt to replicate real-world conditions
- Evaluate the application of the technology with different types of contaminated soils
- Investigate and compare results to laboratory studies

Contact Information

University of Florida:

Tim Townsend ttown@ufl.edu (352) 392-0846

Angela Lindner <u>alind@eng.ufl.edu</u> (352) 846-3033

Graduate Students:

Jae Hac Ko jaehacko@ufl.edu

Aaron Jordan
aajordan@ufl.edu

Kim Cochran kcochran@ufl.edu

(352) 846-3035

Contact Information

FDOT:

Curtis Barnes
cbarnes@wrsie.com
(352) 381-4300

Terry Zinn terry.zinn@dot.state.fl.us (386) 758-3708 Louis Reis louis.reis@dot.state.fl.us (850) 410-5882

1	·
2	
3	
4	Ex-Situ Treatment of Dense Non-Aqueous Phase Liquids
5	Using Calcium Oxide (Quick Lime).
6	
7	
8	Wm. Gordon Dean, PE
9	WRS Infrastructure & Environment, Inc.
10	625 E. Tennessee Street, Suite 100
11	Tallahassee, FL 32308
12	Telephone: (850) 531-9860
13	Fax: (850) 531-9866
14	E-Mail: gdean@wrsie.com
15	
16	
17	19 th Annual Conference on Soils, Sediments and Water
18	Northeast Regional Environmental Public Health Center
19	University of Massachusetts
20	Amherst, Massachusetts
21	October 20 – 23, 2003

Open excavation was selected to remove dense, non-aqueous phase liquids (DNAPLs)

identified by previous assessment activities at the FDOT Fairbanks Disposal Pit in

Gainesville, Florida. The DNAPLs resulted from the disposal of asphalt testing residue

and consisted primarily of trichloroethene and 1,1,1-trichloroethane. Presumptive and

visual evidence of DNAPLs had been found in three areas of the site. Excavation of all

three areas was conducted and DNAPLs were observed as predicted.

The original plan called for ex-situ vacuum extraction of all contaminated soils. All potentially contaminated soils—were to be processed through a rotary trommel, staged in 100 cubic yard piles, and sampled for analytical testing. Due to the increasing clay content of the deeper soils, the trommel could not be used for most of the potentially contaminated soils. Quick lime was mixed into the soils at an approximate 5% ratio to improve the soil handling characteristics. The combination of the heating and chemical reaction between the soils and the lime removed the contaminants to below the leachability soil cleanup target levels, and all contaminated soils were ultimately treated by mixing with quick lime. The soils treated with quick lime were returned to the excavation to stabilize the slopes after confirmation soil samples verified the treatment goals had been reached. Approximately 10,000 cubic yards of soil were treated with quick lime, saving several million dollars as compared to off-site disposal.

Keywords: DNAPL, calcium oxide, quick lime, ex-situ soil treatment

SITE BACKGROUND

$\overline{}$	

The Fairbanks Disposal Pit (FDP) is an abandoned sand borrow pit, approximately 10 acres in size, in Fairbanks, Alachua County, Florida. The FDP is owned by the Florida Department of Environmental Protection (FDEP) and operated by the Florida Department of Transportation (FDOT). FDOT purchased the site in 1956 as a borrow source for sand and clay for road construction. Beginning in 1956, the site was used to dispose of waste and topsoil collected from roadsides, demolition debris, and construction debris. Waste generated by the FDOT's Bureau of Materials Research (BMR) Laboratory was also collected and disposed at the FDP. Disposal activities continued until 1982. No records

exist to document the quantity of hazardous wastes disposed during site operations.

The wastes derived from the BMR Laboratory included chemicals used in laboratory testing. A major portion of their work is to test asphalt paving materials to determine if they meet FDOT specifications. From 1956 until approximately 1961, carbon tetrachloride was the solvent used to dissolve asphalt samples. In 1961, carbon tetrachloride was replaced by the solvent 1,1,1-trichloroethane. In 1980, the Abson recovery process began to be used to dissolve the asphalt samples. Benzene was the solvent used in this process until 1981, when trichloroethene was substituted.

Between 1956 and 1978, waste solvents were recycled after distillation in a solvent still.

The still was closed in 1978 when it was identified as a fire hazard. Information regarding disposal of waste from the distillation unit could not be found. During removal

1 activities conducted in 1983, a total of 1,046 drums were excavated from the pit area. In

2 addition to the initial drum removal in 1983, further excavation at the site in 1990

removed 345 drums. An additional 35 drums were removed during closure activities in

1994 and 1995. In addition to disposal of drummed wastes, liquid wastes were reportedly

5 poured directly into trenches on site.

6

7

8

9

10

11

12

13

14

15

16

17

18

19

20

21

22

23

3

4

WRS Infrastructure & Environment, Inc. (WRS) was retained by FDOT in January 1994 to complete the physical closure activities in response to a CERCLA Administrative Order. Following soil excavation activities, WRS was tasked with designing and installing groundwater treatment systems to address groundwater contamination identified in four aquifers that underlie FDP. Groundwater treatment systems for all four aquifers were installed and started up between December 1995 and April 1996. In 1998 it was noted that the influent concentration in two surficial groundwater recovery trenches closest to the 10-acre site were not decreasing, suggesting a source of contamination was still present. A GeoprobeTM investigation was conducted in 1999 in an effort to assess possible sources contributing to the dissolved phase contaminant concentrations observed in the recovery trenches. WRS initiated direct push investigations on the modified RCRA cap, downgradient of the cap, and along the horizontal recovery trenches. Additional assessments using a membrane interface probe, a RotasonicTM drill rig, and extensive soil sampling by the University of Waterloo were conducted in 2000. Presumptive evidence of dense, non-aqueous phase liquids (DNAPL), defined as groundwater concentrations greater than 1% of the solubility limit, was found in four areas under the northern half of the 10-acre site. Concentrations as

- 1 high as 1,200,000 µg/l of trichloroethene were detected and DNAPL was visually
- 2 identified in three of these areas. The DNAPL was located on top of, and diffused into, a
- 3 clay layer located approximately 35 to 40 feet below land surface.

4

- 5 Based on the findings of additional assessment activities, FDOT elected to proceed with
- 6 physical removal of soils that were possibly acting as continuing contaminant sources.
- 7 WRS's scope of work included the following proposed remediation activities:

8

- Removal of the clean overburden (land surface to 30 feet below land surface)
- Dewatering using horizontal dewatering trenches and sump pumps
- Excavation of potentially contaminated soils below a depth of 30 feet
- Power screening these soils using a rotary trammel to remove any debris
- Sampling and segregating clean and contaminated soils
- Ex-situ vacuum extraction of contaminated soils in an existing, lined storm water
- pond pond
- Addition of 5% calcium oxide (quick lime) as needed to improve the soil handling characteristics of clayey soils that were expected to be encountered at depth.

18

- 19 The goal of the remediation was to remove all soils exceeding the leachability soil
- 20 cleanup target levels in Chapter 62-777, Florida Administrative Code. The target levels
- 21 for the contaminants of concern were benzene (7 μg/kg), 1,1-dichloroethene (60 μg/kg),
- trichloroethene (30 μ g/kg), and 1,1,1-trichloroethane (1,900 μ g/kg).

QUICK LIME PROPERTIES

1	

1

- 3 Calcium oxide (quick lime) is a white crystalline solid manufactured by heating
- 4 (calcining) limestone, dolomite, coral, oyster shells, or chalk (which are all mainly
- 5 calcium carbonate) to drive off carbon dioxide. More than 90% of the lime produced in
- 6 the United States is used for basic or industrial chemistry. The primary uses are (Kirk-
- 7 Othmer 1991a, b; Budavari, 1986):

8

- steel manufacture,
- metallurgy,
- 11 air pollution control,
- water and sewage wastewater treatment,
- cement and mortar,
- chemical manufacturing,
- glass and paper manufacturing,
- sugar refining.

- 18 Calcium oxide is also used frequently in the construction industry for soil drying, soil
- 19 modification, and soil stabilization. Quick lime reacts with water to produce heat (as
- 20 high as 800° C) and calcium hydroxide (hydrated lime). When applied to wet soils or
- 21 mud, the reaction consumes approximately 30% water by weight plus removes additional
- 22 water as steam and provides dry solids for stability. The most dramatic soil
- 23 modifications occur in clay soils of moderate to high plasticity. Modification occurs

- 1 because the calcium cations supplied by the lime replace the cations normally present on
- 2 the surface of the clay mineral. The clay surface mineralogy is permanently altered and
- 3 the clay soils and changed to silts, producing the following benefits (Little, 1999):

4

- 5 Plasticity reduction
- Reduction in moisture-holding capacity (drying)
- 7 Swell reduction
- Improved stability

9

- 10 Highly plastic clays can be immediately and permanently changed to low plasticity silts
- 11 using quick lime. This was the reason quick lime was proposed to amend the soil
- handling properties of the clays expected to be found at depth at the FDP site.

13

- 14 From an environmental standpoint, calcium oxide is benign. The US Food and Drug
- Administration has affirmed that calcium oxide is generally recognized as safe as a direct
- human food ingredient. It may be used in food with no limitation other than current good
- 17 manufacturing practice. However, working with quick lime does present some
- 18 difficulties. It will react with any moisture, including sweat, eyes, and lung tissue so
- 19 adequate personnel protection is essential. It is also incompatible with many organics,
- 20 halogens, acids, and combustible materials.

SOIL REMEDIATION USING QUICK LIME

Excavated soil from below 32 feet at the FDP site demonstrated increasing clay content		
with depth. As the clay content increased, the rotary trommel became unable to		
effectively process the soils. As proposed in the original work plan, quick lime was		
added to improve the materials handling. The objective was to modify the clays into non-		
cohesive silts that could be processed by the trommel. Quick lime was mixed with the		
soils with a large road tiller to amend the soil for treatment. Approximately 5% by		
volume quick lime was added to the clayey soils. The reaction of the quick lime with the		
soil moisture generated significant amounts of heat. In addition, quick lime chemically		
reacts with many organics. Because the contaminants of concern were volatile organics,		
WRS sampled the soils after addition of the quick lime to determine the effect, if any, of		
the quick lime addition. Analytical testing of the soils after mixing with the quick lime		
demonstrated that the target levels had been achieved and that no further treatment was		
required. Perimeter air sampling did not detect any chlorinated solvents during the		
treatment process. Leaching tests were also conducted on the treated soils to determine if		
the quick lime was somehow masking the chlorinated solvents during the soil analyses.		
No contaminants were detected in the leachate samples. It was concluded that the soil		
remediation resulted from volatilizing the chlorinated compounds by the heat of reaction		
between the quick lime and water, possibly combined with a direct chemical reaction		
with either the halogens or the organic compounds.		

1 The soil processing procedure was then modified by staging all potentially contaminated 2 soils in one large pile in the processing area. Soils containing visible DNAPL were 3 treated in the excavation by mixing in quick lime with a backhoe prior to removal. All 4 potentially contaminated soils were placed in the lined soil treatment area in 18-inch lifts. 5 The quick lime was delivered in 2,000 pound supersacks which have a discharge chute 6 built into the bottom. A backhoe was used to pick up the supersacks and spread the quick 7 lime over the soils to be treated. The quick lime was then mixed into the soils using a 8 large road tiller. The treated soils were stockpiled and sampled. A total of 569 soil 9 samples were sampled from the soil processing area. All soils were ultimately classified 10 as clean although some soils required additional treatment before a clean status was 11 achieved. Soil analytical results initially categorized as contaminated (above the 12 leachability soil cleanup target levels), per on-site mobile laboratory results, were re-13 processed with quick lime. Clean soil was hauled to the clean soil stockpile. No soils 14 exceeding the leachability standards left the processing area.

15

16

17

18

Soils from below approximately 35 feet, soils previously placed in the lined pond, and sediments from the dewatering equipment were processed in this manner. Approximately 11,500 cubic yards of contaminated soils were treated with the guick lime.

19

20

21

22

23

Once the planned excavation was completed, floor and wall samples were taken in the excavation to confirm that all contaminated or potentially contaminated material had been removed and that only clean, undisturbed material remained. If the confirmation soil samples indicated values exceeding the leachability levels, an additional ten foot by

- 1 ten foot area around the location was excavated an additional two feet deep. These two
- 2 foot intervals continued until the confirmation samples were below leachability levels.
- 3 As the excavation activities continued, it was apparent that source areas would need to be
- 4 excavated much deeper than the initial 37 feet. The final excavation depth reached 49
- 5 feet below land surface in one area of the site. The excavation boundaries were also
- 6 extended further west and north based on the confirmation sample results.

1 COST

2

The delivered cost of the quick lime was approximately \$200 per 2,000 pound supersack. 3 4 Using a 5% by volume mixture resulted in a material cost of approximately \$10 per cubic 5 The multiple soil handing steps dictated by the site constraints added yard. 6 approximately \$20 per cubic yard in handling and processing costs. The total cost to treat the contaminated soils to the leachability target levels was approximately \$30 per cubic 7 8 yard, or a total of \$350,000 for the approximately 11,500 cubic yards of treated soils. 9 These costs do not include the cost of clean overburden removal, dewatering, or 10 treatment of the dewatering discharge. Compared to an off-site transportation and 11 disposal cost of \$250 to \$300 per ton, a savings of \$2.5 to \$3 million was realized. Any 12 potential liability from the off-site disposal was also eliminated.

CONCLUSIONS

1

3 Calcium oxide (quick lime) was used to successfully remediate 11,500 cubic yards of 4 soils contaminated with chlorinated solvents and DNAPLs for a unit cost of 5 approximately \$30 per cubic yard. The soils were successfully treated to the leachability 6 soil cleanup target levels in Chapter 62-777, Florida Administrative Code and to non-7 detectable concentrations in most cases. The treatment mechanism is most likely a 8 combination of heat to vaporize the volatile contaminants and a direct chemical reaction 9 with the quick lime. Further research is needed to identify the exact mechanisms. The 10 cost savings as compared to off-site transportation and disposal was \$2.5 to \$3 million 11 and any potential liability from the off-site disposal was eliminated.

1	REFERENCES
2	
3	Aldrich Chemical, Inc. MSDS Safety Information for Calcium Oxide; February 10, 1992
4	
5	Ash Grove Cement Co. MSDS for Calcium Oxide
6	
7	Budaveri, S; Calcium Oxide; The Merck Index., 11th Edition, 1989
8	
9	Calcium Oxide - Crops; National Organic Standards Board Technical Advisory Panel
10	Review; Compiled by OMRI for the USDA National Organic Program; April 4, 2002
11	
12	Fisher Scientific, Inc. MSDS for Calcium Oxide
13	
14	Hazardous Substance Fact Sheet for Calcium Oxide; New Jersey Department of Health
15	and Senior Services
16	
17	Kirk-Othmer, Kroschwitz, Howe-Grant, eds; Calcium Compounds; Wiley Interscience
18	Publ.; 1991a
19	
20	Kirk-Othmer, Kroschwitz, Howe-Grant, eds; Vol. 15 Lime and Limestone, Encyclopedia
21	of Chemical Technology, 4th edition; Wiley Interscience Publ.; 1991b
22	
23	Lime Dries Un Mud. National Lime Association

March 2001